Package 'a4Preproc'

November 11, 2026

Type Package

Title Automated Affymetrix Array Analysis Preprocessing Package

Version 1.60.0

Date 2020-10-14

Description Utility functions to pre-
process data for the Automated Affymetrix Array Analysis set of packages.

Imports BiocGenerics, Biobase

Suggests ALL, hgu95av2.db, knitr, rmarkdown

License GPL-3

biocViews Microarray, Preprocessing

RoxygenNote 7.1.1

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/a4Preproc

git_branch RELEASE_3_23

git_last_commit 80653a5

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Willem Talloen [aut],
Tobias Verbeke [aut],
Laure Cougnaud [cre]

Maintainer Laure Cougnaud <laure.cougnaud@openanalytics.eu>

Contents

addGeneInfo 2

Index **4**

addGeneInfo *Utility Function to Add Annotation to existing ExpressionSet Objects*

Description

Adds appropriate featureData, similar to the metadata added in the pipeline script, to the ExpressionSet object.

Usage

```
addGeneInfo(eset, annotationLibrary = NULL)
```

Arguments

`eset`	ExpressionSet object for to which one wants to add additional annotation information
`annotationLibrary`	Annotation Library to use. Must be specified when working with Entrez gene IDs. In this case, one can make use of the JnJ annotation packages such as `hgu133plus2hsentrezgJnJ`. If not specified, the annotation of the package will be automatically requested with `annotation()` of the expressionSet object `eset` and then Affymetrix probe set IDs are expected in `featureNames`

Details

Slots of featureData(a4ALL) are

- `Entrez ID~`: Entrez ID as retrieved from annotation package
- `Ensembl ID~`: Ensembl ID as retrieved from annotation package
- `Gene Symbol~`: Gene symbol as retrieved from annotation package
- `Description~`: Description as retrieved from annotation package

Value

a new ExpressionSet object with the additional information stored as feature data

Note

One should always use subscripting of featureData by column name (e.g. `featureData(a4ALL)$`Entrez ID``; as the pipeline ExpressionSets have one additional column compared to the ExpressionSet objects produced by `addGeneInfo`, i.e. column 2 of the pipeline ExpressionSets corresponds to column one of an `addGeneInfo` ExpressionSet.

Author(s)

Tobias Verbeke, Steven Osselaer

Examples

```
library(ALL)
data(ALL)
a4ALL <- addGeneInfo(ALL)
head(featureData(a4ALL)$`Entrez ID`)
```

Index

∗ **manip**
addGeneInfo, 2

addGeneInfo, 2