Package 'chevreulPlot'

November 11, 2026

Type Package

Title Plots used in the chevreulPlot package

Version 1.4.0

Description Tools for plotting SingleCellExperiment objects in the chevreulPlot package. Includes functions for analysis and visualization of single-cell data. Supported by NIH grants R01CA137124 and R01EY026661 to David Cobrinik.

License MIT + file LICENSE

URL https://github.com/whtns/chevreulPlot, https://whtns.github.io/chevreulPlot/

Date 2024-11-17

BugReports https://github.com/cobriniklab/chevreulPlot/issues

Depends R (>= 4.5.0), SingleCellExperiment, chevreulProcess

Imports base, cluster, clustree, ComplexHeatmap (>= 2.5.4), circlize, dplyr, EnsDb.Hsapiens.v86, forcats, fs, ggplot2, grid, plotly, purrr, S4Vectors, scales, scater, scran, scuttle, stats, stringr, tibble, tidyr, utils, wiggleplotr (>= 1.13.1), tidyselect, patchwork

Suggests BiocStyle, knitr, RefManageR, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Encoding UTF-8

LazyData false

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

biocViews Coverage, RNASeq, Sequencing, Visualization, GeneExpression, Transcription, SingleCell, Transcriptomics, Normalization, Preprocessing, QualityControl, DimensionReduction, DataImport

Config/testthat/edition 3

git_url https://git.bioconductor.org/packages/chevreulPlot

git_branch RELEASE_3_23

git_last_commit 08c5494

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Kevin Stachelek [aut, cre] (ORCID:
<https://orcid.org/0000-0003-2085-695X>),
Bhavana Bhat [aut]

Maintainer Kevin Stachelek <kevin.stachelek@gmail.com>

Contents

chevreulPlot-package . . . 2
cc.genes.cyclone . . . 3
enframe_markers . . . 4
ensembl_version . . . 4
grch38 . . . 5
grch38_tx2gene . . . 6
human_to_mouse_homologs . . . 6
make_complex_heatmap . . . 7
plotly_settings . . . 8
plot_all_transcripts . . . 9
plot_colData_histogram . . . 9
plot_colData_on_embedding . . . 10
plot_feature_on_embedding . . . 11
plot_gene_coverage_by_var . . . 12
plot_marker_features . . . 13
plot_transcript_composition . . . 14
plot_violin . . . 15
small_example_dataset . . . 16
tiny_sce . . . 16

Index **17**

`chevreulPlot-package` *chevreulPlot: Plots used in the chevreulPlot package*

Description

Tools for plotting SingleCellExperiment objects in the chevreulPlot package. Includes functions for analysis and visualization of single-cell data. Supported by NIH grants R01CA137124 and R01EY026661 to David Cobrinik.

Author(s)

Maintainer: Kevin Stachelek <kevin.stachelek@gmail.com> (ORCID)

Authors:

- Bhavana Bhat <bhavanabhat29@gmail.com>

See Also

Useful links:

- https://github.com/whtns/chevreulPlot
- https://whtns.github.io/chevreulPlot/
- Report bugs at https://github.com/cobriniklab/chevreulPlot/issues

---

cc.genes.cyclone *Cyclone cell cycle pairs by symbol*

Description

cell cycle genes with paired expression represented by HGNC symbol

Usage

```
cc.genes.cyclone
```

Format

a list of dataframes with G1, G2, and S gene expression

G1 G1 gene symbols

G2 G2 gene symbols

S S gene symbols ...

Source

cyclone

enframe_markers *Enframe Cluster Markers*

Description

Enframe Cluster Markers

Usage

```
enframe_markers(tbl)
```

Arguments

tbl	a tibble of marker genes

Value

a pivoted tibble of marker genes

ensembl_version *Ensembl version used for build*

Description

Ensembl version used for build

Usage

```
ensembl_version
```

Format

An object of class character of length 1.

Source

http://www.ensembl.org/

Examples

```
# ensembl_version
```

grch38 *Human annotation data*

Description

Human (*Homo sapiens*) annotations based on genome assembly GRCH38 from Ensembl.

Usage

```
grch38
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 76062 rows and 9 columns.

Details

Variables:

- ensgene
- entrez
- symbol
- chr
- start
- end
- strand
- biotype
- description

Source

http://ensembl.org/homo_sapiens

Examples

```
data("grch38")
head(grch38)
```

grch38_tx2gene *Human transcripts to genes*

Description

Lookup table for converting Human (*Homo sapiens*) Ensembl transcript IDs to gene IDs based on genome assembly GRCH38 from Ensembl.

Usage

```
grch38_tx2gene
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 277081 rows and 2 columns.

Details

Variables:

- enstxp
- ensgene

Source

http://ensembl.org/homo_sapiens

Examples

```
data(grch38_tx2gene)
head(grch38_tx2gene)
```

human_to_mouse_homologs *Gene Homologs Between Human and Mouse*

Description

Homologs drawn from Biomart

Usage

```
human_to_mouse_homologs
```

Format

A data frame with 23188 rows and 2 columns

HGNC.symbol human gene symbols

MGI.symbol mouse gene symbols ...

Source

bioMart

`make_complex_heatmap` *Plot Annotated Complexheatmap from SingleCellExperiment object*

Description

Plot Annotated Complexheatmap from SingleCellExperiment object

Usage

```
make_complex_heatmap(
  object,
  features = NULL,
  group.by = "ident",
  cells = NULL,
  assayName = "logcounts",
  experiment = NULL,
  group.bar.height = 0.01,
  column_split = NULL,
  col_arrangement = "ward.D2",
  mm_col_dend = 30,
  ...
)
```

Arguments

`object`	A SingleCellExperiment object
`features`	Vector of features to plot. Features can come
`group.by`	Name of one or more metadata columns to annotate columns by (for example, orig.ident)
`cells`	Cells to retain
`assayName`	"counts" for raw data "scale.data" for log-normalized data
`experiment`	experiment to display
`group.bar.height`	height for group bars
`column_split`	whether to split columns by metadata value

col_arrangement	how to arrange columns whether with a dendrogram (Ward.D2, average, etc.) or exclusively by metadata category
mm_col_dend	height of column dendrogram
...	additional arguments passed to Heatmap

Value

a complexheatmap

Examples

```
data("tiny_sce")
make_complex_heatmap(tiny_sce)
```

---

plotly_settings *Plotly settings*

Description

Change settings of a plotly plot

Usage

```
plotly_settings(plotly_plot, width = 600, height = 700)
```

Arguments

plotly_plot	A plotly plot
width	Default set to '600'
height	Default set to '700'

Value

a plotly plot with altered settings

plot_all_transcripts *Plot All Transcripts*

Description

plot expression all transcripts for an input gene superimposed on embedding

Usage

```
plot_all_transcripts(
  object,
  features,
  embedding = "UMAP",
  from_gene = TRUE,
  ...
)
```

Arguments

object	A object
features	gene or vector of transcripts
embedding	umap
from_gene	whether to look up transcripts for an input gene
...	additional arguments passed to plot_feature_on_embedding

Value

a list of embedding plots colored by a feature of interest

Examples

```
data("tiny_sce")
plot_all_transcripts(tiny_sce, "NRL", from_gene = TRUE)
```

plot_colData_histogram *Plot Read Count*

Description

Draw a box plot for read count data of a metadata variable

Usage

```
plot_colData_histogram(
  object,
  group_by = NULL,
  fill_by = NULL,
  yscale = "linear",
  return_plotly = FALSE
)
```

Arguments

object	A object
group_by	Metadata variable to plot. Default set to "nCount_RNA"
fill_by	Variable to color bins by. Default set to "batch"
yscale	Scale of y axis. Default set to "linear"
return_plotly	whether to return an interactive plotly plot

Value

a histogram of read counts

Examples

```
data(small_example_dataset)
small_example_dataset <- sce_calcn(small_example_dataset)
# static plot
plot_colData_histogram((small_example_dataset), return_plotly = FALSE)
```

---

plot_colData_on_embedding

Plot Metadata Variables

Description

Plots static or interactive plot where each point represents a cell metadata variable whose position on the map depends on cell embeddings determined by the reduction technique used

Usage

```
plot_colData_on_embedding(
  object,
  group = "batch",
  embedding = "UMAP",
  dims = c(1, 2),
  highlight = NULL,
  return_plotly = FALSE,
  ...
)
```

Arguments

object	A SingleCellExperiment object
group	Name of one or more metadata columns to group (color) cells by
embedding	The dimensional reduction technique to be used
dims	Dimensions to plot, must be a two-length numeric vector
highlight	A list of vectors of cells to highlight
return_plotly	Convert plot to interactive web-based graph
...	extra parameters passed to ggplot

Value

a ggplot

Examples

```
data(small_example_dataset)

# static mode
plot_colData_on_embedding(small_example_dataset, "Mutation_Status", return_plotly = FALSE)
```

---

plot_feature_on_embedding *Plot Feature*

Description

Plots gene or transcript expression overlaid on a given embedding.

Usage

```
plot_feature_on_embedding(
  object,
  embedding = c("UMAP", "PCA", "TSNE"),
  features,
  dims = c(1, 2),
  return_plotly = FALSE,
  ...
)
```

Arguments

object	A SingleCellExperiment object
embedding	Dimensional reduction technique to be used
features	Feature to plot
dims	Dimensions to plot, must be a two-length numeric vector
return_plotly	return plotly object
...	additional arguments passed to plotReduceDim

Value

an embedding colored by a feature of interest

Examples

```
data(small_example_dataset)
plot_feature_on_embedding(small_example_dataset, embedding = "UMAP",
features = "Gene_0001")
```

`plot_gene_coverage_by_var` *Plot BigWig Coverage for Genes of Interest by a Given Variable*

Description

Plot BigWig coverage for genes of interest colored by a given variable

Usage

```
plot_gene_coverage_by_var(
  genes_of_interest = "NRL",
  cell_metadata,
  bigwig_tbl,
  group_by = "batch",
  values_of_interest = NULL,
  organism = c("human", "mouse"),
  edb = NULL,
  heights = c(3, 1),
  scale_y = "log10",
  reverse_x = FALSE,
  start = NULL,
  end = NULL,
  summarize_transcripts = FALSE,
  ...
)
```

Arguments

`genes_of_interest`	Gene of interest
`cell_metadata`	a dataframe with cell metadata from object
`bigwig_tbl`	a tibble with colnames "name", "bigWig", and "sample_id" matching the filename, absolute path, and sample name of each cell in the cell_metadata
`group_by`	Variable to color by

values_of_interest
: values of interest

organism
: human (default) or mouse

edb
: ensembldb object

heights
: The heights of each row in the grid of plot

scale_y
: whether to scale coverage

reverse_x
: whether to reverse x axis

start
: start coordinates

end
: end coordinates

summarize_transcripts
: whether to summarize transcript counts

...
: extra arguments passed to plotCoverageFromEnsembldb

Value

a ggplot with coverage faceted by group_by

---

plot_marker_features *Plot Cluster Marker Genes*

Description

Plot a dot plot of n marker features grouped by cell metadata available methods are wilcoxon rank-sum test

Usage

```
plot_marker_features(
  object,
  group_by = "batch",
  num_markers = 5,
  selected_values = NULL,
  return_plotly = FALSE,
  marker_method = "wilcox",
  experiment = "gene",
  hide_technical = NULL,
  unique_markers = FALSE,
  p_val_cutoff = 1,
  ...
)
```

Arguments

object	a object
group_by	the metadata variable from which to pick clusters
num_markers	default is 5
selected_values	selected values to display
return_plotly	whether to return an interactive plotly plot
marker_method	"wilcox"
experiment	experiment to plot default gene
hide_technical	whether to exclude mitochondrial or ribosomal genes
unique_markers	whether to plot only unique marker genes for group
p_val_cutoff	cutoff for p value display
...	extra parameters passed to ggplot2

Value

a ggplot with marker genes from group_by

Examples

```
data(small_example_dataset)
plot_marker_features(small_example_dataset, group_by = "gene_snn_res.1")
```

---

plot_transcript_composition

Plot Transcript Composition

Description

plot the proportion of reads of a given gene map to each transcript

Usage

```
plot_transcript_composition(
  object,
  gene_symbol,
  group.by = "batch",
  standardize = FALSE,
  drop_zero = FALSE
)
```

Arguments

object	A object
gene_symbol	Gene symbol of gene of interest
group.by	Name of one or more metadata columns to annotate columns by (for example, orig.ident)
standardize	whether to standardize values
drop_zero	Drop zero values

Value

a stacked barplot of transcript counts

Examples

```
data(tiny_sce)
plot_transcript_composition(tiny_sce, "NRL")
```

---

plot_violin *Plot Violin plot*

Description

Plots a Violin plot of a single data (gene expression, metrics, etc.) grouped by a metadata variable

Usage

```
plot_violin(
  object,
  group_by = "batch",
  plot_vals = NULL,
  features = "NRL",
  experiment = "gene",
  ...
)
```

Arguments

object	A SingleCellExperiment object
group_by	Variable to group (color) cells by
plot_vals	plot values
features	Features to plot
experiment	Name of experiment to use, defaults to active experiment
...	extra parameters passed to ggplot2

Value

a violin plot

Examples

```
data("tiny_sce")
plot_violin(tiny_sce, "Prep.Method", features = "NRL")
```

`small_example_dataset` *Small example SingleCellExperiment*

Description

created with scuttle::mockSCE

Usage

```
small_example_dataset
```

Format

An SCE with 200 cells and 1000 genes

Source

scuttle::mockSCE

`tiny_sce` *Tiny example SingleCellExperiment*

Description

subset to only NRL from chevreuldata::human_gene_transcript_sce()

Usage

```
tiny_sce
```

Format

An SCE with only expression of NRL gene and NRL transripts

Source

chevreuldata::human_gene_transcript_sce()

Index

∗ **datasets**
cc.genes.cyclone, 3
ensembl_version, 4
grch38, 5
grch38_tx2gene, 6
human_to_mouse_homologs, 6
small_example_dataset, 16
tiny_sce, 16
∗ **internal**
chevreulPlot-package, 2

cc.genes.cyclone, 3
chevreulPlot *(*chevreulPlot-package*)*, 2
chevreulPlot-package, 2

enframe_markers, 4
ensembl_version, 4

grch38, 5
grch38_tx2gene, 6

human_to_mouse_homologs, 6

make_complex_heatmap, 7

plot_all_transcripts, 9
plot_colData_histogram, 9
plot_colData_on_embedding, 10
plot_feature_on_embedding, 11
plot_gene_coverage_by_var, 12
plot_marker_features, 13
plot_transcript_composition, 14
plot_violin, 15
plotly_settings, 8

small_example_dataset, 16

tiny_sce, 16