

Package ‘CCAFE’

June 11, 2026

Type Package

Title Case Control Allele Frequency Estimation

Version 1.5.0

Description Functions to reconstruct case and control AFs from summary statistics.

One function uses OR, NCase, NControl, and SE(log(OR)).

The second function uses OR, NCase, NControl, and AF for the whole sample.

License GPL-3

Encoding UTF-8

LazyData false

RoxygenNote 7.3.2

Roxygen list(markdown = TRUE)

Imports dplyr, VariantAnnotation

Depends R (>= 4.4.0)

Suggests testthat (>= 3.0.0), rmarkdown, markdown, knitr, tidyverse,

DescTools, cowplot, BiocStyle, GenomicRanges,

SummarizedExperiment, S4Vectors, IRanges

VignetteBuilder knitr

Config/testthat/edition 3

URL <https://github.com/wolffha/CCAFE/>

BugReports <https://github.com/wolffha/CCAFE/issues>

biocViews GenomeWideAssociation, ComparativeGenomics, Genetics,

Preprocessing, SNP, Software, WholeGenome

git_url <https://git.bioconductor.org/packages/CCAFE>

git_branch devel

git_last_commit 1905db0

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-06-11

Author Hayley Wolff [cre, aut]

Maintainer Hayley Wolff <hayley.wolff@cuanschutz.edu>

Contents

CCAFE-package	2
CaseControl_AF	2
CaseControl_SE	4
CCAFE_convertVCF	6
sampleDat	7
vcf_sample	7
Index	9

CCAFE-package	<i>CCAFE: Case Control Allele Frequency Estimation</i>
---------------	--

Description

Functions to reconstruct case and control AFs from summary statistics. One function uses OR, NCase, NControl, and SE(log(OR)). The second function uses OR, NCase, NControl, and AF for the whole sample.

Author(s)

Maintainer: Hayley Wolff <hayley.wolff@cuanschutz.edu>

See Also

Useful links:

- <https://github.com/wolffha/CCAFE/>
- Report bugs at <https://github.com/wolffha/CCAFE/issues>

CaseControl_AF	<i>CaseControl_AF</i>
----------------	-----------------------

Description

This is a function to derive the case and control AFs from GWAS summary statistics when the user has access to the whole sample AF, the sample sizes, and the OR (or beta). If user has SE instead of sample AF use [CaseControl_SE\(\)](#)

Usage

```
CaseControl_AF(
  data,
  N_case = 0,
  N_control = 0,
  OR_colname = "OR",
  AF_total_colname = "AF"
)
```

Arguments

`data` dataframe with each row being a variant and columns for AF_total and OR
`N_case` the number of cases in the sample
`N_control` the number of controls in the sample
`OR_colname` a string containing the exact column name in 'data' with the OR
`AF_total_colname` a string containing the exact column name in 'data' with the whole sample AF

Value

returns a dataframe with two columns (AF_case, AF_control) and rows equal to the number of variants

Author(s)

Hayley Wolff (Stoneman), <hayley.wolff@cuanschutz.edu>

References

<https://github.com/wolffha/CCAFE>

See Also

<https://github.com/wolffha/CCAFE> for further documentation

Examples

```
library(CCAFE)

data("sampleDat")
sampleDat <- as.data.frame(sampleDat)

nCase_sample = 16550
nControl_sample = 403923

# get the estimated case and control AFs
af_method_results <- CaseControl_AF(data = sampleDat,
                                     N_case = nCase_sample,
                                     N_control = nControl_sample,
                                     OR_colname = "OR",
                                     AF_total_colname = "true_maf_pop")

head(af_method_results)
```

CaseControl_SE *CaseControl_SE*

Description

This is a function to derive the case, control, and total MAFs from GWAS summary statistics when the user has access to the sample sizes, and the OR (or beta), and SE for the log(OR) for each variant. If user has total AF instead of SE use `CaseControl_AF()` This code uses the GroupFreq function adapted from C from https://github.com/Paschou-Lab/ReAct/blob/main/GrpPRS_src/CountConstruct.c

Usage

```
CaseControl_SE(
  data,
  N_case = 0,
  N_control = 0,
  OR_colname = "OR",
  SE_colname = "SE",
  chromosome_colname = "chr",
  sex_chromosomes = FALSE,
  position_colname = "pos",
  N_XX_case = NA,
  N_XX_control = NA,
  N_XY_case = NA,
  N_XY_control = NA,
  do_correction = FALSE,
  correction_data = NA,
  remove_sex_chromosomes = TRUE,
  verbose = FALSE
)
```

Arguments

<code>data</code>	dataframe where each row is a variant and columns contain the OR, SE, chromosome and positions
<code>N_case</code>	an integer of the number of Case individuals
<code>N_control</code>	an integer of the number of Control individuals
<code>OR_colname</code>	a string containing the exact column name in 'data' with the OR
<code>SE_colname</code>	a string containing the exact column name in 'data' with the SE
<code>chromosome_colname</code>	a string containing the exact column name in 'data' with the chromosomes, default "chr"
<code>sex_chromosomes</code>	boolean, TRUE if variants from sex chromosomes are included in the dataset. Sex chromosomes can be numeric (23, 24) or character (X, Y). If numeric, assumes X=23 and Y=24.
<code>position_colname</code>	a string containing the exact column name in 'data' with the position, default "pos"


```
head(se_method_results)
```

```
CCAFE_convertVCF      CCAFE_convertVCF
```

Description

Formats information from a VCF object for use in CCAFE methods as follows: From the rowRanges object: seqnames (chromosome), ranges (position), From the geno object: ES (effect size of ALT), SE, AF (allele frequency of ALT)

Usage

```
CCAFE_convertVCF(vcf)
```

Arguments

vcf a Variant Call Format (VCF) file read in using VariantAnnotation BioConductor package

Value

a dataframe object with columns Position, RSID, Chromosome, REF, ALT, beta, SE, AF, OR

Author(s)

Hayley Wolff (Stoneman), <hayley.wolff@cuanschutz.edu>

Examples

```
library(VariantAnnotation)
library(CCAFE)

# load the data
data("vcf_sample")

# run the method
df_sample <- CCAFE_convertVCF(vcf_sample)
print(head(df_sample))

# can then use in CCAFE methods
# since we have total AF, will use CaseControl_AF
df_sample <- CaseControl_AF(data = df_sample,
                           N_case = 48286,
                           N_control = 250671,
                           OR_colname = "OR",
                           AF_total_colname = "AF")

head(df_sample)
```

sampleDat

*PanUKBB and gnomAD Diabetes Data***Description**

This is a subset of 500 variants on chromosome 1 from the Pan-UKBB diabetes GWAS with the whole sample (pop), case, and control minor allele frequency (MAF) for those classified in Pan-UKBB as European (EUR). These variants (which are mapped to GRCh37) have been harmonized with gnomAD non-Finnish European (NFE) MAFs.

Usage

```
data("sampleDat")
```

Format

‘sampleDat’ A data frame with 500 rows and 11 columns:

CHR chromosome number

POS base-pair position of variant (GRCh37 coordinates)

REF Reference allele

ALT Alternate allele

true_maf_case MAF in EUR cases in Pan-UKBB Diabetes

true_maf_control MAF in EUR controls in Pan-UKBB Diabetes

true_maf_pop MAF in whole EUR sample in Pan-UKBB Diabetes

beta beta from EUR GWAS in Pan-UKBB Diabetes

SE SE of beta from EUR GWAS in Pan-UKBB Diabetes

OR OR from EUR GWAS in Pan-UKBB Diabetes

gnomad_maf MAF in gnomAD NFE

Source

<<https://pan.ukbb.broadinstitute.org/docs/per-phenotype-files>>

<<https://gnomad.broadinstitute.org/downloads>>

vcf_sample

*A VCF from this GWAS of Type 2 Diabetes
<https://doi.org/10.1038/s41588-018-0084-1>. containing a subset
of 10,000 variants*

Description

A VCF from this GWAS of Type 2 Diabetes <https://doi.org/10.1038/s41588-018-0084-1>. containing a subset of 10,000 variants

Usage

```
data("vcf_sample")
```

Format

```
'vcf_sample' A CollapsedVCF
```

```
dim: 10000 1 rowRanges(vcf): GRanges with 5 metadata columns: paramRangeID, REF, ALT, QUAL, FILTER info(vcf): DataFrame with 1 column: AF info(header(vcf)): Number Type Description AF A Float Allele Frequency geno(vcf): List of length 9: ES, SE, LP, AF, SS, EZ, SI, NC, ID geno(header(vcf)): Number Type Description ES A Float Effect size estimate relative to the alternative allele SE A Float Standard error of effect size estimate LP A Float -log10 p-value for effect estimate AF A Float Alternate allele frequency in the association study SS A Integer Sample size used to estimate genetic effect EZ A Float Z-score provided if it was used to derive the EFFECT and SE fields SI A Float Accuracy score of summary data imputation NC A Integer Number of cases used to estimate genetic effect ID 1 String Study variant identifier
```

Index

* datasets

sampleDat, [7](#)

vcf_sample, [7](#)

* internal

CCAFE-package, [2](#)

CaseControl_AF, [2](#)

CaseControl_AF(), [4](#)

CaseControl_SE, [4](#)

CaseControl_SE(), [2](#)

CCAFE-package, [2](#)

CCAFE_convertVCF, [6](#)

sampleDat, [7](#)

vcf_sample, [7](#)