

# Package ‘MsBackendMsp’

May 9, 2024

**Title** Mass Spectrometry Data Backend for NIST msp Files

**Version** 1.9.0

**Description** Mass spectrometry (MS) data backend supporting import and handling of MS/MS spectra from NIST MSP Format (msp) files. Import of data from files with different MSP \*flavours\* is supported. Objects from this package add support for MSP files to Bioconductor's Spectra package. This package is thus not supposed to be used without the Spectra package that provides a complete infrastructure for MS data handling.

**Depends** R (>= 4.1.0), Spectra (>= 1.5.14)

**Imports** ProtGenerics (>= 1.35.3), BiocParallel, S4Vectors, IRanges, MsCoreUtils, methods, stats

**Suggests** testthat, knitr (>= 1.1.0), roxygen2, BiocStyle (>= 2.5.19), rmarkdown

**License** Artistic-2.0

**Encoding** UTF-8

**VignetteBuilder** knitr

**BugReports** <https://github.com/RforMassSpectrometry/MsBackendMsp/issues>

**URL** <https://github.com/RforMassSpectrometry/MsBackendMsp>

**biocViews** Infrastructure, Proteomics, MassSpectrometry, Metabolomics, DataImport

**Roxygen** list(markdown=TRUE)

**RoxygenNote** 7.3.1

**Collate** 'hidden\_aliases.R' 'MsBackendMsp.R' 'functions-msp.R'

**git\_url** <https://git.bioconductor.org/packages/MsBackendMsp>

**git\_branch** devel

**git\_last\_commit** ebb4196

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.20

**Date/Publication** 2024-05-08

**Author** Neumann Steffen [aut] (<<https://orcid.org/0000-0002-7899-7192>>),  
Johannes Rainer [aut, cre] (<<https://orcid.org/0000-0002-6977-7147>>),  
Michael Witting [ctb] (<<https://orcid.org/0000-0002-1462-4426>>)

**Maintainer** Johannes Rainer <Johannes.Rainer@eurac.edu>

Contents

hidden_aliases . . . . .	2
MsBackendMsp . . . . .	2
readMsp . . . . .	5
<b>Index</b>	<b>7</b>

---

hidden_aliases	<i>Internal page for hidden aliases</i>
----------------	---

---

Description

For S4 methods that require a documentation entry but only clutter the index.

---

MsBackendMsp	<i>MS data backend for msp files</i>
--------------	--------------------------------------

---

Description

The MsBackendMsp class supports import of MS/MS spectra data from files in NIST MSP file format. MsBackendMsp extends the [MsBackendDataFrame\(\)](#) backend directly and supports thus the [applyProcessing\(\)](#) function to make data manipulations persistent.

New objects are created with the MsBackendMsp() function. The backendInitialize() method has to be subsequently called to initialize the object and import MS/MS data from (one or more) msp files.

The MsBackendMsp backend provides an export() method that allows to export the data from the Spectra object (parameter x) to a file in MSP format.

Parameters to this function are:

- x: the Spectra object that should be exported.
- file: character(1) with the desired file name.
- mapping: named character providing the mapping between spectra variables and MSP data fields. Defaults to mapping = spectraVariableMapping(MsBackendMsp()).
- allVariables: logical(1) whether all spectra variables in x should be exported or only those defined with mapping.

- `exportName`: `logical(1)` whether a NAME field should always be exported even if not provided in `x`.

See the package vignette for details and examples.

The `spectraVariableMapping()` function allows to provide the mapping between spectra variable names (i.e. the names that will be used for the spectra variables in the `Spectra()` object) and the data field names of the MSP file. Parameter `format` allows to select pre-defined mappings. Currently supported mapping flavors are:

- `format = "msp"`: default MSP field names. Should work with standard NIST MSP files or MSP files exported from MS-DIAL.
- `format = "mona"`: MSP file format from MoNA including LipidBlast.

## Usage

```
## S4 method for signature 'MsBackendMsp'
backendInitialize(
  object,
  file,
  mapping = spectraVariableMapping(object),
  ...,
  BPPARAM = SerialParam()
)

MsBackendMsp()

## S4 method for signature 'MsBackendMsp'
spectraVariableMapping(object, format = c("msp", "mona"))

## S4 method for signature 'MsBackendMsp'
export(
  object,
  x,
  file = tempfile(),
  mapping = spectraVariableMapping(MsBackendMsp()),
  allVariables = TRUE,
  exportName = TRUE,
  ...
)
```

## Arguments

<code>object</code>	Instance of <code>MsBackendMsp</code> class.
<code>file</code>	character with the (full) file name(s) of the msp file(s) from which MS/MS data should be imported or exported.
<code>mapping</code>	named character vector to rename MSP fields to spectra variables (see <code>spectraVariableMapping()</code> ). This allows to correctly import also custom fields or data from files with different MSP <i>flavors</i> .

...	Currently ignored.
BPPARAM	Parameter object defining the parallel processing setup to import data in parallel. Defaults to BPPARAM = SerialParam(). See <a href="#">bpparam()</a> for more information. Parallel processing would make most sense for import from a large set of individual MSP files, but could also improve performance for import from a (very large) single MSP file.
format	For <code>spectraVariableMapping()</code> : character(1) specifying for which MSP <i>flavour</i> the mapping should be returned. Currently supported are: format = "msp" (generic MSP format, for example for MS-DIAL MSP files) and format = "mona" (MSP files in MoNA flavour).
x	For <code>export()</code> : a <a href="#">Spectra()</a> object that should be exported to the specified MSP file.
allVariables	logical(1) whether all spectra variables in x should be exported or only those defined with mapping.
exportName	logical(1) whether a NAME field should always be exported even if not provided in x.

### Value

MsBackendMsp() and backendInitialize() return an instance of a MsBackendMsp class. `spectraVariableMapping()` a named character vector with the mapping between spectra variables and MSP data fields.

### Note

Format requirements/assumptions of MSP files:

- Comment lines are expected to start with a #.
- Multiple spectra within the same MSP file are separated by an empty line.
- The first n lines of a spectrum entry represent metadata.
- Metadata is provided as "name: value" pairs (i.e. name and value separated by a ":").
- One line per mass peak, with values separated by a whitespace or tabulator.
- Each line is expected to contain at least the m/z and intensity values (in that order) of a peak. Additional values are currently ignored.

### Author(s)

Steffen Neumann, Michael Witting, Laurent Gatto and Johannes Rainer

### Examples

```
## Import spectra from a MSP file from LipidBlast
f <- system.file("extdata", "small-export-LipidBlast.msp",
  package = "MsBackendMsp")
be <- backendInitialize(MsBackendMsp(), f)
be
be$msLevel
```

```
be$intensity
be$mz

## precursor m/z are however all missing
be$precursorMz

## Default spectra variable mapping
spectraVariableMapping(MsBackendMsp())

## In fact, to read MSP files in "LipidBlast flavour" (same as MoNA) we
## should use a different spectra variable mapping
spectraVariableMapping(MsBackendMsp(), "mona")

## Importing the data with this will correctly retrieve data
be <- backendInitialize(MsBackendMsp(), f,
  mapping = spectraVariableMapping(MsBackendMsp(), "mona"))
be$precursorMz

## Other fields are also correctly mapped, but might need to be converted
## to e.g. numeric, such as "exactmass"
be$exactmass

be$exactmass <- as.numeric(be$exactmass)

be$adduct
be$formula

## Exporting Spectra objects in MSP format.

sps <- Spectra(be)
export(MsBackendMsp(), sps, file = stdout())
```

---

readMsp

*Reading MSP files*

---

## Description

The `readMsp()` function imports the data from a file in MGF format reading all specified fields and returning the data as a [DataFrame\(\)](#).

Format constraints for MSP files:

- Comment lines are expected to start with a #.
- Multiple spectra within the same MSP file are separated by an empty line.
- The first n lines of a spectrum entry represent metadata.
- Metadata is provided as "name: value" pairs (i.e. name and value separated by a ":").
- One line per mass peak, with values separated by a whitespace or tabulator.
- Each line is expected to contain at least the m/z and intensity values (in that order) of a peak. Additional values are currently ignored.

## Usage

```
readMsp(  
  f,  
  msLevel = 2L,  
  mapping = spectraVariableMapping(MsBackendMsp()),  
  BPPARAM = SerialParam(),  
  ...  
)
```

## Arguments

f	character(1) with the path to an MSP file.
msLevel	numeric(1) with the MS level. Default is 2. This value will be reported as the spectra's MS level <b>unless</b> the source MSP file defines the MS level.
mapping	named character vector to rename MSP fields to spectra variables (see <a href="#">spectraVariableMapping()</a> ). This allows to correctly import also custom fields or data from files with different MSP <i>flavors</i> .
BPPARAM	parallel processing setup. See <a href="#">bpparam()</a> for more details.
...	Additional parameters, currently ignored.

## Value

A `DataFrame` with each row containing the data from one spectrum in the MSP file. `m/z` and intensity values are available in columns `"mz"` and `"intensity"` in a list representation.

## Author(s)

Laurent Gatto, Steffen Neumann, Johannes Rainer

## Examples

```
f <- system.file("extdata", "minimona.msp", package = "MsBackendMsp")  
  
readMsp(f)
```

# Index

## \* **internal**

- hidden\_aliases, [2](#)
- [, MsBackendDataFrame-method
  - (hidden\_aliases), [2](#)
- applyProcessing(), [2](#)
- backendInitialize, MsBackendMsp-method
  - (MsBackendMsp), [2](#)
- bpparam(), [4](#), [6](#)
- DataFrame(), [5](#)
- export, MsBackendMsp-method
  - (MsBackendMsp), [2](#)
- hidden\_aliases, [2](#)
- MsBackendDataFrame(), [2](#)
- MsBackendMsp, [2](#)
- MsBackendMsp-class (MsBackendMsp), [2](#)
- readMsp, [5](#)
- Spectra(), [3](#), [4](#)
- spectraVariableMapping(), [3](#), [6](#)
- spectraVariableMapping, MsBackendMsp-method
  - (MsBackendMsp), [2](#)