Package 'alabaster.sce'

November 12, 2026

Title Load and Save SingleCellExperiment from File

Version 1.13.1

Date 2026-09-05

License MIT + file LICENSE

Description Save SingleCellExperiment into file artifacts, and load them back into memory.
This is a more portable alternative to serialization of such objects into RDS files.
Each artifact is associated with metadata for further interpretation;
downstream applications can enrich this metadata with context-specific properties.

Depends SingleCellExperiment, alabaster.base

Imports methods, alabaster.se, jsonlite

Suggests knitr, testthat, BiocStyle, rmarkdown

VignetteBuilder knitr

biocViews DataImport, DataRepresentation

Encoding UTF-8

Config/roxygen2/version 8.1.0

git_url https://git.bioconductor.org/packages/alabaster.sce

git_branch devel

git_last_commit c48839b

git_last_commit_date 2026-09-05

Repository Bioconductor 3.24

Date/Publication 2026-11-12

Author Aaron Lun [aut, cre]

Maintainer Aaron Lun <infinite.monkeys.with.keyboards@gmail.com>

Contents

readSingleCellExperiment 2
saveSingleCellExperiment 3

Index 4

readSingleCellExperiment *Read a SingleCellExperiment from disk*

Description

Read a SingleCellExperiment object from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in `readObject`.

Usage

```
readSingleCellExperiment(path, metadata, ...)
```

Arguments

`path`	String containing a path to a directory, itself created using the `saveObject` method for SingleCellExperiment objects.
`metadata`	Named list of metadata for this object, see `readObjectFile` for details.
`...`	Further arguments passed to `readRangedSummarizedExperiment` and internal `altReadObject` calls.

Value

A SingleCellExperiment object.

Author(s)

Aaron Lun

See Also

"`saveObject,SingleCellExperiment-method`", to save the SingleCellExperiment to disk.

Examples

```
# Mocking up an SCE:
mat <- matrix(rpois(10000, 10), ncol=10)
colnames(mat) <- letters[1:10]
rownames(mat) <- sprintf("GENE_%i", seq_len(nrow(mat)))

se <- SingleCellExperiment(list(counts=mat))
se$stuff <- LETTERS[1:10]
se$blah <- runif(10)
reducedDims(se) <- list(
    PCA=matrix(rnorm(ncol(se)*10), ncol=10),
    TSNE=matrix(rnorm(ncol(se)*2), ncol=2)
)
altExps(se) <- list(spikes=SummarizedExperiment(list(counts=mat[1:2,])))

# Staging it:
tmp <- tempfile()
saveObject(se, tmp)
readObject(tmp)
```

saveSingleCellExperiment *Save a SingleCellExperiment to disk*

Description

Save a SingleCellExperiment to its on-disk representation.

Usage

```
## S4 method for signature 'SingleCellExperiment'
saveObject(x, path, ...)
```

Arguments

x	A SingleCellExperiment object or one of its subclasses.
path	String containing the path to a directory in which to save x.
...	Further arguments to pass to "saveObject,RangedSummarizedExperiment-method".

Value

x is saved into path and NULL is invisibly returned.

Author(s)

Aaron Lun

See Also

readSingleCellExperiment, to read the SingleCellExperiment back into the R session.

Examples

```
# Mocking up an SCE:
mat <- matrix(rpois(10000, 10), ncol=10)
colnames(mat) <- letters[1:10]
rownames(mat) <- sprintf("GENE_%i", seq_len(nrow(mat)))

se <- SingleCellExperiment(list(counts=mat))
se$stuff <- LETTERS[1:10]
se$blah <- runif(10)
reducedDims(se) <- list(
    PCA=matrix(rnorm(ncol(se)*10), ncol=10),
    TSNE=matrix(rnorm(ncol(se)*2), ncol=2)
)
altExps(se) <- list(spikes=SummarizedExperiment(list(counts=mat[1:2,])))

# Staging it:
tmp <- tempfile()
saveObject(se, tmp)
list.files(tmp, recursive=TRUE)
```

Index

altReadObject, *2*

loadSingleCellExperiment
        *(*readSingleCellExperiment*)*, 2

readObject, *2*
readObjectFile, *2*
readRangedSummarizedExperiment, *2*
readSingleCellExperiment, 2, *3*

saveObject, *2*
saveObject,SingleCellExperiment-method
        *(*saveSingleCellExperiment*)*, 3
saveSingleCellExperiment, 3
SingleCellExperiment, *2*, *3*
stageObject,SingleCellExperiment-method
        *(*saveSingleCellExperiment*)*, 3