

Package ‘survtype’

April 18, 2025

Type Package

Title Subtype Identification with Survival Data

Description Subtypes are defined as groups of samples that have distinct molecular and clinical features. Genomic data can be analyzed for discovering patient subtypes, associated with clinical data, especially for survival information. This package is aimed to identify subtypes that are both clinically relevant and biologically meaningful.

Version 1.25.0

Date 2019-12-18

Author Dongmin Jung

Maintainer Dongmin Jung <dmdmjung@gmail.com>

Depends SummarizedExperiment, pheatmap, survival, survminer, clustvarsel, stats, utils

Suggests maftools, scales, knitr, rmarkdown

License Artistic-2.0

biocViews Software, StatisticalMethod, GeneExpression, Survival, Clustering, Sequencing, Coverage

NeedsCompilation no

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/survtype>

git_branch devel

git_last_commit 169cc78

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-04-17

Contents

| | |
|----------------------------------|---|
| Exprs.survtype | 2 |
| gene.clust | 3 |
| MAF.survgroup | 4 |
| maf2matrix | 5 |
| plot.survtype | 6 |
| quantile_normalization | 7 |
| Single.survgroup | 7 |
| Surv.survtype | 8 |

Index**10**

| | |
|----------------|--|
| Exprs.survtype | <i>Sample subtype identification via survival information and gene expression data</i> |
|----------------|--|

Description

For discovery of subtypes of samples that are both clinically relevant and biologically meaningful, the Cox regression model and hierarchical clustering are combined.

Usage

```
Exprs.survtype(surv.data, time, status, exprs.data, K = 2, num.genes = 100,
              gene.sel = FALSE, gene.sel.opt = list(verbose = FALSE), ...)
```

Arguments

| | |
|--------------|--|
| surv.data | survival data |
| time | survival time |
| status | status indicator |
| exprs.data | expression data |
| K | the number of clusters (default: 2) |
| num.genes | the number of top genes based on the Cox score, before variable selection (default: 100) |
| gene.sel | a logical value indicating whether or not gene selection for clustering is applied (default: FALSE) |
| gene.sel.opt | a list of options for the gene selection function "clustvarsel". "verbose" is set to FALSE as default. |
| ... | additional parameters for the "pheatmap" |

Value

| | |
|------------|--|
| n | the number of subjects in each group |
| obs | the weighted observed number of events in each group |
| exp | the weighted expected number of events in each group |
| chisq | the chi-squared statistic for a test of equality |
| call | the matched call |
| fit | fitted survival curves |
| cluster | a vector of integers indicating the cluster to which each sample is assigned |
| time | survival time |
| status | status indicator |
| surv.data | survival data |
| exprs.data | expression data |

Author(s)

Dongmin Jung

References

Bair, E., & Tibshirani, R. (2004). Semi-supervised methods to predict patient survival from gene expression data. *PLoS biology*, 2(4), e108.

See Also

survival::Surv, survival::survfit, survival::survdiff, survival::coxph, clustvarsel::clustvarsel, pheatmap::pheatmap

Examples

```
set.seed(1)
nrows <- 5
ncols <- nrow(ovarian)
counts <- matrix(runif(nrows * ncols, 1, 1e4), nrows)
colnames(counts) <- paste("X", 1:ncols, sep = "")
rownames(ovarian) <- paste("X", 1:ncols, sep = "")
SE <- SummarizedExperiment(assays = SimpleList(counts = counts))
ovarian.survtype <- Exprs.survtype(ovarian, time = "fuptime", status = "fustat",
                                assay(SE), num.genes = 2, scale = "row",
                                clustering_method = "ward.D2")
plot(ovarian.survtype, pval = TRUE)
```

gene.clust

Plots of the heatmap for each cluster of expression data

Description

Heatmaps of clustered genes for subtypes of samples can be drawn.

Usage

```
gene.clust(object, K, ...)
```

Arguments

| | |
|--------|--|
| object | the result of "Exprs.survtype" |
| K | the number of clusters |
| ... | additional parameters for the "pheatmap" |

Value

Heatmap for each cluster

Author(s)

Dongmin Jung

See Also

pheatmap::pheatmap

Examples

```

set.seed(1)
nrows <- 5
ncols <- nrow(ovarian)
counts <- matrix(runif(nrows * ncols, 1, 1e4), nrows)
colnames(counts) <- paste("X", 1:ncols, sep = "")
rownames(ovarian) <- paste("X", 1:ncols, sep = "")
SE <- SummarizedExperiment(assays = SimpleList(counts = counts))
ovarian.survtype <- Exprs.survtype(ovarian, time = "fuptime", status = "fustat",
                                assay(SE), num.genes = 5, scale = "row",
                                clustering_method = "ward.D2")
plot(ovarian.survtype, pval = TRUE)
gene.clust(ovarian.survtype, 2, scale = "row", clustering_method = "ward.D2")

```

| | |
|---------------|---|
| MAF.survgroup | <i>Patient group identification via survival data and mutation annotation information</i> |
|---------------|---|

Description

The groups of patients are identified according to whether the variants exist on a single gene. Survival difference between patients with and without mutations is compared.

Usage

```

MAF.survgroup(surv.data, time, status, maf, variants = NULL,
              sample.name = "Tumor_Sample_Barcode", gene.name = "Hugo_Symbol",
              variant.type = "Variant_Classification", num.genes = 10,
              significant.genes = 1, ...)

```

Arguments

| | |
|-------------------|--|
| surv.data | survival data |
| time | survival time |
| status | status indicator |
| maf | a MAF file |
| variants | types of variants on a single gene for mutated samples. samples with any mutations, defined as mutated samples by default. |
| sample.name | the column name containing sample names (default: "Tumor_Sample_Barcode") |
| gene.name | the column name containing gene names (default: "Hugo_Symbol") |
| variant.type | the column name containing variant types (default: "Variant_Classification") |
| num.genes | the number of top genes based on the number of mutated genes (default: 10) |
| significant.genes | the number of top genes based on the statistical significance of mutated genes (default: 1) |
| ... | additional parameters for the "ggsurvplot" for the statistically significant genes |

Value

| | |
|------------|---|
| time | survival time |
| status | status indicator |
| surv.data | survival data |
| maf.matrix | a mutation matrix |
| summary | a list of number of samples with variants, chi-squared statistics and p-values |
| cluster | a vector of integers indicating the cluster to which each sample is assigned, for the most significant gene |
| fit | fitted survival curves, for the most significant gene |

Author(s)

Dongmin Jung

See Also

survival::Surv, survival::survfit, survival::survdiff, survminer::ggsurvplot

Examples

```
library(maftools)
laml.maf <- system.file('extdata', 'tcga_laml.maf.gz', package = 'maftools', mustWork = TRUE)
laml.clin <- system.file('extdata', 'tcga_laml_annot.tsv', package = 'maftools', mustWork = TRUE)
laml.maf <- read.csv(laml.maf, sep = "\t")
laml.clinical.data <- read.csv(laml.clin, sep = "\t", row.names = 1)
index <- which(laml.clinical.data$days_to_last_followup == -Inf)
laml.clinical.data <- laml.clinical.data[-index,]
laml.clinical.data <- data.frame(laml.clinical.data)
laml.survgroup <- MAF.survgroup(laml.clinical.data, time = "days_to_last_followup",
                               status = "Overall_Survival_Status", laml.maf,
                               num.genes = 3, significant.genes = 1,
                               pval = TRUE)
```

maf2matrix

Convert a MAF file to a mutation matrix

Description

Create a mutation matrix using variant types

Usage

```
maf2matrix(maf, surv.data = NULL, sample.name = "Tumor_Sample_Barcode",
           gene.name = "Hugo_Symbol", variant.type = "Variant_Classification")
```

Arguments

| | |
|--------------|--|
| maf | a MAF file |
| surv.data | survival data for sample names (default: NULL) |
| sample.name | the column name containing sample names (default: "Tumor_Sample_Barcode") |
| gene.name | the column name containing gene names (default: "Hugo_Symbol") |
| variant.type | the column name containing variant types (default: "Variant_Classification") |

Value

a mutation matrix

Author(s)

Dongmin Jung

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml.maf <- read.csv(laml.maf, sep = "\t")
laml.mat <- maf2matrix(laml.maf)
```

plot.survtype

Plot of survival curves of sample subtypes

Description

Survival curves for subtypes of samples can be drawn.

Usage

```
## S3 method for class 'survtype'
plot(object, ...)
```

Arguments

| | |
|--------|--|
| object | object of class "survtype" |
| ... | additional parameters for the "ggsurvplot" |

Value

Survival curves

Author(s)

Dongmin Jung

See Also

survminer::ggsurvplot

Examples

```
data(ovarian)
ovarian.survtype <- Surv.survtype(ovarian, time = "fuptime", status = "fustat")
plot(ovarian.survtype, pval = TRUE)
```

`quantile_normalization`*Normalize a gene expression profile*

Description

Normalize expression data using quantile normalization

Usage

```
quantile_normalization(x)
```

Arguments

`x` an expression profile

Value

a normalized matrix

Author(s)

Dongmin Jung

Examples

```
set.seed(1)
nrows <- 10
ncols <- 5
counts <- matrix(runif(nrows * ncols, 1, 1e4), nrows)
normalized.matrix <- quantile_normalization(counts)
```

`Single.survgroup`*Patient group identification via survival information and expression of a single gene*

Description

All midpoints of the expression level or real-valued statistic are investigated to find the best threshold giving the most significant difference between two groups. Any patients having the value greater than the best cutoff are assigned as the "high-score" class. Otherwise, the others belong to the "low-score" class.

Usage

```
Single.survgroup(surv.data, time, status, single.gene, intermediate = FALSE,
                 group.names = c("High", "Intermediate", "Low"))
```

Arguments

| | |
|--------------|---|
| surv.data | survival data |
| time | survival time |
| status | status indicator |
| single.gene | expression level of a single gene |
| intermediate | a logical value indicating whether or not the intermediate class is considered (default: FALSE) |
| group.names | the name of clusters for "high-score", "intermediate-score", and "low-score" classes (default: "High", "Intermediate", "Low") |

Value

| | |
|-----------|---|
| time | survival time |
| status | status indicator |
| surv.data | survival data |
| score | a vector of scores |
| summary | a list of thresholds, chi-squared statistics and p-values |
| cluster | a vector of clusters to which samples are assigned |
| fit | fitted survival curves |

Author(s)

Dongmin Jung

See Also

survival::Surv, survival::survfit, survival::survdiff

Examples

```
set.seed(1)
nrows <- 1
ncols <- nrow(ovarian)
counts <- matrix(runif(nrows * ncols, 1, 1e4), nrows)
colnames(counts) <- paste("X", 1:ncols, sep = "")
rownames(ovarian) <- paste("X", 1:ncols, sep = "")
Single.ovarian <- Single.survgroup(ovarian, time = "fuptime", status = "fustat", counts[1,])
plot(Single.ovarian, pval = TRUE)
```

Surv.survtype

Sample subtype identification via survival information

Description

Any patient who lived longer than the median was considered to be a "low-risk" patient, and any patient that lived less than the median was considered to be a "high-risk" patient. In this manner, we assigned a class label to each observation. For censored data, we can estimate the probability that each censored observation belongs to the "low-risk" and "high-risk" classes, respectively.

Usage

```
Surv.survtype(surv.data, time, status)
```

Arguments

| | |
|------------------------|------------------|
| <code>surv.data</code> | survival data |
| <code>time</code> | survival time |
| <code>status</code> | status indicator |

Value

| | |
|------------------------|--|
| <code>n</code> | the number of subjects in each group |
| <code>obs</code> | the weighted observed number of events in each group |
| <code>exp</code> | the weighted expected number of events in each group |
| <code>chisq</code> | the chi-squared statistic for a test of equality |
| <code>call</code> | the matched call |
| <code>cluster</code> | a vector of clusters to which samples are assigned |
| <code>time</code> | survival time |
| <code>status</code> | status indicator |
| <code>surv.data</code> | survival data |
| <code>fit</code> | fitted survival curves |

Author(s)

Dongmin Jung

References

Bair, E., & Tibshirani, R. (2004). Semi-supervised methods to predict patient survival from gene expression data. *PLoS biology*, 2(4), e108.

See Also

`survival::Surv`, `survival::survfit`, `survival::survdiff`

Examples

```
data(ovarian)
ovarian.survtype <- Surv.survtype(ovarian, time = "fuptime", status = "fustat")
```

Index

Exprs.survtype, [2](#)

gene.clust, [3](#)

MAF.survgroup, [4](#)

maf2matrix, [5](#)

plot (plot.survtype), [6](#)

plot.survtype, [6](#)

quantile_normalization, [7](#)

Single.survgroup, [7](#)

Surv.survtype, [8](#)