Package 'bioCancer'

November 12, 2026

Title Interactive Multi-Omics Cancers Data Visualization and Analysis

Version 1.41.0

Date 2024-02-14

Description This package is a Shiny App to visualize and analyse interactively Multi-Assays of Cancer Genomic Data.

Depends R (>= 3.6.0), radiant.data (>= 0.9.1), cBioPortalData, XML(>= 3.98)

Imports R.oo, R.methodsS3, DT (>= 0.3), dplyr (>= 0.7.2), tidyr, shiny (>= 1.0.5), AlgDesign (>= 1.1.7.3), import (>= 1.1.0), methods, AnnotationDbi, shinythemes, Biobase, geNetClassifier, org.Hs.eg.db, org.Bt.eg.db, DOSE, clusterProfiler, reactome.db, ReactomePA, DiagrammeR(<= 1.01), visNetwork, htmlwidgets, plyr, tibble, GO.db

Suggests BiocStyle, prettydoc, rmarkdown, knitr, testthat (>= 0.10.0)

VignetteBuilder knitr

URL https://kmezhoud.github.io/bioCancer/

BugReports https://github.com/kmezhoud/bioCancer/issues

License AGPL-3 | file LICENSE

LazyData true

biocViews GUI, DataRepresentation, Network, MultipleComparison, Pathways, Reactome, Visualization,GeneExpression,GeneTarget

RoxygenNote 7.3.1

Encoding UTF-8

git_url https://git.bioconductor.org/packages/bioCancer

git_branch devel

git_last_commit adaad4e

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-11-12

Author Karim Mezhoud [aut, cre]

Maintainer Karim Mezhoud <kmezhoud@gmail.com>

Contents

.dbEscapeString . . . 3
.getTableName . . . 3
.pickRef . . . 4
AnnotationFuncs . . . 5
attriColorGene . . . 6
attriColorValue . . . 6
attriColorVector . . . 7
attriShape2Gene . . . 8
attriShape2Node . . . 9
bioCancer . . . 9
CGDS . . . 10
checkDimensions . . . 10
coffeewheel . . . 11
coffeewheelOutput . . . 12
displayTable . . . 12
Edges_Diseases_obj . . . 13
epiGenomics . . . 14
findPhantom . . . 14
getEvidenceCodes . . . 15
getFreqMutData . . . 15
getGenesClassification . . . 16
getListProfData . . . 17
getList_Cases . . . 18
getList_GenProfs . . . 18
getOrthologs . . . 19
getProfData . . . 21
getSequensed_SampleSize . . . 22
mapLists . . . 22
metabologram . . . 23
metabologramOutput . . . 24
Mutation_obj . . . 25
Node_df_FreqIn . . . 25
Node_Diseases_obj . . . 26
Node_obj_CNA_ProfData . . . 27
Node_obj_FreqIn . . . 27
Node_obj_Met_ProfData . . . 28
Node_obj_mRNA_Classifier . . . 29
pickGO . . . 30
pickRefSeq . . . 31
removeNAs . . . 32
renderCoffeewheel . . . 32
renderMetabologram . . . 33
reStrColorGene . . . 34
reStrDimension . . . 34
reStrDisease . . . 35
returnTextAreaInput . . . 36
Studies_obj . . . 37
switchButton . . . 37
test.CGDS . . . 38
translate . . . 38

UnifyRowNames 40
user_CNA 41
user_MetHM27 41
user_MetHM450 42
user_mRNA 42
user_Mut 43
whichGeneList 43
widgetThumbnail 44

Index **45**

`.dbEscapeString` *Private Escape string*

Description

Does not escape strings, but raises an error if any character expect normal letters and underscores are found in the string.

Usage

```
.dbEscapeString(str, raise.error = TRUE)
```

Arguments

`str`	String to test
`raise.error`	Logical, whether to raise an error or not.

Value

Invisible logical

`.getTableName` *Gets the table name from the INPARANOID style genus names.*

Description

Gets the table name from the INPARANOID style genus names.

Usage

```
.getTableName(genus)
```

Arguments

`genus`	5 character INPARANOID genus name, such as "BOSTA", "HOMSA" or "MUSMU".

Value

Table name for genus.

Author(s)

Stefan McKinnon Edwards <stefanm.edwards@agrsci.dk>

References

https://www.bioconductor.org/packages/release/bioc/html/AnnotationDbi.html

---

.pickRef *Secret function that does the magic for pickRefSeq.*

Description

Do not use it, use pickRefSeq!

Usage

```
.pickRef(l, priorities, reduce = c("all", "first", "last"))
```

Arguments

l	List.
priorities	How to prioritize.
reduce	How to reduce.

Value

List.

Note

Hey, you found a secret function! Keep it that way!

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

See Also

pickRefSeq

AnnotationFuncs *Annotation translation functions*

Description

Package:	AnnotationFuncs
Type:	Package
Version:	1.3.0
Date:	2011-06-10
License:	GPL-2
LazyLoad:	yes

Details

Functions for handling translations between different identifieres using the Biocore Data Team data-packages (e.g. `org.Bt.eg.db`). Primary functions are `translate` for translating and `getOrthologs` for efficient lookup of homologes using the Inparanoid databases. Other functions include functions for selecting Refseqs or Gene Ontologies (GO).

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

References

https://www.iysik.com/index.php?page=annotation-functions

See Also

`translate`, `getOrthologs`

Examples

```
library(org.Bt.eg.db)
gene.symbols <- c('DRBP1','SERPINA1','FAKE','BLABLA')
# Find entrez identifiers of these genes.
eg <- translate(gene.symbols, org.Bt.egSYMBOL2EG)
# Note that not all symbols were translated.

# Go directly to Refseq identifiers.
refseq <- translate(gene.symbols, from=org.Bt.egSYMBOL2EG, to=org.Bt.egREFSEQ)
# Pick the proteins:
 pickRefSeq(refseq, priorities=c('NP','XP'), reduce='all')
```

attriColorGene *Attribute Color to Gene*

Description

Attribute Color to Gene

Usage

```
attriColorGene(df)
```

Arguments

df	data frame with mRNA or CNA or mutation frequency or methylation (numeric). Without sampleID column.

Value

A list colors for every gene

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

attriColorValue *Attribute Color to Value*

Description

Attribute Color to Value

Usage

```
attriColorValue(Value, df, colors=c(a,b,c),feet)
```

Arguments

Value	integer
df	data frame with numeric values
colors	a vector of 5 colors
feet	the interval between two successive colors in the palette (0.1)

Value

Hex Color Code

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

---

attriColorVector *Attribute color to a vector of numeric values*

Description

Attribute color to a vector of numeric values

Usage

```
attriColorVector(Value, vector, colors=c(a,b,c),feet)
```

Arguments

Value	numeric
vector	A vector of numeric data
colors	3 colors
feet	An interval between two numeric value needed to change the color

Value

A vetor of colors

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

`attriShape2Gene` *Attribute shape to nodes*

Description

Attribute shape to nodes

Usage

```
attriShape2Gene(gene, genelist)
```

Arguments

`gene`	Gene symbol
`genelist`	Gene list

Value

A character "BRCA1[shape = 'circle', "

Examples

```
how <- "runManually"
## Not run:
GeneList <- whichGeneList("73")
attriShape2Gene("P53", GeneList)
attriShape2Gene("GML",GeneList)

## End(Not run)
```

attriShape2Node *Attributes shape to Nodes*

Description

Attributes shape to Nodes

Usage

```
attriShape2Node(gene, genelist)
```

Arguments

gene	symbol "TP53"
genelist	a vector of gene symbol

Value

A data frame with egdes attributes

Examples

```
GeneList <- c("DKK3" , "NBN"  , "MYO6" , "TP53" , "PML"  , "IFI16" ,"BRCA1")
NodeShape <- attriShape2Gene("DKK3", GeneList)
```

bioCancer *Launch bioCancer with default browser*

Description

The Main function to run bioCancer App

Usage

```
bioCancer()
```

Value

web page of bioCancer Shiny App

Examples

```
ShinyApp <-  1
## Not run:
bioCancer()

## End(Not run)
```

CGDS *CGDS connect object to cBioPortal*

Description

Creates a CGDS connection object from a CGDS endpoint URL. This object must be passed on to the methods which query the server.

Usage

```
CGDS(url,verbose=FALSE,ploterrormsg='',token=NULL)
```

Arguments

url	A CGDS URL (required).
verbose	A boolean variable specifying verbose output (default FALSE)
ploterrormsg	An optional message to display in plots if an error occurs (default ")
token	An optional 'Authorization: Bearer' token to connect to cBioPortal instances that require authentication (default NULL)

checkDimensions *Check wich Cases and genetic profiles are available for selected study*

Description

Check wich Cases and genetic profiles are available for selected study

Usage

```
checkDimensions(StudyID)
```

Arguments

StudyID	Study reference using cBioPortal index

Value

A data frame with two column (Cases, Genetic profiles). Every row has a dimension (CNA, mRNA...). The data frame is filled with yes/no response.

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

`coffeewheel` *This is an htmlwidgets-based visualization tool for hierarchical data. It is zoomable, meaning that you can interact with the hierarchy and zoom in/out accordingly.*

Description

This is an htmlwidgets-based visualization tool for hierarchical data. It is zoomable, meaning that you can interact with the hierarchy and zoom in/out accordingly.

Usage

```
coffeewheel(treeData, width=600, height=600, main="", partitionAttribute="value")
```

Arguments

`treeData`	A hierarchical tree data as in example
`width`	600
`height`	600
`main`	Title
`partitionAttribute`	"value"

Value

A circular layout with genetic profile.

Examples

```
How <- "runManually"
## Not run:
 coffeewheel(treeData = sampleWheelData)

## End(Not run)
```

coffeewheelOutput *Widget output function for use in Shiny*

Description

Widget output function for use in Shiny

Usage

```
coffeewheelOutput(outputId, width=700, height=700)
```

Arguments

outputId	id
width	700
height	700

Value

A circular layout with genetic profile in Shiny App.

Examples

```
How <- "runManually"
## Not run:
coffeewheel(treeData = sampleWheelData)

## End(Not run)
```

displayTable *Display dataframe in table using DT package*

Description

Display dataframe in table using DT package

Usage

```
displayTable(df)
```

Arguments

df	a dataframe

Value

A table

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

Edges_Diseases_obj *get Edges dataframe for Gene/Disease association from geNetClassifier*

Description

get Edges dataframe for Gene/Disease association from geNetClassifier

Usage

```
Edges_Diseases_obj(genesclassdetails)
```

Arguments

genesclassdetails	a dataframe from geNetClassifier

Value

A data frame with egdes attributes

Examples

```
GenesClassDetails <- structure(list(Genes = c("FANCF", "MLH1", "MSH2", "ATR", "PARP1",
"CHEK2", "RAD51"), ranking = c(1L, 1L, 1L, 2L, 3L, 1L, 2L), class = c("brca_tcga",
"gbm_tcga", "lihc_tcga", "lihc_tcga", "lihc_tcga", "lusc_tcga",
"lusc_tcga"), postProb = c(1, 0.99, 1, 0.99, 0.99, 1,
0.98), exprsMeanDiff = c(180, 256, -373, -268,
-1482, 258, 143), exprsUpDw = c("UP", "UP", "DOWN",
"DOWN", "DOWN", "UP", "UP")), .Names = c("Genes", "ranking",
"class", "postProb", "exprsMeanDiff", "exprsUpDw"),
class = "data.frame", row.names = c(NA,-7L))

Ed_Diseases_obj <- Edges_Diseases_obj(genesclassdetails=GenesClassDetails)
```

epiGenomics *Default dataset of bioCancer*

Description

Default dataset of bioCancer

Usage

```
epiGenomics
```

Format

An object of class `data.frame` with 48 rows and 7 columns.

Author(s)

Karim Mezhoud <kmezhoud@gmail.com>

findPhantom *Check if PhantomJS is installed. Similar to webshot*

Description

Check if PhantomJS is installed. Similar to webshot

Usage

```
findPhantom()
```

Value

Logic object

Examples

```
How <- "runManually"
## Not run:
findPhantom()

## End(Not run)
```

getEvidenceCodes *Returns GO evidence codes.*

Description

Returns GO evidence codes.

Usage

```
getEvidenceCodes()
```

Value

Matrix of two columns, first column with codes, second column with description of codes.

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

References

?org.Bt.egGO

See Also

pickGO

Examples

```
getEvidenceCodes()
```

getFreqMutData *get mutation frequency*

Description

get mutation frequency

Usage

```
getFreqMutData(list, geneListLabel)
```

Arguments

list	a list of data frame with mutation data. Each data frame is for one study
geneListLabel	file name of geneList examples: "73"

Value

a data frame with mutation frequency. gene is in rows and study is in column

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

`getGenesClassification` *get genes classification*

Description

get genes classification

Usage

```
getGenesClassification(checked_Studies, GeneList,
 samplesize, threshold, listGenProfs, listCases)
```

Arguments

`checked_Studies`	checked studies
`GeneList`	gene list
`samplesize`	sample size
`threshold`	p-value threshold
`listGenProfs`	list of genetic profiles
`listCases`	list of cases

Value

A table with genes classed by study

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
```

```
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

`getListProfData` *get list of data frame with profiles data (CNA,mRNA, Methylation, Mutation...)*

Description

get list of data frame with profiles data (CNA,mRNA, Methylation, Mutation...)

Usage

```
getListProfData(checked_Studies, geneListLabel)
```

Arguments

`checked_Studies`	checked studies in corresponding panel (input$StudiesIDCircos, input$StudiesIDReactome).
`geneListLabel`	The label of GeneList. There are three cases: "Genes" user gene list, "Reactome_GeneList" GeneList plus genes from reactomeFI "file name" from Examples

Value

A LIST of profiles data (CNA, mRNA, Methylation, Mutation, miRNA, RPPA). Each dimension content a list of studies.

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

getList_Cases *get list of cases of each selected study in Classifier panel*

Description

get list of cases of each selected study in Classifier panel

Usage

```
getList_Cases(checked_Studies)
```

Arguments

checked_Studies	checked studies

Value

A list of cases

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

getList_GenProfs *get list of genetic profiles of each selected study in Classifier panel*

Description

get list of genetic profiles of each selected study in Classifier panel

Usage

```
getList_GenProfs(checked_Studies)
```

Arguments

checked_Studies
: checked studies

Value

A list of genetics profiles

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

---

getOrthologs *Performs quicker lookup for orthologs in homologe data packages*

Description

Using the INPARANOID data packages such as `hom.Hs.inp.db` is very, very slow and can take up to 11 min (on this particular developers workstation). This function introduces a new method that can do it in just 20 seconds (on the developers workstation). In addition, it includes options for translating between different identifers both before and after the mapping.

Usage

```
getOrthologs(
  values,
  mapping,
  genus,
  threshold = 1,
  pre.from = NULL,
  pre.to = NULL,
  post.from = NULL,
  post.to = NULL,
  ...
)
```

Arguments

values	Vector, coerced to character vector, of values needed mapping by homology.
mapping	Homology mapping object, such as hom.Hs.inpBOSTA or revmap(hom.Hs.inpBOSTA).
genus	Character vector. 5 character INPARANOID style genus name of the mapping object, e.g. 'BOSTA' for both hom.Hs.inpBOSTA and revmap(hom.Hs.inpBOSTA).
threshold	Numeric value between 0 and 1. Only clustered homologues with a parwise score above the threshold is included. The native implementation has this set to 1.
pre.from	Mapping object if values needs translation before mapping. E.g. values are entrez and hom.Hs.inpBOSTA requires ENSEMBLPROT, hom.Hs.inpAPIME requires Refseq (?). Arguments from and to are just like in translate.
pre.to	Second part of translation before mapping.
post.from	Translate the result from homology mapping to a desired id; just like in translate.
post.to	Second part of translation after mapping.
...	Additional arguments sent to translate.

Value

List. Names of list corresponds to values, except those that could not be mapped nor translated. Entries are character vectors.

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

References

?hom.Hs.inp.db - https://inparanoidb.sbc.su.se/

Berglund, A.C., Sjolund, E., Ostlund, G., Sonnhammer, E.L.L. (2008) InParanoid 6: eukaryotic ortholog clusters with inparalogs *Nucleic Acids Res.* **36**:D263–266

O'Brien, K.P., Maido, R., Sonnhammer, E.L.L (2005) Inparanoid: A Comprehensive Database of Eukaryotic Orthologs *NAR* **33**:D476–D480

Remm, M., Storm, C.E.V, Sonnhammer, E.L.L (2001) Automatic clustering of orthologs and inparalogs from pairwise species comparisons *J. Mol. Biol.* **314**:1041–1052

See Also

translate, .getTableName, mapLists

Examples

```
tmp <-1
```

getProfData *search and get genetic profiles (CNA,mRNA, Methylation, Mutation...)*

Description

search and get genetic profiles (CNA,mRNA, Methylation, Mutation...)

Usage

```
getProfData(study,genProf, listGenProf, GeneList, Mut)
```

Arguments

study	Study ID
genProf	Genetic Profile id (cancer_study_id_[mutations, cna, methylation, mrna]).
listGenProf	A list of Genetic Profiles for one study.
GeneList	A list of genes
Mut	Condition to set if the genetic profile is mutation or not (0,1)

Details

See https://github.com/kmezhoud/bioCancer/wiki

Value

A data frame with Genetic profile

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

`getSequensed_SampleSize` *get samples size of sequensed genes*

Description

get samples size of sequensed genes

Usage

```
getSequensed_SampleSize(StudiesID)
```

Arguments

`StudiesID`	Studies ID as a vector

Value

dataframe with sample size for each selected study.

Examples

```
## Not run:
 sampleSize <- getSequensed_SampleSize(input$StudiesIDCircos)

## End(Not run)
```

`mapLists` *Replaces contents of list A with elements of list B*

Description

Combines two lists, `A` and `B`, such that `names(A)` are preserved, mapping to the values of `B`, using `names(B)` as look up. Ie. replaces values in `A` with values in `B`, using `names(B)` as look up for values in `A`. Once more? See examples. *NB!* None-mapped entries are returned as NA, but can be removed using `removeNAs`.

Usage

```
mapLists(A, B, removeNAs = TRUE)
```

Arguments

`A`	List, elements are coerced to character for mapping to B.
`B`	List.
`removeNAs`	Boolean, whether to remove the `NA`s that occur because an element was not found in `B`.

Value

List.

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

See Also

removeNAs

Examples

```
A <- list('a1'='alpha','a2'='beta','a3'=c('gamma','delta'))
B <- list('alpha'='b1', 'gamma'=c('b2', 'b3'), 'delta'='b4')
mapLists(A, B)
```

---

metabologram *Circular plot of hierarchital data of genetic profile.*

Description

Circular plot of hierarchital data of genetic profile.

Usage

```
metabologram(treeData,width=600,height=600,main="",showLegend=FALSE,
                     legendBreaks=NULL,
                     legendColors=NULL,
                      fontSize=12,
                     legendText="Legend")
```

Arguments

treeData	A hierarchical tree data as in example
width	600
height	600
main	Title
showLegend	FALSE
legendBreaks	NULL
legendColors	NULL
fontSize	12
legendText	Legend

Value

A circular layout with genetic profile.

See Also

https://github.com/armish/metabologram

Examples

```
How <- "runManually"
## Not run:
 metabologram(treeData = sampleWheelData, width=600,
 height=600, main="title", showLegend = TRUE, fontSize = 10,
 legendBreaks=c("NA","Min","Negative", "0", "Positive", "Max"),
 legendColors=c("black","blue","cyan","white","yellow","red") ,
 legendText="Legend")

## End(Not run)
```

`metabologramOutput` *Widget output function for use in Shiny*

Description

Widget output function for use in Shiny

Usage

```
metabologramOutput(outputId, width = 600, height = 500)
```

Arguments

`outputId`	id
`width`	600
`height`	600

Value

A circular plot with genetic profile in Shiny App.

Examples

```
## Not run:
library(bioCancer)
bioCancer::metabologram(treeData = sampleMetabologramData)

## End(Not run)
```

Mutation_obj *Atribute mutation frequency to nodes*

Description

Atribute mutation frequency to nodes

Usage

```
Mutation_obj(list,FreqMutThreshold, geneListLabel)
```

Arguments

list	A list of data frame with mutation data. Each data frame to study
FreqMutThreshold	threshold Rate of cases (patients) having mutation (0-1).
geneListLabel	file name of geneList examples: "73"

Value

A dat frame with mutation frequency. Ech column corresponds to a study.

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

Node_df_FreqIn *Attributes size to Nodes depending on number of interaction*

Description

Attributes size to Nodes depending on number of interaction

Usage

```
Node_df_FreqIn(genelist, freqIn)
```

Arguments

genelist	a vector of genes
freqIn	dataframe with Node interaction frequencies

Value

A data frame with nodes size attributes

Examples

```
Node_df_FreqIn
## Not run:
r_data <- new.env()
r_data[["FreqIn"]] <- structure(list(Genes = c("ATM", "ATR", "BRCA1", "BRCA2", "CHEK1",
"CHEK2", "FANCF", "MDC1", "RAD51"), FreqSum = c(0.04, 0.05, 0.05,
 0.03, 0.05, 0.04, 0.03, 0.03, 0.02)), .Names = c("Genes", "FreqSum"),
 class = "data.frame", row.names = c(NA, -9L))
GeneList <- whichGeneList("DNA_damage_Response")
node_df <- Node_df_FreqIn(GeneList, r_data$FreqIn)

## End(Not run)
```

Node_Diseases_obj *Attributes color and shape to Nodes of Diseases*

Description

Attributes color and shape to Nodes of Diseases

Usage

```
Node_Diseases_obj(genesclassdetails)
```

Arguments

genesclassdetails	a dataframe from geNetClassifier function

Value

A data frame with nodes Shapes and colors

Examples

```
GenesClassDetails <- structure(list(Genes = c("FANCF", "MLH1", "MSH2", "ATR", "PARP1",
"CHEK2", "RAD51"), ranking = c(1L, 1L, 1L, 2L, 3L, 1L, 2L), class = c("brca_tcga",
"gbm_tcga", "lihc_tcga", "lihc_tcga", "lihc_tcga", "lusc_tcga",
"lusc_tcga"), postProb = c(1, 0.99, 1, 0.99, 0.99, 1,
0.98), exprsMeanDiff = c(180, 256, -373, -268,
-1482, 258, 143), exprsUpDw = c("UP", "UP", "DOWN",
"DOWN", "DOWN", "UP", "UP")), .Names = c("Genes", "ranking",
"class", "postProb", "exprsMeanDiff", "exprsUpDw"),
class = "data.frame", row.names = c(NA,-7L))
```

```
Node_Diseases_df <- Node_Diseases_obj(genesclassdetails= GenesClassDetails)
```

`Node_obj_CNA_ProfData` *Attribute CNA data to node border*

Description

Attribute CNA data to node border

Usage

```
Node_obj_CNA_ProfData(list)
```

Arguments

`list`	A list of data frame with CNA data. Each data frame corresponds to a study.

Value

A data frame with node border attributes

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

`Node_obj_FreqIn` *Attribute interaction frequency to node size*

Description

Attribute interaction frequency to node size

Usage

```
Node_obj_FreqIn(geneList)
```

Arguments

geneList	A list of gene symbol

Value

A data frame with node attributes

Examples

```
r_data <- new.env()
r_data[["FreqIn"]] <- structure(list(Genes = c("ATM", "ATR", "BRCA1", "BRCA2", "CHEK1",
"CHEK2", "FANCF", "MDC1", "RAD51"), FreqSum = c(0.04, 0.05, 0.05,
 0.03, 0.05, 0.04, 0.03, 0.03, 0.02)), .Names = c("Genes", "FreqSum"),
 class = "data.frame", row.names = c(NA, -9L))
 ## Not run:
GeneList <- whichGeneList("DNA_damage_Response")
nodeObj <- Node_obj_FreqIn(GeneList)

## End(Not run)
```

Node_obj_Met_ProfData *Attribute gene Methylation to Nodes*

Description

Attribute gene Methylation to Nodes

Usage

```
Node_obj_Met_ProfData(list, type, threshold)
```

Arguments

list	a list of data frame with methylation data
type	HM450 or HM27
threshold	the Rate cases (patients) that have a silencing genes by methylation

Value

a data frame with node shape attributes

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
```

```
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

Node_obj_mRNA_Classifier *Atrribute genes expression to color nodes*

Description

Atrribute genes expression to color nodes

Usage

```
Node_obj_mRNA_Classifier(geneList,genesclassdetails)
```

Arguments

geneList	A gene list.
genesclassdetails	A dataframe with genes classes and genes expression.

Value

A data frame with node color attributes

Examples

```
r_data <- new.env()
input <- NULL

r_data[["FreqIn"]] <- structure(list(Genes = c("ATM", "ATR", "BRCA1", "BRCA2", "CHEK1",
"CHEK2", "FANCF", "MDC1", "RAD51"), FreqSum = c(0.04, 0.05, 0.05,
 0.03, 0.05, 0.04, 0.03, 0.03, 0.02)), .Names = c("Genes", "FreqSum"),
 class = "data.frame", row.names = c(NA, -9L))

GenesClassDetails <- structure(list(Genes = c("FANCF", "MLH1", "MSH2", "ATR", "PARP1",
"CHEK2", "RAD51"), ranking = c(1L, 1L, 1L, 2L, 3L, 1L, 2L), class = c("brca_tcga",
"gbm_tcga", "lihc_tcga", "lihc_tcga", "lihc_tcga", "lusc_tcga",
"lusc_tcga"), postProb = c(1, 0.99, 1, 0.99, 0.99, 1,
0.98), exprsMeanDiff = c(180, 256, -373, -268,
-1482, 258, 143), exprsUpDw = c("UP", "UP", "DOWN",
"DOWN", "DOWN", "UP", "UP")), .Names = c("Genes", "ranking",
"class", "postProb", "exprsMeanDiff", "exprsUpDw"),
class = "data.frame", row.names = c(NA,-7L))
## Not run:
GeneList <- whichGeneList("DNA_damage_Response")
nodeObj <- Node_obj_mRNA_Classifier(GeneList, GenesClassDetails)

## End(Not run)
```

pickGO *Cleans up result from org.Xx.egGO and returns specific GO identifiers*

Description

Cleans up result from org.Xx.egGO and returns GO identifier for either biological process (BP), cellular component (CC), or molecular function (MF). Can be used on list of GOs from translate, or a single list of GOs from an annotation package. May reduce list, if the (sub)list does not contain the chosen class!

Usage

```
pickGO(l, evidence = NA, category = NA)
```

Arguments

l	Character vector, or list of GO identifiers.
evidence	Character vector, filters on which kind of evidence to return; for a larger list see getEvidenceCodes. * Evidence codes may be: c('IMP','IGI','IPI','ISS','IDA','IEP','IEA * Leave as NA to ignore filtering on this part.
category	Character vector, filters on which ontology to return: biological process (BP), cellular component (CC), or molecular function (MF). * Leave as NA to ignore filtering on this part.

Value

List with only the picked elements.

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

See Also

pickRefSeq, getEvidenceCodes, translate

Examples

```
library(org.Bt.eg.db)
genes <- c(280705, 280706, 100327208)
translate(genes, org.Bt.egSYMBOL)

symbols <- c("SERPINA1","KERA","CD5")
refseq <- translate(symbols, from=org.Bt.egSYMBOL2EG, to=org.Bt.egREFSEQ)
# Pick the proteins:
pickRefSeq(refseq, priorities=c('NP','XP'), reduce='all')

# If you wanted do do some further mapping on the result from
# translate, simply use lapply.

library(GO.db)
GO <- translate(genes, org.Bt.egGO)
```

```
# Get all biological processes:
## Not run:
pickGO(GO, category='BP')
 # $`280705`
 # [1] "GO:0006826" "GO:0006879"
 # $`280706`
# [1] "GO:0006590" "GO:0007165" "GO:0042446"
# Get all ontologies with experimental evidence:
pickGO(GO, evidence=c('IMP','IGI','IPI','ISS','IDA','IEP','IEA'))
 # $`280705`
 # [1] "GO:0006826" "GO:0006879" "GO:0005615" "GO:0008199"
 # $`280706`
 # [1] "GO:0006590" "GO:0007165" "GO:0042446" "GO:0005615" "GO:0005179" "GO:0042393"

## End(Not run)
```

`pickRefSeq` *Picks a prioritised RefSeq identifier from a list of identifiers*

Description

When translating to RefSeq, typically multiple identifiers are returned, referring to different types of products, such as genomic molecule, mature mRNA or the protein, and they can be predicted, properties that can be read from the prefix (https://www.ncbi.nlm.nih.gov/refseq/). E.g. "XM_" is predicted mRNA and "NP_" is a protein. Run `?org.Bt.egREFSEQ`.

Usage

```
pickRefSeq(
  l,
  priorities = c("NP", "XP", "NM", "XM"),
  reduce = c("all", "first", "last")
)
```

Arguments

`l`	Vector or list of RefSeqs accessions to pick from. If list given, applies the prioritation to each element in the list.
`priorities`	Character vector of prioritised prefixes to pick by. Eg. `c("NP","NM")` returns RefSeqs starting 'NP', and if none found, those starting 'NM'. If no RefSeqs are found according to the priorities, Null is returned, unless the last element in priorities is '*'. Uses grepl, so see these for pattern matching. Default: c('NP','XP','NM','XM')
`reduce`	Reducing method, either return all annotations (one-to-many relation) or the first or last found annotation. The reducing step is applied after translating to the goal: `all`: returns all annotations `first` or `last`: choose first or last of arbitrarily ordered list.

Value

If vector given, returns vector. If list given, returns list without element where nothing could be picked.

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

Examples

```
library(org.Bt.eg.db)
symbols <- c("SERPINA1","KERA","CD5")
refseq <- translate(symbols, from=org.Bt.egSYMBOL2EG, to=org.Bt.egREFSEQ)
mRNA <- pickRefSeq(refseq, priorities=c('NM','XM'))
proteins <- pickRefSeq(refseq, priorities=c('NP','XP'))
```

---

removeNAs *Removes entries equal* NA *from list or vector*

Description

Removes entries equal NA, but not mixed entries containing, amongst others, NA. Good for use after mapLists that might return entries equal NA.

Usage

```
removeNAs(l)
```

Arguments

l	Vector or list.

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

Examples

```
removeNAs(list('a'=NA, 'b'=c(NA, 'B'), 'c'='C'))
```

---

renderCoffeewheel *Widget render function for use in Shiny*

Description

Widget render function for use in Shiny

Usage

```
renderCoffeewheel(expr,env =  parent.frame(),  quoted = FALSE)
```

Arguments

expr	id
env	parent.frame()
quoted	FALSE

Value

A circular layout with genetic profile in Shiny App.

Examples

```
How <- "runManually"
## Not run:
coffeewheel(treeData = sampleWheelData)

## End(Not run)
```

`renderMetabologram` *Widget render function for use in Shiny*

Description

Widget render function for use in Shiny

Usage

```
renderMetabologram(expr, env= parent.frame(),  quoted = FALSE)
```

Arguments

`expr`	expression
`env`	parent.frame()
`quoted`	FALSE

Value

A circular plot with genetic profile in Shiny App.

Examples

```
## Not run:
library(bioCancer)
bioCancer::metabologram(treeData = sampleMetabologramData)

## End(Not run)
```

reStrColorGene — *Restructure the list of color attributed to the genes in every dimenssion for every studies*

Description

Restructure the list of color attributed to the genes in every dimenssion for every studies

Usage

```
reStrColorGene(df)
```

Arguments

df	data frame with colors attributed to the genes

Value

Hierarchical color attribute: gene > color

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

reStrDimension — *Restructure the list of color attributed to the genes in every study for every dimensions*

Description

Restructure the list of color attributed to the genes in every study for every dimensions

Usage

```
reStrDimension(LIST)
```

Arguments

LIST	list of hierarchical dimensions

Value

Hierarchical structure of: Study > dimensions > gene > color

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

---

reStrDisease *Restructure the list of color attributed to the genes in every disease*

Description

Restructure the list of color attributed to the genes in every disease

Usage

```
reStrDisease(List)
```

Arguments

List	of data frame with color attributes

Value

Hierarchy of dimensions in the same study: dimensions > gene > color

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

`returnTextAreaInput` *Return message when the filter formula is not correct (mRNA > 500)*

Description

Return message when the filter formula is not correct (mRNA > 500)

Usage

```
returnTextAreaInput(inputId,
                            label= NULL,
                            rows = 2,
                           placeholder = NULL,
                           resize= "vertical",
                           value = "")
```

Arguments

`inputId`	The ID of the object
`label`	Text describes the box area
`rows`	Number of rows
`placeholder`	Error message if needed
`resize`	orientation of text
`value`	default text in the area box

Value

text message

Examples

```
ShinyApp <-  1
## Not run:
returnTextAreaInput(inputId = "data-filter",
                    label = "Error message",
                    rows =  2,
                  placeholder = "Provide a filter (e.g., Genes == 'ATM') and press return",
                    resize = "vertical",
                    value="")

## End(Not run)
```

Studies_obj *get object for grViz. Link Studies to genes*

Description

get object for grViz. Link Studies to genes

Usage

```
Studies_obj(df)
```

Arguments

df	data frame with gene classes

Value

grViz object. a data frame with Study attributes

Examples

```
Studies_obj(data.frame("col1", "col2", "col3", "col4", "col5", "col6"))
## Not run:
Genes ranking     class postProb exprsMeanDiff exprsUpDw
1 FANCF       1 brca_tcga  1.00000      179.9226        UP
2  MLH1       1  gbm_tcga  0.99703      256.3173        UP

## End(Not run)
```

switchButton *A function to change the Original checkbox of rshiny into a nice true/false or on/off switch button No javascript involved. Only CSS code.*

Description

To be used with CSS script 'button.css' stored in a 'www' folder in your Shiny app folder

Usage

```
switchButton(inputId, label = NULL, value = FALSE, col = "GB", type = "TF")
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value (TRUE or FALSE).
col	Color set of the switch button. Choose between "GB" (Grey-Blue) and "RG" (Red-Green)
type	Text type of the button. Choose between "TF" (TRUE - FALSE), "OO" (ON - OFF) or leave empty for no text.

test.CGDS *S3 method to test cBioPortal connection*

Description

S3 method to test cBioPortal connection

Usage

```
## S3 method for class 'CGDS'
test(x, ...)
```

Arguments

x	connection object
...	not used

translate *Translate between different identifiers*

Description

Function for translating from one annotation to another, eg. from RefSeq to Ensemble. This function takes a vector of annotation values and translates first to the primary annotation in the Biocore Data Team package (ie. entrez gene identifier for org.Bt.eg.db) and then to the desired product, while removing non-translated annotations and optionally reducing the result so there is only a one-to-one relation.

Usage

```
translate(
  values,
  from,
  to = NULL,
  reduce = c("all", "first", "last"),
  return.list = TRUE,
  remove.missing = TRUE,
  simplify = FALSE,
  ...
)
```

Arguments

values	Vector of annotations that needs translation. Coerced to character vector.
from	Type of annotation values are given in. NB! take care in the orientation of the package, ie. if you have RefSeq annotations, use org.Bt.egREFSEQ2EG or (in some cases) revmap(org.Bt.egREFSEQ).

to	Desired goal, eg. org.Bt.egENSEMBLPROT. If NULL (default), goal if the packages primary annotation (eg. entrez gene for org.Bt.eg.db). Throws a warning if the organisms in from and to are not the same.
reduce	Reducing method, either return all annotations (one-to-many relation) or the first or last found annotation. The reducing step is applied after translating to the goal: all: returns all annotations first or last: choose first or last of arbitrarily ordered list.
return.list	Logical, when TRUE, returns the translation as a list where names
remove.missing	Logical, whether to remove non-translated values, defaults TRUE.
simplify	Logical, unlists the result. Defaults to FALSE. Usefull when using translate in a lapply or sapply.
...	Additional arguments sent to pickGO if from returns GO set.

Details

If you want to do some further mapping on the result, you will have to use either unlist og lapply, where the first returns all the end-products of the first mapping, returning a new list, and the latter produces a list-within-list.

If from returns GO identifiers (e.g. from = org.Bt.egGO), then the returned resultset is more complex and consists of several layers of lists instead of the usual list of character vectors. If to has also been specified, the GO IDs must be extracted (internally) and you have the option of filtering for evidence and category at this point. See pickGO.

Value

List; names of elements are values and the elements are the translated elements, or NULL if not translatable with remove.missing = TRUE.

Note

Requires user to deliver the annotation packages such as org.Bt.egREFSEQ.

Author(s)

Stefan McKinnon Edwards <stefan.hoj-edwards@agrsci.dk>

See Also

pickRefSeq, pickGO

Examples

```
library(org.Bt.eg.db)
genes <- c(280705, 280706, 100327208)
translate(genes, org.Bt.egSYMBOL)

symbols <- c("SERPINA1","KERA","CD5")
refseq <- translate(symbols, from=org.Bt.egSYMBOL2EG, to=org.Bt.egREFSEQ)
# Pick the proteins:
pickRefSeq(refseq, priorities=c('NP','XP'), reduce='all')

# If you wanted do do some further mapping on the result from
# translate, simply use lapply.
```

```
library(GO.db)
GO <- translate(genes, org.Bt.egGO)
```

UnifyRowNames *Unify row names in data frame with the same order of gene list.*

Description

Unify row names in data frame with the same order of gene list.

Usage

```
UnifyRowNames(x,geneList)
```

Arguments

x	data frame with gene symbol in the row name
geneList	a gene list

Value

a data frame having the gene in row name ordered as in gene list.

Examples

```
cgds <- cBioPortal(
hostname = "www.cbioportal.org",
protocol = "https",
api = "/api/v2/api-docs"
)
## Not run:
getDataByGenes( api =  cgds,
studyId = "gbm_tcga_pub",
genes = c("NF1", "TP53", "ABL1"),
by = "hugoGeneSymbol",
molecularProfileIds = "gbm_tcga_pub_mrna"
)

## End(Not run)
```

user_CNA *Example of Copy Number Alteration (CNA) dataset*

Description

Example of Copy Number Alteration (CNA) dataset

Usage

```
user_CNA
```

Format

An object of class `data.frame` with 579 rows and 13 columns.

Author(s)

Karim Mezhoud <kmezhoud@gmail.com>

user_MetHM27 *Example of Methylation HM27 dataset*

Description

Example of Methylation HM27 dataset

Usage

```
user_MetHM27
```

Format

An object of class `data.frame` with 600 rows and 13 columns.

Author(s)

Karim Mezhoud <kmezhoud@gmail.com>

user_MetHM450 *Example of Methylation HM450 dataset*

Description

Example of Methylation HM450 dataset

Usage

```
user_MetHM450
```

Format

An object of class `data.frame` with 10 rows and 13 columns.

Author(s)

Karim Mezhoud <kmezhoud@gmail.com>

user_mRNA *Example of mRNA expression dataset*

Description

Example of mRNA expression dataset

Usage

```
user_mRNA
```

Format

An object of class `data.frame` with 307 rows and 13 columns.

Author(s)

Karim Mezhoud <kmezhoud@gmail.com>

user_Mut *Example of Mutation dataset*

Description

Example of Mutation dataset

Usage

```
user_Mut
```

Format

An object of class `data.frame` with 37 rows and 23 columns.

Author(s)

Karim Mezhoud <kmezhoud@gmail.com>

whichGeneList *Verify which gene list is selected*

Description

Verify which gene list is selected

Usage

```
whichGeneList(geneListLabel)
```

Arguments

`geneListLabel`	The label of GeneList. There are three cases: "Genes" user gene list, "Reactome_GeneList" GeneList plus genes from reactomeFI "file name" from Examples

Value

Gene List label

Examples

```
How <- "runManually"
## Not run:
whichGeneList("102")

## End(Not run)
```

widgetThumbnail *Capture html output widget as .png in R*

Description

Capture html output widget as .png in R

Usage

```
widgetThumbnail(p, thumbName, width = 1024, height = 1024)
```

Arguments

p	is the html widget
thumbName	is the name of the new png file
width	1024
height	1024

Value

3 files .html, .js and .png

Examples

```
How <- "runManually"
## Not run:
# Load package
library(networkD3)
library(htmlwidgets)
# Create fake data
src <- c("A", "A", "A", "A", "B", "B", "C", "C", "D")
target <- c("B", "C", "D", "J", "E", "F", "G", "H", "I")
networkData <- data.frame(src, target)
# Plot
plot = simpleNetwork(networkData)
# Save html as png
widgetThumbnail(p = plot, thumbName = "plot", width = 1024, height = 1024)

## End(Not run)
```

Index

∗ **datasets**
epiGenomics, 14
user_CNA, 41
user_MetHM27, 41
user_MetHM450, 42
user_mRNA, 42
user_Mut, 43
∗ **package**
AnnotationFuncs, 5
-package *(*bioCancer*)*, 9
.dbEscapeString, 3
.getTableName, 3, *20*
.pickRef, 4

AnnotationFuncs, 5
attriColorGene, 6
attriColorValue, 6
attriColorVector, 7
attriShape2Gene, 8
attriShape2Node, 9

bioCancer, 9

CGDS, 10
checkDimensions, 10
coffeewheel, 11
coffeewheelOutput, 12

displayTable, 12

Edges_Diseases_obj, 13
epiGenomics, 14

findPhantom, 14

getEvidenceCodes, 15, *30*
getFreqMutData, 15
getGenesClassification, 16
getList_Cases, 18
getList_GenProfs, 18
getListProfData, 17
getOrthologs, *5*, 19
getProfData, 21
getSequensed_SampleSize, 22

mapLists, *20*, 22, *32*
metabologram, 23
metabologramOutput, 24
Mutation_obj, 25

Node_df_FreqIn, 25
Node_Diseases_obj, 26
Node_obj_CNA_ProfData, 27
Node_obj_FreqIn, 27
Node_obj_Met_ProfData, 28
Node_obj_mRNA_Classifier, 29

pickGO, *15*, 30, *39*
pickRefSeq, *4*, *30*, 31, *39*

removeNAs, *22, 23*, 32
renderCoffeewheel, 32
renderMetabologram, 33
reStrColorGene, 34
reStrDimension, 34
reStrDisease, 35
returnTextAreaInput, 36

Studies_obj, 37
switchButton, 37

test.CGDS, 38
translate, *5*, *20*, *30*, 38

UnifyRowNames, 40
user_CNA, 41
user_MetHM27, 41
user_MetHM450, 42
user_mRNA, 42
user_Mut, 43

whichGeneList, 43
widgetThumbnail, 44