Package 'epivizrChart'

November 13, 2026

Title R interface to epiviz web components

Version 1.35.0

Description This package provides an API for interactive visualization of genomic data using epiviz web components. Objects in R/BioConductor can be used to generate interactive R markdown/notebook documents or can be visualized in the R Studio's default viewer.

Imports epivizrData (>= 1.5.1), epivizrServer, htmltools, rjson, methods, BiocGenerics

Suggests testthat, roxygen2, knitr, Biobase, GenomicRanges, S4Vectors, IRanges, SummarizedExperiment, antiProfilesData, hgu133plus2.db, Mus.musculus, BiocStyle, Homo.sapiens, shiny, minfi, Rsamtools, rtracklayer, RColorBrewer, magrittr, AnnotationHub

Collate 'utils.R' 'EpivizChartDataMgr-class.R' 'EpivizWebComponent-class.R' 'EpivizViewComponent-class.R' 'EpivizDataSource-class.R' 'EpivizEnvironment-class.R' 'EpivizChart-class.R' 'EpivizNavigation-class.R' 'EpivizCharts-classes.R' 'vignette_data.R' 'util-inits.R' 'generics.R'

VignetteBuilder knitr

Depends R (>= 3.4.0)

License Artistic-2.0

Encoding UTF-8

LazyData true

biocViews Visualization, GUI

RoxygenNote 7.1.0

git_url https://git.bioconductor.org/packages/epivizrChart

git_branch devel

git_last_commit 2846232

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-11-12

Author Brian Gottfried [aut], Jayaram Kancherla [aut], Hector Corrada Bravo [aut, cre]

Maintainer Hector Corrada Bravo <hcorrada@gmail.com>

Contents

.constructURL . . . 3
.initialize_chart . . . 3
.register_all_the_epiviz_things . . . 4
.settings_as_df . . . 4
append_region . . . 5
bcode_eset . . . 5
BlocksTrack . . . 6
cgi_gr . . . 6
chart_default_settings_colors . . . 7
EpivizBlocksTrack-class . . . 7
epivizChart . . . 8
EpivizChart-class . . . 9
EpivizChartDataMgr-class . . . 10
EpivizDataSource-class . . . 10
epivizEnv . . . 11
EpivizEnvironment-class . . . 12
EpivizGenesTrack-class . . . 13
EpivizHeatmapPlot-class . . . 13
EpivizIGVTrack-class . . . 14
EpivizLinePlot-class . . . 14
EpivizLineTrack-class . . . 14
epivizNav . . . 15
EpivizNavigation-class . . . 15
EpivizScatterPlot-class . . . 16
EpivizStackedBlocksTrack-class . . . 17
EpivizStackedLinePlot-class . . . 17
EpivizStackedLineTrack-class . . . 17
EpivizViewComponent-class . . . 18
EpivizWebComponent-class . . . 18
get_available_chart_types . . . 19
get_registered_data_types . . . 19
HeatmapPlot . . . 20
json_parser . . . 20
json_writer . . . 21
LinePlot . . . 22
LineTrack . . . 22
plot,EpivizEnvironment,ANY-method . . . 23
rand_id . . . 23
ScatterPlot . . . 24
StackedBlocksTrack . . . 24
StackedLinePlot . . . 25
StackedLineTrack . . . 25
sumexp . . . 26
tcga_colon_blocks . . . 26
tcga_colon_curves . . . 27
tcga_colon_expression . . . 27

Index **29**

.constructURL *Construct URL for Websocket connection between R and UI*

Description

Construct URL for Websocket connection between R and UI

Usage

```
.constructURL(host = "localhost", port = 7123L, path = "")
```

Arguments

host	host
port	port
path	path

Value

url

.initialize_chart *Initialize Epiviz Chart based on chart type*

Description

Initialize Epiviz Chart based on chart type

Usage

```
.initialize_chart(chart_type, ...)
```

Arguments

chart_type	Chart type.
...	Arguments for EpivizChart objects.

.register_all_the_epiviz_things *(taken from epivizr) register epiviz actions*

Description

(taken from epivizr) register epiviz actions

Usage

```
.register_all_the_epiviz_things(srv, app)
```

Arguments

srv	epivizrServer object
app	EpivizApp object

.settings_as_df *(taken from epivizr) print settings in a readable format*

Description

(taken from epivizr) print settings in a readable format

Usage

```
.settings_as_df(chart_settings)
```

Arguments

chart_settings	chart settings

Value

chart settings as data frame

append_region *Generic method to add navigation regions*

Description

Generic method to add navigation regions

Usage

```
append_region(x, ...)

## S4 method for signature 'EpivizEnvironment'
append_region(x, chr, start, end, return_parent = FALSE)
```

Arguments

x	an object of type EpivizEnvironment
...	other parameters
chr	chromosome id. ex. "chr11"
start	genomic region start
end	genomic region end
return_parent	To return the parent or the new navigation element. Defaults to FALSE

bcode_eset *Example expression data from the Gene Expression barcode project*

Description

See vignette data_preprocessing for code to build this object.

Usage

```
data(bcode_eset)
```

Format

An Biobase::ExpressionSet object

BlocksTrack *Method to add Blocks Track*

Description

Method to add Blocks Track

Usage

```
BlocksTrack(x, y, ...)

## S4 method for signature 'EpivizEnvironment'
BlocksTrack(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

cgi_gr *Locations of CpG Islands*

Description

Locations of CpG Islands

Usage

```
data(cgi_gr)
```

Format

A GenomicRanges::GRanges object with locations of CpG Islands in hg19

chart_default_settings_colors *Get default chart settings and colors*

Description

Get default chart settings and colors

Usage

```
chart_default_settings_colors(chart_type)
```

Arguments

chart_type	chart type

Value

list of settings and colors

EpivizBlocksTrack-class *Data container for an Epiviz Blocks Track.*

Description

Data container for an Epiviz Blocks Track.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

epivizChart *Initialize an EpivizChart object to visualize in viewer or knit to HTML.*

Description

Initialize an EpivizChart object to visualize in viewer or knit to HTML.

Usage

```
epivizChart(
  data_obj = NULL,
  measurements = NULL,
  datasource_name = NULL,
  parent = NULL,
  chart = NULL,
  chr = NULL,
  start = NULL,
  end = NULL,
  settings = NULL,
  colors = NULL,
  ...
)
```

Arguments

data_obj	A data object that will register to an EpivizData object.
measurements	An EpivizMeasurement object.
datasource_name	A name for the datasource. For example, "Mean by Sample Type".
parent	An object of class EpivizEnvironment or EpivizNavigation to append the chart within.
chart	The chart type to be visualized: "BlocksTrack", HeatmapPlot", "LinePlot", "LineTrack", "ScatterPlot", "StackedLinePlot", "StackedLineTrack".
chr	The chromosome to filter on, e.g., chr="chr11".
start	The start location, e.g., start=110800000.
end	The end location, e.g., end=130383180.
settings	List of settings, e.g., list(title="Blocks Chart").
colors	List of colors. When chart is rendered to html this will be converted to a string encoded as JSON
...	Additional arguments passed to epivizrData::register, e.g., type="bp", columns=c("normal, cancer").

Value

An object of class EpivizChart.

Examples

```
data(tcga_colon_blocks)
start <- 99800000
end <- 103383180
blocks_track <- epivizChart(tcga_colon_blocks, chr="chr11", start=start, end=end)
# See package vignette for more examples.
```

`EpivizChart-class` *Data container for an Epiviz chart component.*

Description

Data container for an Epiviz chart component.

Fields

`data` (list) Values of an epiviz chart's data attribute.

`colors` (character) Epiviz chart's colors attribute.

`settings` (list) Epiviz chart's settings attribute.

`parent` An object of class `EpivizEnvironment` where chart is appended.

Methods

`get_attributes()` Get attributes for rendering chart

`get_available_settings()` Get available settings

`get_colors()` Get chart colors

`get_data()` Get chart data

`get_parent()` Get parent

`get_settings()` Get chart settings

`navigate(chr, start, end)` Navigate chart to a genomic location

- **chr** Chromosome
- **start** Start location
- **end** End location

`render_component(shiny = FALSE)` Render to html

`revisualize(chart_type)` Revisualize chart as the given chart type

- **chart_type** The type of chart to be visualized (BlocksTrack, HeatmapPlot, LinePlot, LineTrack, ScatterPlot, StackedLinePlot, StackedLineTrack)

`set_colors(colors)` Set chart colors

`set_data(data)` Set chart data

`set_settings(settings)` Modify current settings

- **settings** List of new settings. Call get_available_settings for settings available to modify.

EpivizChartDataMgr-class

Class providing data manager for epiviz charts.

Description

Class providing data manager for epiviz charts.

Fields

`.ms_list` (environment) List of measurment records

`.ms_idCounter` (integer) Counter for ID generator

Methods

`add_genome(genome)` Add genome to data manager (for seqInfo)

chr Chromosome

start Start location

end End location

`add_measurements( obj, datasource_name = NULL, datasource_obj_name = deparse(substitute(obj)), ... )` Register measurements in data manager

`get_data(measurements, chr = NULL, start = NULL, end = NULL)` Get data from data mgr based on measurements, chr, start, and end

measurements List of EpivizMeasurements

chr Chromosome

start Start location

end End location

`register_shiny_handler(session)` Handlers to enable interactions with Shiny session.

session Shiny session object

`rm_all_measurements()` Remove all registered measurements

`rm_measurements(ms_obj_or_id)` Remove registered measurements from a given data object

EpivizDataSource-class

Data container for an Epiviz Data Source component.

Description

Data container for an Epiviz Data Source component.

Fields

`provider_type` (character)

`provider_id` (character)

`provider_url` (character)

Methods

`get_attributes()` Get attributes for rendering web component

`get_component_type()` Get component type for prefix of random id generator

`get_name()` Get name of Epiviz Web Component

`get_provider_id()` Get provider id

`get_provider_type()` Get provider type

`get_provider_url()` Get provider url

`render_component(shiny = FALSE)` Render to html

`set_provder_url(url)` Set provider url

`set_provider_id(id)` Set provider id

`set_provider_type(type)` Set provider type

`epivizEnv` *Initialize an* `EpivizEnvironment` *object.*

Description

Initialize an `EpivizEnvironment` object.

Usage

```
epivizEnv(chr = NULL, start = NULL, end = NULL, interactive = FALSE, ...)
```

Arguments

`chr`	The chromosome to filter on, e.g., `chr="chr11"`
`start`	The start location, e.g., `start=99800000`.
`end`	The end location, e.g., `end=130383180`.
`interactive`	(logical) enable if running a websocket/shiny server
`...`	Additional params to pass to `EpivizWebComponent`

Value

An object of class `EpivizEnvironment`

Examples

```
epiviz <- epivizEnv(chr="chr11", start=99800000, end=103383180)
```

EpivizEnvironment-class

Data container for an Epiviz environment component.

Description

Data container for an Epiviz environment component.

Fields

`charts` List of class `EpivizViewComponent` used to track nested elements.

`interactive` Logical value of whether componenet is interactive with data source componenet..

`epiviz_ds` `EpivizDataSource` object for interactive documents.

Methods

`add_data(...)` Add data to environment's data manager

... Arguments for add_measurements and register, e.g., data, datasource_name, datasource_obj_name, type, etc

`add_genome(genome, type = "gene_info", datasource_name = NULL)` Add a genome to the view, and a genes-track.

genome annotation object. eg. Homo.sapiens

`append_chart(chart)` Append chart or navigation to environment

`append_region(chr = NULL, start = NULL, end = NULL, ...)` Add a child Navigation element to the given genomic region

`get_charts()` Get charts within environment

`get_component_type()` Get component type for prefix of random id generator

`get_measurements()` Get measurements

`get_name()` Get name of Epiviz Web Component

`get_rows(...)` Get row data from environment's data manager

`get_values(...)` Get value data from environment's data manager

`init_region(chr = NULL, start = NULL, end = NULL)` Initialize navigation based on a genomic region

chr Chromosome

start Start location

end End location

`init_regions(regions)` Initialize navigations based on genomic regions

regions List of named lists of genomic locations, e.g., list(list(chr='chr11', start=99800000, end=103383180))

`is_interactive()` Return whether the environment is interactive with a data source

`navigate(chr = NULL, start = NULL, end = NULL)` Navigate environment to genomic location

chr Chromosome

start Start location

end End location

`order_charts(ordered_charts)` Order the charts within an environment

charts An ordered list of EpivizViewComponent objects

`plot(...)` Plot an EpivizChart within the environment

... Arguments for epivizChart

`register_shiny_handler(session)` Enable components to interact with Shiny session.

session Shiny session object

`remove_all_charts()` Remove all charts from environment

`remove_chart(chart)` Remove chart from environment

`render_component(shiny = FALSE)` Render to html

shiny if rendering component in a shiny environment

`set_charts(charts)` Set charts of environment

`EpivizGenesTrack-class` *Data container for an Epiviz Genes Track.*

Description

Data container for an Epiviz Genes Track.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

`EpivizHeatmapPlot-class` *Data container for an Epiviz Heatmap Plot.*

Description

Data container for an Epiviz Heatmap Plot.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

EpivizIGVTrack-class *Data container for an Epiviz Genes Track.*

Description

Data container for an Epiviz Genes Track.

Methods

`get_attributes()` Get attributes for rendering component

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

EpivizLinePlot-class *Data container for an Epiviz Line Plot.*

Description

Data container for an Epiviz Line Plot.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

EpivizLineTrack-class *Data container for an Epiviz Line Track.*

Description

Data container for an Epiviz Line Track.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

epivizNav *Initialize an EpivizNavigation object to visualize in viewer or knit to HTML.*

Description

Initialize an EpivizNavigation object to visualize in viewer or knit to HTML.

Usage

```
epivizNav(
  chr = NULL,
  start = NULL,
  end = NULL,
  parent = NULL,
  interactive = FALSE,
  ...
)
```

Arguments

chr	The chromosome to filter on, e.g., chr="chr11".
start	The start location, e.g., start=99800000.
end	The end location, e.g., end=130383180.
parent	An object of class [EpivizEnvironment] or EpivizNavigation to append the chart within.
interactive	(logical) enable if running a websocket/shiny server
...	Additional arguments for initializing navigation, e.g., gene and geneInRange.

Value

An object of class EpivizNavigation.

Examples

```
epiviz <- epivizNav(chr="chr11", start=99800000, end=103383180)
```

EpivizNavigation-class *Data container for an Epiviz navigation component.*

Description

Data container for an Epiviz navigation component.

Fields

`gene` (character) Gene

`geneInRange` (character) Nearest Gene in range.

`parent` An object of class `EpivizEnvironment` where navigation is appended.

Methods

`add_genome(genome, type = "gene_info", datasource_name = NULL)` Add a genome to the view, and a genes-track.

genome annotation object. eg. Homo.sapiens

`clone_charts(charts)` Clone EpivizCharts and append to navigation. Each chart must already exist in the navigation's data manager, otherwise an error will occur when attempting to initialize using their measurements

charts list of EpivizCharts whose data exists in the navigation's data manager

`get_attributes()` Get attributes for rendering chart

`get_component_type()` Get component type for prefix of random id generator

`get_gene()` Get gene

`get_geneInRange()` Get gene in range

`get_name()` Get name of Epiviz Web Component

`render_component(shiny = FALSE)` Render to html

shiny if rendering component in a shiny environment

`set_gene(gene)` Set gene

`set_geneInRange(gene)` Set step ratio

EpivizScatterPlot-class

Data container for an Epiviz Scatter Plot.

Description

Data container for an Epiviz Scatter Plot.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

EpivizStackedBlocksTrack-class

Data container for an Epiviz Blocks Track.

Description

Data container for an Epiviz Blocks Track.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

EpivizStackedLinePlot-class

Data container for an Epiviz Stacked Line Plot.

Description

Data container for an Epiviz Stacked Line Plot.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

EpivizStackedLineTrack-class

Data container for an Epiviz Stacked Line Track.

Description

Data container for an Epiviz Stacked Line Track.

Methods

`get_component_type()` Get component type for prefix of random id generator

`get_default_colors()` Get default colors

`get_default_settings()` Get default settings

`get_name()` Get name of Epiviz Web Component

EpivizViewComponent-class

Data container for an Epiviz web component.

Description

Data container for an Epiviz web component.

Fields

`chr` (CharacterOrNULL) Chromosome location.

`start` (NumericOrNULL) Start location.

`end` (NumericOrNULL) End location.

`measurements` (ListOrNULL) list of measurements of class `EpivizMeasurement`.

Methods

`get_attributes()` Get attributes for rendering web component

`get_chr()` Get chromosome

`get_end()` Get end

`get_measurements()` Get measurements

`get_start()` Get start

`set_chr(chr)` Set the chromosome

`set_end(end)` Set end

`set_measurements(ms)` Set measurements

`set_start(start)` Set start

EpivizWebComponent-class

Data container for an Epiviz Web component.

Description

Data container for an Epiviz Web component.

Fields

`data_mgr` `EpivizChartDataMgr`

`name` (character) Epiviz chart type (tag name).

`class` (CharacterOrNULL) Epiviz chart's class attribute.

`id` (character) Epiviz chart's id attribute.

Methods

`get_attributes()` Get attributes for rendering web component

`get_class()` Get class

`get_data_mgr()` Get data manager

`get_id()` Get id

`get_name()` Get name of Epiviz Web Component

`set_class(class)` Set chart class

`set_id(id)` Set chart id

`set_name(name)` Set name

---

get_available_chart_types

Construct URL for Websocket connection between R and UI

Description

Construct URL for Websocket connection between R and UI

Usage

```
get_available_chart_types()
```

Value

url

---

get_registered_data_types

Construct URL for Websocket connection between R and UI

Description

Construct URL for Websocket connection between R and UI

Usage

```
get_registered_data_types()
```

Value

url

HeatmapPlot *Method to add Heatmap Plot*

Description

Method to add Heatmap Plot

Usage

```
HeatmapPlot(x, y, ...)

## S4 method for signature 'EpivizEnvironment'
HeatmapPlot(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

json_parser *JSON parser used by this package*

Description

Currently this just renames fromJSON in the rjson package.

Usage

```
json_parser(
  json_str,
  file,
  method = "C",
  unexpected.escape = "error",
  simplify = TRUE
)
```

Arguments

json_str	json string to parse
file	file to read json_Str from
method	method used to parse json
unexpected.escape	handling escape characters, one of error, skip, keep
simplify	if TRUE, convert json-encoded lists to vectors

Value

a JSON object

See Also

fromJSON

Examples

```
json_parser('{"a":true, "b":false, "c":null}')
```

`json_writer` *JSON writer used by this package*

Description

Currently this just renames toJSON in the rjson package.

Usage

```
json_writer(x, indent = 0, method = "C")
```

Arguments

x	object to write to json
indent	integer specifying how much indentation to use when formatting the JSON object; if 0, no pretty-formatting is used
method	method used to write json

Value

a string with JSON encoding of object

See Also

toJSON

Examples

```
json_writer(1:10)
```

LinePlot *Method to add Line Plot*

Description

Method to add Line Plot

Usage

```
LinePlot(x, y, ...)

## S4 method for signature 'EpivizEnvironment'
LinePlot(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

LineTrack *Method to add Line Track*

Description

Method to add Line Track

Usage

```
LineTrack(x, y, ...)

## S4 method for signature 'EpivizEnvironment'
LineTrack(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

plot,EpivizEnvironment,ANY-method *Generic methods to plot charts and add navigation regions*

Description

Generic methods to plot charts and add navigation regions

Usage

```
## S4 method for signature 'EpivizEnvironment,ANY'
plot(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

Examples

```
## Not run:
library(epivizrChart)
library(Homo.sapiens)
require(magrittr)

# example data set
data(sumexp)
# create an environment element
epivizEnv <- epivizEnv()

# chain and add navigation regions and plots.
epivizEnv %>%
plot(sumexp, datasource_name="sumExp", columns=c("cancer", "normal")) %>%
append_region(chr="chr11", start=118000000, end=121000000) %>%
plot(sumexp, datasource_name="sumExp", columns=c("normal", "cancer"))
epivizEnv

## End(Not run)
```

rand_id *Random ID generator for epiviz charts*

Description

Random ID generator for epiviz charts

Usage

```
rand_id(prefix = "")
```

Arguments

prefix	prefix for random ID

Value

random ID

ScatterPlot *Method to add Scatter Plot*

Description

Method to add Scatter Plot

Usage

```
ScatterPlot(x, y, ...)

## S4 method for signature 'EpivizEnvironment'
ScatterPlot(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

StackedBlocksTrack *Method to add Stacked Blocks Track*

Description

Method to add Stacked Blocks Track

Usage

```
StackedBlocksTrack(x, y, ...)

## S4 method for signature 'EpivizEnvironment'
StackedBlocksTrack(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

StackedLinePlot *Method to add Stacked Line Plot*

Description

Method to add Stacked Line Plot

Usage

```
StackedLinePlot(x, y, ...)

## S4 method for signature 'EpivizEnvironment'
StackedLinePlot(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

StackedLineTrack *Method to add Stacked Line Track*

Description

Method to add Stacked Line Track

Usage

```
StackedLineTrack(x, y, ...)

## S4 method for signature 'EpivizEnvironment'
StackedLineTrack(x, y, ...)
```

Arguments

x	an object of type EpivizEnvironment or EpivizNavigation
y	a genomic data object
...	other parameters for the plot method

sumexp *Example SummarizedExperiment for epivizr vignette*

Description

Example SummarizedExperiment for epivizr vignette

Usage

```
data(sumexp)
```

Format

A `SummarizedExperiment::RangedSummarizedExperiment` object.

tcga_colon_blocks *Example methylation data (blocks) for epivizr vignette.*

Description

Example results from methylation analysis of human chromosome 11 using the `minfi` package of TCGA 450k beadarray samples. This object contains large regions of methylation difference between tumor and normal samples obtained from `minfi::blockFinder()`.

Usage

```
data(tcga_colon_blocks)
```

Format

A `GenomicRanges::GRanges` object with 129 and `mcols`:

`value` average smooth methylation difference within block

`area` block area estimate (abs(value) * length)

`cluster` id of cluster blockgroup within which block occurs

`indexStart` index of first cluster in block

`indexEnd` index of last cluster in block

`L` number of clusters in block

`clusterL` number of probes in block

`p.value` permutation p.value based on difference conditioned on length

`fwer` family-wise error rate estimate based on difference conditioned on length

`p.valueArea` permutation p.value based on area

`fwerArea` family-wise error rate estimate based on area

Source

TCGA project: https://tcga-data.nci.nih.gov/tcga/

tcga_colon_curves *Example methylation data (smoothed methylation levels) for epivizr vignette*

Description

Example results from methylation analysis of human chromosome 11 using the `minfi` package of TCGA 450k beadarray samples. This object contains probe cluster level methylation estimates from `minfi::blockFinder()`.

Usage

```
data(tcga_colon_curves)
```

Format

A `GenomicRanges::GRanges` object with 7135 ranges and `mcols`:

`id` probe cluster id

`type` probe cluster type

`blockgroup` probe cluster block group

`diff` raw methylation percentage difference between normal and tumor

`smooth` smooth methylation percentage difference between normal and tumor

`normalMean` mean methylation estimate for normal samples

`cancerMean` mean methylation estimate for cancer samples

Source

TCGA project: https://tcga-data.nci.nih.gov/tcga/

tcga_colon_expression *Example exon-level RNAseq data from TCGA project for epivizr vignette.*

Description

A `SummarizedExperiment::RangedSummarizedExperiment` object containing exon-level counts from RNAseq data for colon tumor and normal tissue from the TCGA project. Only exons in human chromosome 11 are included.

Usage

```
data(tcga_colon_expression)
```

Format

A SummarizedExperiment::RangedSummarizedExperiment object with 12,800 rows (exons) and 40 samples.

`assay(tcga_colon_expression)` exon-level count matrix

`colData(tcga_colon_expression)` a DataFrame containing sample information. Normal/Tumor status is given in column `sample_type`

Source

TCGA project: https://tcga-data.nci.nih.gov/tcga/

Index

.constructURL, 3
.initialize_chart, 3
.register_all_the_epiviz_things, 4
.settings_as_df, 4

append_region, 5
append_region,EpivizEnvironment-method
(append_region), 5

bcode_eset, 5
BlocksTrack, 6
BlocksTrack,EpivizEnvironment-method
(BlocksTrack), 6

cgi_gr, 6
chart_default_settings_colors, 7

EpivizBlocksTrack
(EpivizBlocksTrack-class), 7
EpivizBlocksTrack-class, 7
EpivizChart, *3*, *8*
EpivizChart (EpivizChart-class), 9
epivizChart, 8
EpivizChart-class, 9
EpivizChartDataMgr, *18*
EpivizChartDataMgr
(EpivizChartDataMgr-class), 10
EpivizChartDataMgr-class, 10
EpivizData, *8*
EpivizDataSource, *12*
EpivizDataSource
(EpivizDataSource-class), 10
EpivizDataSource-class, 10
epivizEnv, 11
EpivizEnvironment, *5, 6*, *8, 9*, *11*, *16*, *20*,
22–25
EpivizEnvironment
(EpivizEnvironment-class), 12
EpivizEnvironment-class, 12
EpivizGenesTrack
(EpivizGenesTrack-class), 13
EpivizGenesTrack-class, 13
EpivizHeatmapPlot
(EpivizHeatmapPlot-class), 13
EpivizHeatmapPlot-class, 13
EpivizIGVTrack (EpivizIGVTrack-class),
14
EpivizIGVTrack-class, 14
EpivizLinePlot (EpivizLinePlot-class),
14
EpivizLinePlot-class, 14
EpivizLineTrack
(EpivizLineTrack-class), 14
EpivizLineTrack-class, 14
EpivizMeasurement, *8*, *18*
epivizNav, 15
EpivizNavigation, *6*, *8*, *15*, *20*, *22–25*
EpivizNavigation
(EpivizNavigation-class), 15
EpivizNavigation-class, 15
epivizrData::register, *8*
EpivizScatterPlot
(EpivizScatterPlot-class), 16
EpivizScatterPlot-class, 16
EpivizStackedBlocksTrack
(EpivizStackedBlocksTrack-class),
17
EpivizStackedBlocksTrack-class, 17
EpivizStackedLinePlot
(EpivizStackedLinePlot-class),
17
EpivizStackedLinePlot-class, 17
EpivizStackedLineTrack
(EpivizStackedLineTrack-class),
17
EpivizStackedLineTrack-class, 17
EpivizViewComponent, *12*
EpivizViewComponent
(EpivizViewComponent-class), 18
EpivizViewComponent-class, 18
EpivizWebComponent, *11*
EpivizWebComponent
(EpivizWebComponent-class), 18
EpivizWebComponent-class, 18

fromJSON, *20, 21*

get_available_chart_types, 19

get_registered_data_types, 19

HeatmapPlot, 20
HeatmapPlot,EpivizEnvironment-method
(HeatmapPlot), 20

json_parser, 20
json_writer, 21

LinePlot, 22
LinePlot,EpivizEnvironment-method
(LinePlot), 22
LineTrack, 22
LineTrack,EpivizEnvironment-method
(LineTrack), 22

minfi::blockFinder(), *26*, *27*

plot,EpivizEnvironment,ANY-method, 23

rand_id, 23

ScatterPlot, 24
ScatterPlot,EpivizEnvironment-method
(ScatterPlot), 24
StackedBlocksTrack, 24
StackedBlocksTrack,EpivizEnvironment-method
(StackedBlocksTrack), 24
StackedLinePlot, 25
StackedLinePlot,EpivizEnvironment-method
(StackedLinePlot), 25
StackedLineTrack, 25
StackedLineTrack,EpivizEnvironment-method
(StackedLineTrack), 25
sumexp, 26

tcga_colon_blocks, 26
tcga_colon_curves, 27
tcga_colon_expression, 27
toJSON, *21*