# Package 'miloR'

December 31, 2024

Type Package

Title Differential neighbourhood abundance testing on a graph

Version 2.3.0

**Description** Milo performs single-cell differential abundance testing. Cell states are modelled as representative neighbourhoods on a nearest neighbour graph. Hypothesis testing is performed using either

a negative bionomial generalized linear model or negative binomial generalized linear mixed model.

License GPL-3 + file LICENSE

**Encoding** UTF-8

URL https://marionilab.github.io/miloR

### BugReports https://github.com/MarioniLab/miloR/issues

biocViews SingleCell, MultipleComparison, FunctionalGenomics, Software

LinkingTo Rcpp, RcppArmadillo, RcppEigen, RcppML

**Depends** R (>= 4.0.0), edgeR

- Imports BiocNeighbors, BiocGenerics, SingleCellExperiment, Matrix (>= 1.3-0), MatrixGenerics, S4Vectors, stats, stringr, methods, igraph, irlba, utils, cowplot, BiocParallel, BiocSingular, limma, ggplot2, tibble, matrixStats, ggraph, gtools, SummarizedExperiment, patchwork, tidyr, dplyr, ggrepel, ggbeeswarm, RColorBrewer, grDevices, Rcpp, pracma, numDeriv
- Suggests testthat, mvtnorm, scater, scran, covr, knitr, rmarkdown, uwot, scuttle, BiocStyle, MouseGastrulationData, MouseThymusAgeing, magick, RCurl, MASS, curl, scRNAseq, graphics, sparseMatrixStats

# RoxygenNote 7.3.2

NeedsCompilation no

Collate 'AllClasses.R' 'AllGenerics.R' 'buildFromAdjacency.R' 'buildGraph.R' 'calcNhoodExpression.R' 'calcNhoodDistance.R' 'checkSeparation.R' 'countCells.R' 'findNhoodMarkers.R' 'graphSpatialFDR.R' 'glmm.R' 'makeNhoods.R' 'milo.R'

### Contents

'miloR-package.R' 'methods.R' 'plotNhoods.R' 'sim\_discrete.R' 'sim\_family.R' 'sim\_nbglmm.R' 'sim\_trajectory.R' 'testNhoods.R' 'testDiffExp.R' 'utils.R' 'buildNhoodGraph.R' 'annotateNhoods.R' 'groupNhoods.R' 'findNhoodGroupMarkers.R' 'RcppExports.R' 'miloR.R'

### VignetteBuilder knitr

git\_url https://git.bioconductor.org/packages/miloR

git\_branch devel

git\_last\_commit 959804d

git\_last\_commit\_date 2024-10-29

**Repository** Bioconductor 3.21

Date/Publication 2024-12-30

Author Mike Morgan [aut, cre] (ORCID: <https://orcid.org/0000-0003-0757-0711>), Emma Dann [aut, ctb]

Maintainer Mike Morgan <michael.morgan@abdn.ac.uk>

# Contents

miloR-package 3
annotateNhoods
buildFromAdjacency
buildGraph
buildNhoodGraph
calcNhoodDistance
calcNhoodExpression
checkSeparation
computePvalue
countCells
findNhoodGroupMarkers
findNhoodMarkers
fitGeneticPLGlmm
fitGLMM
$fitPLGlmm  \ldots  \ldots  \ldots  \ldots  \ldots  \ldots  \ldots  \ldots  \ldots $
glmmControl.defaults
graphSpatialFDR
groupNhoods
initialiseG
initializeFullZ
makeNhoods
matrix.trace
Milo-class
Milo-methods
miloR
plotDAbeeswarm
plotNhoodCounts

2

# miloR-package

plotNhoodExpressionDA	38
plotNhoodGraph	40
plotNhoodGraphDA	41
plotNhoodGroups	42
plotNhoodMA	43
plotNhoodSizeHist	44
Satterthwaite_df	45
sim_discrete	46
sim_family	47
sim_nbglmm	47
sim_trajectory	48
testDiffExp	49
testNhoods	51
	55

# Index

miloR-package

The miloR package

# Description

The **miloR** package provides modular functions to perform differential abundance testing on replicated single-cell experiments. For details please see the vignettes vignette("milo\_demo", package="miloR") and vignette("milo\_gastrulation", package="miloR").

# Value

The miloR package

# Author(s)

Mike Morgan & Emma Dann

annotateNhoods Add annotations from colData to DA testing results

# Description

This function assigns a categorical label to neighbourhoods in the differential abundance results data.frame (output of testNhoods), based on the most frequent label among cells in each neighbourhood. This can be useful to stratify DA testing results by cell types or samples. Also the fraction of cells carrying that label is stored.

### Usage

```
annotateNhoods(x, da.res, coldata_col, subset.nhoods = NULL)
```

3

### Arguments

х	A Milo object containing single-cell gene expression and neighbourhoods.
da.res	A data.frame containing DA results, as expected from running testNhoods.
coldata_col	A character scalar determining which column of $colData(x)$ stores the annotation to be added to the neighbourhoods
subset.nhoods	A character, numeric or logical vector that will subset the annotation to the spe- cific nhoods. If a character vector these should correspond to row names of nhoodCounts. If a logical vector then these should have the same length as nrow of nhoodCounts. If numeric, then these are assumed to correspond to in- dices of nhoodCounts - if the maximal index is greater than nrow(nhoodCounts(x)) an error will be produced. This is necessary if testNhoods was run using subset.nhoods=

### Details

For each neighbourhood, this calculates the most frequent value of colData(x)[coldata\_col] among cells in the neighbourhood and assigns that value as annotation for the neighbourhood, adding a column in the da.res data.frame. In addition, a coldata\_col\_fraction column will be added, storing the fraction of cells carrying the assigned label. While in practice neighbourhoods are often homogeneous, one might choose to remove an annotation label when the fraction of cells with the label is too low (e.g. below 0.6).

# Value

A data.frame of model results (as da.res input) with two new columns: (1) coldata\_col storing the assigned label for each neighbourhood; (2) coldata\_col\_fraction storing the fraction of cells in the neighbourhood with the assigned label.

# Author(s)

Emma Dann

### Examples

NULL

buildFromAdjacency Build a graph from an input adjacency matrix

# Description

Construct a kNN-graph from an input adjacency matrix - either binary or distances between NNs.

# buildGraph

### Arguments

x	An n X n matrix of single-cells, where values represent edges between cells; 0 values are taken to mean no edge between cells. If the matrix is not binary, then it is assumed the values are distances; 0 retain the same meaning. This behaviour can be toggled using is.binary=TRUE.
k	(optional) Scalar value that represents the number of nearest neighbours in the original graph. This can also be inferred directly from the adjacency matrix x.
is.binary	Logical scalar indicating if the input matrix is binary or not.

# Details

This function will take a matrix as input and construct the kNN graph that it describes. If the matrix is not symmetric then the graph is assumed to be directed, whereas if the matrix is not binary, i.e. all 0's and 1's then the input values are taken to be distances between graph vertices; 0 values are assumed to represent a lack of edge between vertices.

# Value

A Milo with the graph slot populated.

# Author(s)

Mike Morgan

#### Examples

```
r <- 1000
c <- 1000
k <- 35
m <- floor(matrix(runif(r*c), r, c))
for(i in seq_along(1:r)){
    m[i, sample(1:c, size=k)] <- 1
}
```

milo <- buildFromAdjacency(m)</pre>

buildGraph

Build a k-nearest neighbour graph

# Description

This function is borrowed from the old buildKNNGraph function in scran. Instead of returning an igraph object it populates the graph and distance slots in a Milo object. If the input is a Single-CellExperiment object or a matrix then it will return a de novo Milo object with the same slots filled.

# Usage

```
buildGraph(
    x,
    k = 10,
    d = 50,
    transposed = FALSE,
    get.distance = FALSE,
    reduced.dim = "PCA",
    BNPARAM = KmknnParam(),
    BSPARAM = bsparam(),
    BPPARAM = SerialParam()
)
```

# Arguments

X	A matrix, SingleCellExperiment or Milo object containing feature X cell gene expression data.
k	An integer scalar that specifies the number of nearest-neighbours to consider for the graph building.
d	The number of dimensions to use if the input is a matrix of cells X reduced dimensions. If this is provided, transposed should also be set=TRUE.
transposed	Logical if the input x is transposed with rows as cells.
get.distance	A logical scalar whether to compute distances during graph construction.
reduced.dim	A character scalar that refers to a specific entry in the reduceDim slot of the ${\tt Milo}$ object.
BNPARAM	refer to buildKNNGraph for details.
BSPARAM	refer to buildKNNGraph for details.
BPPARAM	refer to buildKNNGraph for details.

# Details

This function computes a k-nearest neighbour graph. Each graph vertex is a single-cell connected by the edges between its neighbours. Whilst a kNN-graph is strictly directed, we remove directionality by forcing all edge weights to 1; this behaviour can be overriden by providing directed=TRUE.

If you wish to use an alternative graph structure, such as a shared-NN graph I recommend you construct this separately and add to the relevant slot in the Milo object.

# Value

A Milo object with the graph and distance slots populated.

# Author(s)

Mike Morgan, with KNN code written by Aaron Lun & Jonathan Griffiths.

6

# buildNhoodGraph

# Examples

buildNhoodGraph Build an abstracted graph of neighbourhoods for visualization

# Description

Build an abstracted graph of neighbourhoods for visualization

### Usage

```
buildNhoodGraph(x, overlap = 1)
```

### Arguments

х	A Milo object with a non-empty nhoods slot.
overlap	A numeric scalar that thresholds graph edges based on the number of overlap-
	ping cells between neighbourhoods.

# Details

This constructs a weighted graph where nodes represent neighbourhoods and edges represent the number of overlapping cells between two neighbourhoods.

# Value

A Milo object containg an igraph graph in the nhoodGraph slot.

### Author(s)

Emma Dann

### Examples

NULL

calcNhoodDistance Co

### Description

This function will calculate Euclidean distances between single-cells in a neighbourhood using the same dimensionality as was used to construct the graph. This step follows the makeNhoods call to limit the number of distance calculations required.

### Usage

```
calcNhoodDistance(x, d, reduced.dim = NULL, use.assay = "logcounts")
```

### Arguments

X	A Milo object with a valid graph slot. If reduced.dims is not provided and there is no valid populated reducedDim slot in x, then this is computed first with $d + 1$ principal components.
d	The number of dimensions to use for computing within-neighbourhood dis- tances. This should be the same value used construct the graph.
reduced.dim	If x is an Milo object, a character indicating the name of the reducedDim slot in the Milo object to use as (default: 'PCA'). Otherwise this should be an N X P matrix with rows in the same order as the columns of the input Milo object x.
use.assay	A character scalar defining which assay slot in the Milo to use

# Value

A Milo object with the distance slots populated.

# Author(s)

Mike Morgan, Emma Dann

calcNhoodExpression Average expression within neighbourhoods

### Description

This function calculates the mean expression of each feature in the Milo object stored in the assays slot. Neighbourhood expression data are stored in a new slot nhoodExpression.

# Usage

calcNhoodExpression(x, assay = "logcounts", subset.row = NULL, exprs = NULL)

### Arguments

x	A Milo object with nhoods slot populated, alternatively a NxM indicator matrix of N cells and M nhoods.
assay	A character scalar that describes the assay slot to use for calculating neighbour- hood expression.
subset.row	A logical, integer or character vector indicating the rows of x to use for sumamrizing over cells in neighbourhoods.
exprs	If x is a list of neighbourhoods, exprs is a matrix of genes X cells to use for calculating neighbourhood expression.

# Details

This function computes the mean expression of each gene, subset by subset.rows where present, across the cells contained within each neighbourhood.

# Value

A Milo object with the nhoodExpression slot populated.

# Author(s)

Mike Morgan

```
require(SingleCellExperiment)
m <- matrix(rnorm(100000), ncol=100)
milo <- Milo(SingleCellExperiment(assays=list(logcounts=m)))
milo <- buildGraph(m, k=20, d=30)
milo <- makeNhoods(milo)
milo <- calcNhoodExpression(milo)
dim(nhoodExpression(milo))</pre>
```

checkSeparation

# Description

Check the count distributions for each nhood according to a test variable of interest. This is important for checking if there is separation in the GLMM to inform either nhood subsetting or recomputation of the NN-graph and refined nhoods.

### Arguments

Milo object with a non-empty nhoodCounts slot.
A data.frame containing meta-data in which condition is a column variable. The rownames must be the same as, or a subset of, the colnames of $nhoodCounts(x)$ .
A character scalar of the test variable contained in design.df. This should be a factor variable if it is numeric or character it will be cast to a factor variable.
A numeric scalar that sets the minimum number of counts across condition level samples, below which separation is defined.
A logical scalar that sets the factor variable level checking. See <i>details</i> for more information.

### Details

This function checks across nhoods for separation based on the separate levels of an input factor variable. It checks if *condition* is a factor variable, and if not it will cast it to a factor. Note that the function first checks for the number of unique values - if this exceeds > 50 error is generated. Users can override this behaviour with factor.check=FALSE.

# Value

A logical vector of the same length as ncol(nhoodCounts(x)) where *TRUE* values represent nhoods where separation is detected. The output of this function can be used to subset nhood-based analyses e.g. testNhoods(..., subset.nhoods=checkSepartion(x, ...)).

# Author(s)

Mike Morgan

```
library(SingleCellExperiment)
ux.1 <- matrix(rpois(12000, 5), ncol=400)
ux.2 <- matrix(rpois(12000, 4), ncol=400)
ux <- rbind(ux.1, ux.2)
vx <- log2(ux + 1)
pca <- prcomp(t(vx))</pre>
```

```
sce <- SingleCellExperiment(assays=list(counts=ux, logcounts=vx),</pre>
                               reducedDims=SimpleList(PCA=pca$x))
milo <- Milo(sce)</pre>
milo <- buildGraph(milo, k=20, d=10, transposed=TRUE)</pre>
milo <- makeNhoods(milo, k=20, d=10, prop=0.3)</pre>
milo <- calcNhoodDistance(milo, d=10)</pre>
cond <- rep("A", ncol(milo))</pre>
cond.a <- sample(1:ncol(milo), size=floor(ncol(milo)*0.25))</pre>
cond.b <- setdiff(1:ncol(milo), cond.a)</pre>
cond[cond.b] <- "B"</pre>
meta.df <- data.frame(Condition=cond, Replicate=c(rep("R1", 132), rep("R2", 132), rep("R3", 136)))</pre>
meta.df$SampID <- paste(meta.df$Condition, meta.df$Replicate, sep="_")</pre>
milo <- countCells(milo, meta.data=meta.df, samples="SampID")</pre>
test.meta <- data.frame("Condition"=c(rep("A", 3), rep("B", 3)), "Replicate"=rep(c("R1", "R2", "R3"), 2))</pre>
test.meta$Sample <- paste(test.meta$Condition, test.meta$Replicate, sep="_")</pre>
rownames(test.meta) <- test.meta$Sample</pre>
check.sep <- checkSeparation(milo, design.df=test.meta, condition='Condition')</pre>
sum(check.sep)
```

computePvalue Compute the p-value for the fixed effect parameters

# Description

Based on the asymptotic t-distribution, comptue the 2-tailed p-value that estimate != 0. This function is not intended to be used directly, but is included for reference or if an alternative estimate of the degrees of freedom is available.

#### Usage

```
computePvalue(Zscore, df)
```

#### Arguments

Zscore	A numeric vector containing the Z scores for each fixed effect parameter
df	A numeric vector containing the estimated degrees of freedom for each fixed effect parameter
	eneer parameter

# Details

Based on sampling from a 2-tailed t-distribution with df degrees of freedom, compute the probability that the calculated Zscore is greater than or equal to what would be expected from random chance.

# Value

Numeric vector of p-values, 1 per fixed effect parameter

# Author(s)

Mike Morgan & Alice Kluzer

# Examples

NULL

countCells

Count cells in neighbourhoods

# Description

This function quantifies the number of cells in each neighbourhood according to an input experimental design. This forms the basis for the differential neighbourhood abundance testing.

# Usage

```
countCells(x, samples, meta.data = NULL)
```

# Arguments

Х	A Milo object with non-empty graph and nhoods slots.
samples	Either a string specifying which column of data should be used to identify the experimental samples for counting, or a named vector of sample ids mapping each single cell to it's respective sample.
meta.data	A cell X variable data.frame containing study meta-data including experimen- tal sample IDs. Assumed to be in the same order as the cells in the input Milo object.

# Details

This function generates a counts matrix of nhoods X samples, and populates the nhoodCounts slot of the input Milo object. This matrix is used down-stream for differential abundance testing.

# Value

A Milo object containing a counts matrix in the nhoodCounts slot.

# Author(s)

Mike Morgan, Emma Dann

# findNhoodGroupMarkers

# Examples

```
library(igraph)
m <- matrix(rnorm(100000), ncol=100)
milo <- buildGraph(t(m), k=20, d=10)
milo <- makeNhoods(milo, k=20, d=10, prop=0.3)
cond <- rep("A", nrow(m))
cond.a <- sample(seq_len(nrow(m)), size=floor(nrow(m)*0.25))
cond.b <- setdiff(seq_len(nrow(m)), cond.a)
cond[cond.b] <- "B"
meta.df <- data.frame(Condition=cond, Replicate=c(rep("R1", 330), rep("R2", 330), rep("R3", 340)))
meta.df$SampID <- paste(meta.df$Condition, meta.df$Replicate, sep="_")
milo <- countCells(milo, meta.data=meta.df, samples="SampID")
milo</pre>
```

findNhoodGroupMarkers Identify post-hoc neighbourhood marker genes

### Description

This function will perform differential gene expression analysis on groups of neighbourhoods. Adjacent and concordantly DA neighbourhoods can be defined using groupNhoods or by the user. Cells *between* these aggregated groups are compared. For differential gene experession based on an input design *within* DA neighbourhoods see testDiffExp.

# Usage

```
findNhoodGroupMarkers(
    x,
    da.res,
    assay = "logcounts",
    aggregate.samples = FALSE,
    sample_col = NULL,
    subset.row = NULL,
    gene.offset = TRUE,
    subset.nhoods = NULL,
    subset.groups = NULL,
    na.function = "na.pass"
)
```

### Arguments

х	A Milo object containing single-cell gene expression and neighbourhoods.
da.res	A data.frame containing DA results, as expected from running testNhoods, as
	a NhoodGroup column specifying the grouping of neighbourhoods, as expected
	from

assay	A character scalar determining which assays slot to extract from the Milo object to use for DGE testing.
aggregate.sampl	es
	logical indicating wheather the expression values for cells in the same sample and neighbourhood group should be merged for DGE testing. This allows to perform testing exploiting the replication structure in the experimental design, rather than treating single-cells as independent replicates. The function used for aggregation depends on the selected gene expression assay: if assay="counts" the expression values are summed, otherwise we take the mean.
sample_col	a character scalar indicating the column in the colData storing sample information (only relevant if <code>aggregate.samples==TRUE</code> )
subset.row	A logical, integer or character vector indicating the rows of x to use for sumamrizing over cells in neighbourhoods.
gene.offset	A logical scalar the determines whether a per-cell offset is provided in the DGE GLM to adjust for the number of detected genes with expression $> 0$ .
subset.nhoods	A logical, integer or character vector indicating which neighbourhoods to subset before aggregation and DGE testing (default: NULL).
subset.groups	A character vector indicating which groups to test for markers (default: NULL)
na.function	A valid NA action function to apply, should be one of na.fail, na.omit, na.exclude, na.pass.

# Details

Using a one vs. all approach, each aggregated group of cells is compared to all others using the single-cell log normalized gene expression with a GLM (for details see limma-package), or the single-cell counts using a negative binomial GLM (for details see edgeR-package). When using the latter it is recommended to set gene.offset=TRUE as this behaviour adjusts the model offsets by the number of detected genes in each cell.

### Value

A data.frame of DGE results containing a log fold change and adjusted p-value for each aggregated group of neighbourhoods. If return.groups then the return value is a list with the slots groups and dge containing the aggregated neighbourhood groups per single-cell and marker gene results, respectively.

*Warning*: If all neighbourhoods are grouped together, then it is impossible to run findNhoodMarkers. In this (hopefully rare) instance, this function will return a warning and return NULL.

### Examples

NULL

# Description

This function will perform differential gene expression analysis on differentially abundant neighbourhoods, by first aggregating adjacent and concordantly DA neighbourhoods, then comparing cells *between* these aggregated groups. For differential gene expression based on an input design *within* DA neighbourhoods see testDiffExp.

# Arguments

х	A Milo object containing single-cell gene expression and neighbourhoods.
da.res	A data.frame containing DA results, as expected from running testNhoods.
da.fdr	A numeric scalar that determines at what FDR neighbourhoods are declared DA for the purposes of aggregating across concorantly DA neighbourhoods.
assay	A character scalar determining which assays slot to extract from the Milo object to use for DGE testing.
aggregate.sampl	es
	logical indicating wheather the expression values for cells in the same sample and neighbourhood group should be merged for DGE testing. This allows to perform testing exploiting the replication structure in the experimental design, rather than treating single-cells as independent replicates. The function used for aggregation depends on the selected gene expression assay: if assay="counts" the expression values are summed, otherwise we take the mean.
sample_col	a character scalar indicating the column in the colData storing sample information (only relevant if <code>aggregate.samples==TRUE</code> )
overlap	A scalar integer that determines the number of cells that must overlap between adjacent neighbourhoods for merging.
lfc.threshold	A scalar that determines the absolute log fold change above which neighbour- hoods should be considerd 'DA' for merging. Default=NULL
merge.discord	A logical scalar that overrides the default behaviour and allows adjacent neigh- bourhoods to be merged if they have discordant log fold change signs. Using this argument is generally discouraged, but may be useful for constructing an empirical null group of cells, regardless of DA sign.
subset.row	A logical, integer or character vector indicating the rows of x to use for sumamrizing over cells in neighbourhoods.
gene.offset	A logical scalar the determines whether a per-cell offset is provided in the DGE GLM to adjust for the number of detected genes with expression > 0.
return.groups	A logical scalar that returns a data.frame of the aggregated groups per single- cell. Cells that are members of non-DA neighbourhoods contain NA values.
subset.nhoods	A logical, integer or character vector indicating which neighbourhoods to subset before aggregation and DGE testing.

na.function	A valid NA action function to apply, should be one of na.fail, na.omit, na.exclude, na.pass.
compute.new	A logical scalar indicating whether to force computing a new neighbourhood adjacency matrix if already present.

# Details

Louvain clustering is applied to the neighbourhood graph. This graph is first modified based on two criteria: 1) neighbourhoods share at least overlap number of cells, and 2) the DA log fold change sign is concordant. This behaviour can be modulated by setting overlap to be more or less stringent. Additionally, a threshold on the log fold-changes can be set, such that lfc.threshold is required to retain edges between adjacent neighbourhoods. Note: adjacent neighbourhoods will never be merged with opposite signs.

Using a one vs. all approach, each aggregated group of cells is compared to all others using the single-cell log normalized gene expression with a GLM (for details see limma-package), or the single-cell counts using a negative binomial GLM (for details see edgeR-package). When using the latter it is recommended to set gene.offset=TRUE as this behaviour adjusts the model offsets by the number of detected genes in each cell.

### Value

A data.frame of DGE results containing a log fold change and adjusted p-value for each aggregated group of neighbourhoods. If return.groups then the return value is a list with the slots groups and dge containing the aggregated neighbourhood groups per single-cell and marker gene results, respectively.

*Warning*: If all neighbourhoods are grouped together, then it is impossible to run findNhoodMarkers. In this (hopefully rare) instance, this function will return a warning and return NULL.

# Author(s)

Mike Morgan & Emma Dann

# fitGeneticPLGlmm

```
cond.a <- sample(seq_len(ncol(milo)), size=floor(ncol(milo)*0.25))
cond.b <- setdiff(seq_len(ncol(milo)), cond.a)
cond[cond.b] <- "B"
meta.df <- data.frame(Condition=cond, Replicate=c(rep("R1", 132), rep("R2", 132), rep("R3", 136)))
meta.df$SampID <- paste(meta.df$Condition, meta.df$Replicate, sep="_")
milo <- countCells(milo, meta.data=meta.df, samples="SampID")
test.meta <- data.frame("Condition"=c(rep("A", 3), rep("B", 3)), "Replicate"=rep(c("R1", "R2", "R3"), 2))
test.meta$Sample <- paste(test.meta$Condition, test.meta$Replicate, sep="_")
rownames(test.meta) <- test.meta$Sample
da.res <- testNhoods(milo, design=~0 + Condition, design.df=test.meta[colnames(nhoodCounts(milo)), ])
nhood.dge <- findNhoodMarkers(milo, da.res, overlap=1, compute.new=TRUE)
nhood.dge
```

fitGeneticPLG1mm GLMM parameter estimation using pseudo-likelihood with a custom covariance matrix

# Description

Iteratively estimate GLMM fixed and random effect parameters, and variance component parameters using Fisher scoring based on the Pseudo-likelihood approximation to a Normal loglihood. This function incorporates a user-defined covariance matrix, e.g. a kinship matrix for genetic analyses.

### Usage

```
fitGeneticPLGlmm(
  Ζ,
  Χ,
 Κ,
  muvec.
  offsets,
  curr_beta,
  curr_theta,
  curr_u,
  curr_sigma,
  curr_G,
  у,
  u_indices,
  theta_conv,
  rlevels,
  curr_disp,
  REML,
  maxit,
  solver,
  vardist
)
```

### Arguments

Z	mat - sparse matrix that maps random effect variable levels to observations
Х	mat - sparse matrix that maps fixed effect variables to observations
К	mat - sparse matrix that defines the known covariance patterns between indi- vidual observations. For example, a kinship matrix will then adjust for the known/estimated genetic relationships between observations.
muvec	vec vector of estimated phenotype means
offsets	vec vector of model offsets
curr_beta	vec vector of initial beta estimates
curr_theta	vec vector of initial parameter estimates
curr_u	vec of initial u estimates
curr_sigma	vec of initial sigma estimates
curr_G	mat c X c matrix of variance components
У	vec of observed counts
u_indices	List a List, each element contains the indices of Z relevant to each RE and all its levels
theta_conv	double Convergence tolerance for paramter estimates
rlevels	List containing mapping of RE variables to individual levels
curr_disp	double Dispersion parameter estimate
REML	bool - use REML for variance component estimation
maxit	int maximum number of iterations if theta_conv is FALSE
solver	string which solver to use - either HE (Haseman-Elston regression) or Fisher scoring
vardist	string which variance form to use NB = negative binomial, P=Poisson [not yet

# Details

Fit a NB-GLMM to the counts provided in *y*. The model uses an iterative approach that switches between the joint fixed and random effect parameter inference, and the variance component estimation. A pseudo-likelihood approach is adopted to minimise the log-likelihood of the model given the parameter estimates. The fixed and random effect parameters are estimated using Hendersons mixed model equations, and the variance component parameters are then estimated with the specified solver, i.e. Fisher scoring, Haseman-Elston or constrained Haseman-Elston regression. As the domain of the variance components is [0, +Inf], any negative variance component estimates will trigger the switch to the HE-NNLS solver until the model converges.

# Value

A list containing the following elements (note: return types are dictated by Rcpp, so the R types are described here):

FE: numeric vector of fixed effect parameter estimates.

- RE: list of the same length as the number of random effect variables. Each slot contains the best linear unbiased predictors (BLUPs) for the levels of the corresponding RE variable.
- Sigma: numeric vector of variance component estimates, 1 per random effect variable. For this model the last variance component corresponds to the input *K* matrix.

converged: logical scalar of whether the model has reached the convergence tolerance or not.

Iters: numeric scalar with the number of iterations that the model ran for. Is strictly <= max.iter.

- Dispersion: numeric scalar of the dispersion estimate computed off-line
- Hessian: matrix of 2nd derivative elements from the fixed and random effect parameter inference.
- SE: matrix of standard error estimates, derived from the hessian, i.e. the square roots of the diagonal elements.
- t: numeric vector containing the compute t-score for each fixed effect variable.
- COEFF: matrix containing the coefficient matrix from the mixed model equations.
- P: matrix containing the elements of the REML projection matrix.
- Vpartial: list containing the partial derivatives of the (pseudo)variance matrix with respect to each variance component.
- Ginv: matrix of the inverse variance components broadcast to the full Z matrix.
- Vsinv: matrix of the inverse pseudovariance.
- Winv: matrix of the inverse elements of  $W = D^{-1} V D^{-1}$
- VCOV: matrix of the variance-covariance for all model fixed and random effect variable parameter estimates. This is required to compute the degrees of freedom for the fixed effect parameter inference.
- CONVLIST: list of list containing the parameter estimates and differences between current and previous iteration estimates at each model iteration. These are included for each fixed effect, random effect and variance component parameter. The list elements for each iteration are: *ThetaDiff, SigmaDiff, beta, u, sigma*.

# Author(s)

Mike Morgan

#### Examples

NULL

fitGLMM	Perform differential abundance testing using a NB-generalised linear
	mixed model

### Description

This function will perform DA testing per-nhood using a negative binomial generalised linear mixed model

# Usage

```
fitGLMM(
 Χ,
 Ζ,
 у,
 offsets,
 init.theta = NULL,
 Kin = NULL,
 random.levels = NULL,
 REML = FALSE,
 glmm.control = list(theta.tol = 1e-06, max.iter = 100, init.sigma = NULL, init.beta =
   NULL, init.u = NULL, solver = NULL),
 dispersion = 1,
  geno.only = FALSE,
  intercept.type = "fixed",
  solver = NULL
)
```

# Arguments

Х	A matrix containing the fixed effects of the model.
Z	A matrix containing the random effects of the model.
У	A matrix containing the observed phenotype over each neighborhood.
offsets	A vector containing the (log) offsets to apply normalisation for different numbers of cells across samples.
init.theta	A column vector (m X 1 matrix) of initial estimates of fixed and random effect coefficients
Kin	A n x n covariance matrix to explicitly model variation between observations
random.levels	A list describing the random effects of the model, and for each, the different unique levels.
REML	A logical value denoting whether REML (Restricted Maximum Likelihood) should be run. Default is TRUE.
glmm.control	A list containing parameter values specifying the theta tolerance of the model, the maximum number of iterations to be run, initial parameter values for the fixed (init.beta) and random effects (init.u), and glmm solver (see details).
dispersion	A scalar value for the initial dispersion of the negative binomial.
geno.only	A logical value that flags the model to use either just the matrix 'Kin' or the supplied random effects.
intercept.type	A character scalar, either <i>fixed</i> or <i>random</i> that sets the type of the global intercept variable in the model. This only applies to the GLMM case where additional random effects variables are already included. Setting intercept.type="fixed" or intercept.type="random" will require the user to test their model for failures with each. In the case of using a kinship matrix, intercept.type="fixed" is set automatically.

20

### fitGLMM

solver a character value that determines which optimisation algorithm is used for the variance components. Must be either HE (Haseman-Elston regression) or Fisher (Fisher scoring).

# Details

This function runs a negative binomial generalised linear mixed effects model. If mixed effects are detected in testNhoods, this function is run to solve the model. The solver defaults to the *Fisher* optimiser, and in the case of negative variance estimates it will switch to the non-negative least squares (NNLS) Haseman-Elston solver. This behaviour can be pre-set by passing glmm.control\$solver="HE" for Haseman-Elston regression, which is the recommended solver when a covariance matrix is provided, or glmm.control\$solver="HE-NNLS" which is the constrained HE optimisation algorithm.

# Value

A list containing the GLMM output, including inference results. The list elements are as follows:

- FE: numeric vector of fixed effect parameter estimates.
- RE: list of the same length as the number of random effect variables. Each slot contains the best linear unbiased predictors (BLUPs) for the levels of the corresponding RE variable.
- Sigma: numeric vector of variance component estimates, 1 per random effect variable.
- converged: logical scalar of whether the model has reached the convergence tolerance or not.
- Iters: numeric scalar with the number of iterations that the model ran for. Is strictly <= max.iter.
- Dispersion: numeric scalar of the dispersion estimate computed off-line

Hessian: matrix of 2nd derivative elements from the fixed and random effect parameter inference.

- SE: matrix of standard error estimates, derived from the hessian, i.e. the square roots of the diagonal elements.
- t: numeric vector containing the compute t-score for each fixed effect variable.
- COEFF: matrix containing the coefficient matrix from the mixed model equations.
- P: matrix containing the elements of the REML projection matrix.
- Vpartial: list containing the partial derivatives of the (pseudo)variance matrix with respect to each variance component.
- Ginv: matrix of the inverse variance components broadcast to the full Z matrix.
- Vsinv: matrix of the inverse pseudovariance.
- Winv: matrix of the inverse elements of  $W = D^{-1} V D^{-1}$
- VCOV: matrix of the variance-covariance for all model fixed and random effect variable parameter estimates. This is required to compute the degrees of freedom for the fixed effect parameter inference.
- DF: numeric vector of the number of inferred degrees of freedom. For details see Satterthwaite\_df.
- PVALS: numeric vector of the compute p-values from a t-distribution with the inferred number of degrees of freedom.
- ERROR: list containing Rcpp error messages used for internal checking.

# Author(s)

Mike Morgan

### Examples

fitPLG1mm

GLMM parameter estimation using pseudo-likelihood

# Description

Iteratively estimate GLMM fixed and random effect parameters, and variance component parameters using Fisher scoring based on the Pseudo-likelihood approximation to a Normal loglihood.

# Usage

```
fitPLGlmm(
  Ζ,
 Χ,
 muvec,
 offsets,
  curr_beta,
  curr_theta,
  curr_u,
  curr_sigma,
  curr_G,
 у,
  u_indices,
  theta_conv,
  rlevels,
  curr_disp,
 REML,
```

22

```
maxit,
  solver,
  vardist
)
```

# Arguments

Z	mat - sparse matrix that maps random effect variable levels to observations
х	mat - sparse matrix that maps fixed effect variables to observations
muvec	vec vector of estimated phenotype means
offsets	vec vector of model offsets
curr_beta	vec vector of initial beta estimates
curr_theta	vec vector of initial parameter estimates
curr_u	vec of initial u estimates
curr_sigma	vec of initial sigma estimates
curr_G	mat c X c matrix of variance components
У	vec of observed counts
u_indices	List a List, each element contains the indices of Z relevant to each RE and all its levels
theta_conv	double Convergence tolerance for paramter estimates
rlevels	List containing mapping of RE variables to individual levels
curr_disp	double Dispersion parameter estimate
REML	bool - use REML for variance component estimation
maxit	int maximum number of iterations if theta_conv is FALSE
solver	string which solver to use - either HE (Haseman-Elston regression) or Fisher scoring
vardist	string which variance form to use NB = negative binomial, P=Poisson [not yet implemented.]

# Details

Fit a NB-GLMM to the counts provided in y. The model uses an iterative approach that switches between the joint fixed and random effect parameter inference, and the variance component estimation. A pseudo-likelihood approach is adopted to minimise the log-likelihood of the model given the parameter estimates. The fixed and random effect parameters are estimated using Hendersons mixed model equations, and the variance component parameters are then estimated with the specified solver, i.e. Fisher scoring, Haseman-Elston or constrained Haseman-Elston regression. As the domain of the variance components is [0, +Inf], any negative variance component estimates will trigger the switch to the HE-NNLS solver until the model converges.

Value

A list containing the following elements (note: return types are dictated by Rcpp, so the R types are described here):

- FE: numeric vector of fixed effect parameter estimates.
- RE: list of the same length as the number of random effect variables. Each slot contains the best linear unbiased predictors (BLUPs) for the levels of the corresponding RE variable.
- Sigma: numeric vector of variance component estimates, 1 per random effect variable.

converged: logical scalar of whether the model has reached the convergence tolerance or not.

- Iters: numeric scalar with the number of iterations that the model ran for. Is strictly <= max.iter.
- Dispersion: numeric scalar of the dispersion estimate computed off-line
- Hessian: matrix of 2nd derivative elements from the fixed and random effect parameter inference.
- SE: matrix of standard error estimates, derived from the hessian, i.e. the square roots of the diagonal elements.
- t: numeric vector containing the compute t-score for each fixed effect variable.
- COEFF: matrix containing the coefficient matrix from the mixed model equations.
- P: matrix containing the elements of the REML projection matrix.
- Vpartial: list containing the partial derivatives of the (pseudo)variance matrix with respect to each variance component.
- Ginv: matrix of the inverse variance components broadcast to the full Z matrix.
- Vsinv: matrix of the inverse pseudovariance.
- Winv: matrix of the inverse elements of  $W = D^{-1} V D^{-1}$
- VCOV: matrix of the variance-covariance for all model fixed and random effect variable parameter estimates. This is required to compute the degrees of freedom for the fixed effect parameter inference.
- CONVLIST: list of list containing the parameter estimates and differences between current and previous iteration estimates at each model iteration. These are included for each fixed effect, random effect and variance component parameter. The list elements for each iteration are: *ThetaDiff, SigmaDiff, beta, u, sigma*.

#### Author(s)

Mike Morgan

# Examples

NULL

glmmControl.defaults glmm control default values

# Description

This will give the default values for the GLMM solver

#### Usage

```
glmmControl.defaults(...)
```

### Arguments

... see fitGLMM for details

### Details

The default values for the parameter estimation convergence is 1e-6, and the maximum number of iterations is 100. In practise if the solver converges it generally does so fairly quickly on moderately well conditioned problems. The default solver is Fisher scoring, but this will switch (with a warning produced) to the NNLS Haseman-Elston solver if negative variance estimates are found.

#### Value

list containing the default values GLMM solver. This can be saved in the user environment and then passed to testNhoods directly to modify the convergence criteria of the solver that is used.

- theta.tol: numeric scalar that sets the convergence threshold for the parameter inference this is applied globally to fixed and random effect parameters, and to the variance estimates.
- max.iter: numeric scalar that sets the maximum number of iterations that the NB-GLMM will run for.
- solver: character scalar that sets the solver to use. Valid values are *Fisher*, *HE* or *HE-NNLS*. See fitGLMM for details.

# Author(s)

Mike Morgan

```
mmcontrol <- glmmControl.defaults()
mmcontrol
mmcontrol$solver <- "HE-NNLS"
mmcontrol</pre>
```

graphSpatialFDR

#### Description

Borrowing heavily from cydar which corrects for multiple-testing using a weighting scheme based on the volumetric overlap over hyperspheres. In the instance of graph neighbourhoods this weighting scheme can use graph connectivity or incorpate different within-neighbourhood distances for the weighted FDR calculation.

#### Arguments

x.nhoods	A list of vertices and the constituent vertices of their neighbourhood	
graph	The kNN graph used to define the neighbourhoods	
pvalues	A vector of p-values calculated from a GLM or other appropriate statistical test for differential neighbourhood abundance	
k	A numeric integer that determines the kth nearest neighbour distance to use for the weighted FDR. Only applicaple when using weighting="k-distance".	
weighting	A string scalar defining which weighting scheme to use. Choices are: max, k-distance, neighbour-distance or graph-overlap.	
reduced.dimensions		
	(optional) A matrix of cells X reduced dimensions used to calculate the kNN graph. Only necessary if this function is being used outside of testNhoods where the Milo object is not available	
distances	(optional) A matrix of cell-to-cell distances or a list of distance matrices, 1 per neighbourhood. Only necessary if this function is being used outside of testNhoods where the Milo object is not available.	
indices	(optional) A list of neighbourhood index vertices in the same order as the input neighbourhoods. Only used for the k-distance weighting.	

## Details

Each neighbourhood is weighted according to the weighting scheme defined. k-distance uses the distance to the kth nearest neighbour of the index vertex, neighbour-distance uses the average within-neighbourhood Euclidean distance in reduced dimensional space, max uses the largest within-neighbourhood distance from the index vertex, and graph-overlap uses the total number of cells overlapping between neighborhoods (distance-independent measure). The frequency-weighted version of the BH method is then applied to the p-values, as in cydar.

# Value

A vector of adjusted p-values

#### Author(s)

Adapted by Mike Morgan, original function by Aaron Lun

# groupNhoods

# Examples

NULL

groupNhoods

Group neighbourhoods

# Description

This function groups overlapping and concordantly DA neighbourhoods, using the louvain community detection algorithm.

# Usage

```
groupNhoods(
    x,
    da.res,
    da.fdr = 0.1,
    overlap = 1,
    max.lfc.delta = NULL,
    merge.discord = FALSE,
    subset.nhoods = NULL,
    compute.new = FALSE,
    na.function = "na.pass"
)
```

# Arguments

x	A Milo object containing single-cell gene expression and neighbourhoods.
da.res	A data.frame containing DA results, as expected from running testNhoods.
da.fdr	A numeric scalar that determines at what FDR neighbourhoods are declared DA for the purposes of aggregating across concorantly DA neighbourhoods.
overlap	A scalar integer that determines the number of cells that must overlap between adjacent neighbourhoods for merging.
max.lfc.delta	A scalar that determines the absolute difference in log fold change below which neighbourhoods should not be considered adjacent. Default=NULL
merge.discord	A logical scalar that overrides the default behaviour and allows adjacent neighbourhoods to be merged if they have discordant log fold change signs. Using this argument is generally discouraged, but may be useful for constructing an empirical null group of cells, regardless of DA sign.
subset.nhoods	A logical, integer or character vector indicating which neighbourhoods to subset before grouping. All other neighbourhoods will be assigned NA
compute.new	A logical scalar indicating whether to force computing a new neighbourhood adjacency matrix if already present.
na.function	A valid NA action function to apply, should be one of na.fail, na.omit, na.exclude, na.pass (default='na.pass').

# Details

Louvain clustering is applied to the neighbourhood graph. This graph is first modified based on two criteria: 1) neighbourhoods share at least overlap number of cells, and 2) the DA log fold change sign is concordant. This behaviour can be modulated by setting overlap to be more or less stringent. Additionally, a threshold on the log fold-changes can be set, such that max.lfc.delta is required to retain edges between adjacent neighbourhoods. Note: adjacent neighbourhoods will never be merged with opposite signs.

# Value

A data.frame of model results (as da.res input) with a new column storing the assigned group label for each neighbourhood (NhoodGroup column)

#### Author(s)

Emma Dann & Mike Morgan

initialiseG

Construct the initial G matrix

#### Description

This function maps the variance estimates onto the full  $c \ge q$  levels for each random effect. This ensures that the matrices commute in the NB-GLMM solver. This function is included for reference, and should not be used directly

### Usage

initialiseG(cluster\_levels, sigmas, Kin = NULL)

# Arguments

cluster_levels	A list containing the random effect levels for each variable
sigmas	A matrix of c $\boldsymbol{X}$ 1, i.e. a column vector, containing the variance component estimates
Kin	A matrix containing a user-supplied covariance matrix

### Details

Broadcast the variance component estimates to the full c\\*q x c\\*q matrix.

# Value

matrix of the full broadcast variance component estimates.

# Author(s)

Mike Morgan & Alice Kluzer

28

# initializeFullZ

# Examples

initializeFullZ Construct the full Z matrix

### Description

Using a simplified version of the  $n \times c Z$  matrix, with one column per variable, construct the fully broadcast  $n \times (c \times q)$  binary matrix that maps each individual onto the random effect variable levels. It is not intended for this function to be called by the user directly, but it can be useful to debug mappings between random effect levels and input variables.

# Usage

```
initializeFullZ(Z, cluster_levels, stand.cols = FALSE)
```

### Arguments

Z	A n x c matrix containing the numeric or character levels
cluster_levels	A list that maps the column names of Z onto the individual levels
stand.cols	A logical scalar that determines if Z* should be computed which is the row- centered and scaled version of the full Z matrix

#### Details

To make sure that matrices commute it is necessary to construct the full  $n \ge c \le q$  matrix. This is a binary matrix where each level of each random effect occupies a column, and the samples/observations are mapped onto the correct levels based on the input Z.

# Value

matrix Fully broadcast Z matrix with one column per random effect level for all random effect variables in the model.

### Author(s)

Mike Morgan & Alice Kluzer

# Examples

makeNhoods

Define neighbourhoods on a graph (fast)

# Description

This function randomly samples vertices on a graph to define neighbourhoods. These are then refined by either computing the median profile for the neighbourhood in reduced dimensional space and selecting the nearest vertex to this position (refinement\_scheme = "reduced\_dim"), or by computing the vertex with the highest number of triangles within the neighborhood (refinement\_scheme = "graph"). Thus, multiple neighbourhoods may be collapsed down together to prevent oversampling the graph space.

#### Usage

```
makeNhoods(
    x,
    prop = 0.1,
    k = 21,
    d = 30,
    refined = TRUE,
    reduced_dims = "PCA",
    refinement_scheme = "reduced_dim"
)
```

### Arguments

x	A Milo object with a non-empty graph slot. Alternatively an igraph object on which neighbourhoods will be defined.
prop	A double scalar that defines what proportion of graph vertices to randomly sample. Must be $0 < \text{prop} < 1$ .
k	An integer scalar - the same k used to construct the input graph.
d	The number of dimensions to use if the input is a matrix of cells X reduced dimensions.
refined	A logical scalar that determines the sampling behavior, default=TRUE implements a refined sampling scheme, specified by the refinement_scheme argument.

30

### matrix.trace

```
reduced_dims If x is an Milo object, a character indicating the name of the reducedDim slot
in the Milo object to use as (default: 'PCA'). If x is an igraph object, a matrix
of vertices X reduced dimensions with rownames() set to correspond to the
cellIDs.
refinement_scheme
```

A abarrator appler that defin

A character scalar that defines the sampling scheme, either "reduced\_dim" or "graph". Default is "reduced\_dim".

# Details

This function randomly samples graph vertices, then refines them to collapse down the number of neighbourhoods to be tested. The refinement behaviour can be turned off by setting refine=FALSE, however, we do not recommend this as neighbourhoods will contain a lot of redundancy and lead to an unnecessarily larger multiple-testing burden.

### Value

A Milo object containing a list of vertices and the indices of vertices that constitute the neighbourhoods in the nhoods slot. If the input is a igraph object then the output is a matrix containing a list of vertices and the indices of vertices that constitute the neighbourhoods.

#### Author(s)

Emma Dann, Mike Morgan

#### Examples

```
require(igraph)
m <- matrix(rnorm(100000), ncol=100)
milo <- buildGraph(m, d=10)
milo <- makeNhoods(milo, prop=0.1)
milo</pre>
```

matrix.trace Compute the trace of a matrix

### Description

Exactly what it says on the tin - compute the sum of the matrix diagonal

#### Usage

matrix.trace(x)

#### Arguments

х

A matrix

# Details

It computes the matrix trace of a square matrix.

# Value

numeric scalar of the matrix trace.

### Author(s)

Mike Morgan

# Examples

matrix.trace(matrix(runif(9), ncol=3, nrow=3))

Milo-class

#### The Milo constructor

# Description

The Milo class extends the SingleCellExperiment class and is designed to work with neighbourhoods of cells. Therefore, it inherits from the SingleCellExperiment class and follows the same usage conventions. There is additional support for cell-to-cell distances via distance, and the KNNgraph used to define the neighbourhoods.

# Usage

```
Milo(
    ...,
    graph = list(),
    nhoodDistances = Matrix(0L, sparse = TRUE),
    nhoods = Matrix(0L, sparse = TRUE),
    nhoodCounts = Matrix(0L, sparse = TRUE),
    nhoodIndex = list(),
    nhoodExpression = Matrix(0L, sparse = TRUE),
    .k = NULL
)
```

# Arguments

	Arguments passed to the Milo constructor to fill the slots of the base class. This should be either a SingleCellExperiment or matrix of features X cells
graph	An igraph object or list of adjacent vertices that represents the KNN-graph
nhoodDistances	A list containing sparse matrices of cell-to-cell distances for cells in the same neighbourhoods, one list entry per neighbourhood.

# Milo-class

nhoods	A list of graph vertices, each containing the indices of the constiuent graph vertices in the respective neighbourhood	
nhoodCounts	A matrix of neighbourhood X sample counts of the number of cells in each neighbourhood derived from the respective samples	
nhoodIndex	A list of cells that are the neighborhood index cells.	
nhoodExpression		
	A matrix of gene X neighbourhood expression.	
.k	An integer value. The same value used to build the k-NN graph if already computed.	

# Details

In this class the underlying structure is the gene/feature X cell expression data. The additional slots provide a link between these single cells and the neighbourhood representation. This can be further extended by the use of an abstracted graph for visualisation that preserves the structure of the single-cell KNN-graph

A Milo object can also be constructed by inputting a feature X cell gene expression matrix. In this case it simply constructs a SingleCellExperiment and fills the relevant slots, such as reducedDims.

# Value

a Milo object

# Author(s)

Mike Morgan

Milo-methods

#### Description

Get and set methods for Milo object slots. Generally speaking these methods are used internally, but they allow the user to assign their own externally computed values - should be used *with caution*.

### Value

See individual methods for return values

#### Getters

In the following descriptions x is always a Milo object.

- graph(x): Returns an igraph object representation of the KNN-graph, with number of vertices equal to the number of single-cells.
- nhoodDistances(x): Returns a list of sparse matrix of cell-to-cell distances between nearest neighbours, one list entry per neighbourhood. Largely used internally for computing the k-distance weighting in graphSpatialFDR.
- nhoodCounts(x): Returns a NxM sparse matrix of cell counts in each of N neighbourhoods with respect to the M experimental samples defined.
- nhoodExpression(x): Returns a GxN matrix of gene expression values.
- nhoodIndex(x): Returns a list of the single-cells that are the neighbourhood indices.
- nhoodReducedDim(x): Returns an NxP matrix of reduced dimension positions. Either generated by projectNhoodExpression(x) or by providing an NxP matrix (see setter method below).
- nhoods(x): Returns a sparse matrix of CxN mapping of C single-cells toN neighbourhoods.
- nhoodGraph(x): Returns an igraph object representation of the graph of neighbourhoods, with number of vertices equal to the number of neighbourhoods.
- nhoodAdjacency(x): Returns a matrix of N by N neighbourhoods with entries of 1 where neighbourhods share cells, and 0 elsewhere.

#### Setters

In the following descriptions x is always a Milo object.

- graph(x) <- value: Populates the graph slot with value this should be a valid graph representation in either igraph or list format.
- nhoodDistances(x) <- value: Replaces the internally comptued neighbourhood distances. This is normally computed internally during graph building, but can be defined externally. Must be a list with one entry per neighbourhood containing the cell-to-cell distances for the cells within that neighbourhood.</p>
- nhoodCounts(x) <- value: Replaces the neighbourhood counts matrix. This is normally computed and assigned by countCells, however, it can also be user-defined.

- nhoodExpression(x) <- value: Replaces the nhoodExpression slot. This is calculated internally by calcNhoodExpression, which calculates the mean expression. An alternative summary function can be used to assign an alternative in this way.
- nhoodIndex(x) <- value: Replaces the list of neighbourhood indices. This is provided purely for completeness, and is usually only set internally in makeNhoods.
- nhoodReducedDim(x) <- value: Replaces the reduced dimensional representation or projection of neighbourhoods. This can be useful for externally computed projections or representations.
- nhoods(x) <- value: Replaces the neighbourhood matrix. Generally use of this function is discouraged, however, it may be useful for users to define their own bespoke neighbourhoods by some means.
- nhoodGraph(x) <- value: Populates the nhoodGraph slot with value this should be a valid graph representation in either igraph or list format.
- nhoodAdjacency(x) <- value: Populates the nhoodAdjacency slot with value this should be a
   N by N matrix with elements denoting which neighbourhoods share cells</pre>

# Miscellaneous

A collection of non-getter and setter methods that operate on Milo objects.

show(x): Prints information to the console regarding the Milo object.

### Author(s)

Mike Morgan

#### Examples

```
example(Milo, echo=FALSE)
show(milo)
```

miloR

miloR

#### Description

Milo performs single-cell differential abundance testing. Cell states are modelled as representative neighbourhoods on a nearest neighbour graph. Hypothesis testing is performed using a negative bionomial generalized linear model.

# Description

This function constructs a beeswarm plot using the ggplot engine to visualise the distribution of log fold changes across neighbourhood annotations.

# Usage

```
plotDAbeeswarm(da.res, group.by = NULL, alpha = 0.1, subset.nhoods = NULL)
```

# Arguments

da.res	a data.frame of DA testing results
group.by	a character scalar determining which column of da.res to use for grouping. This can be a column added to the DA testing results using the 'annotateNhoods' function. If da.res[,group.by] is a character or a numeric, the function will coerce it to a factor (see details) (default: NULL, no grouping)
alpha	significance level for Spatial FDR (default: 0.1)
subset.nhoods	A logical, integer or character vector indicating a subset of nhoods to show in plot (default: NULL, no subsetting)

# Details

The group.by variable will be coerced to a factor. If you want the variables in group.by to be in a given order make sure you set the column to a factor with the levels in the right order before running the function.

### Value

a ggplot object

# Author(s)

Emma Dann

# Examples

NULL

plotNhoodCounts

# Description

Plot the number of cells in a neighbourhood per sample and condition

# Usage

```
plotNhoodCounts(x, subset.nhoods, design.df, condition, n_col = 3)
```

### Arguments

Х	A Milo object with a non-empty nhoodCounts slot.
subset.nhoods	A logical, integer or character vector indicating the rows of nhoodCounts(x) to use for plotting. If you use a logical vector, make sure the length matches $nrow(nhoodCounts(x))$ .
design.df	A data.frame which matches samples to a condition of interest. The row names should correspond to the samples. You can use the same design.df that you already used in the testNhoods function.
condition	String specifying the condition of interest Has to be a column in the design.
n_col	Number of columns in the output ggplot.

# Value

A ggplot-class object

# Author(s)

Nick Hirschmüller

plotNhoodExpressionDA Visualize gene expression in neighbourhoods

# Description

Plots the average gene expression in neighbourhoods, sorted by DA fold-change

Plots the average gene expression in neighbourhood groups

# Usage

```
plotNhoodExpressionDA(
  х,
  da.res,
  features,
  alpha = 0.1,
  subset.nhoods = NULL,
  cluster_features = FALSE,
  assay = "logcounts",
  scale_to_1 = FALSE,
  show_rownames = TRUE,
 highlight_features = NULL
)
plotNhoodExpressionGroups(
  х,
  da.res,
  features.
  alpha = 0.1,
  subset.nhoods = NULL,
  cluster_features = FALSE,
  assay = "logcounts",
  scale_to_1 = FALSE,
```

```
show_rownames = TRUE,
highlight_features = NULL,
grid.space = "free"
)
```

# Arguments

х	A Milo object	
da.res	a data.frame of DA testing results	
features	a character vector of features to plot (they must be in rownames(x))	
alpha	significance level for Spatial FDR (default: 0.1)	
subset.nhoods	A logical, integer or character vector indicating a subset of nhoods to show in plot (default: NULL, no subsetting)	
cluster_feature	s	
	logical indicating whether features should be clustered with hierarchical cluster- ing. If FALSE then the order in features is maintained (default: FALSE)	
assay	A character scalar that describes the assay slot to use for calculating neighbour- hood expression. (default: logcounts) Of note: neighbourhood expression will be computed only if the requested features are not in the nhoodExpression slot of the milo object. If you wish to plot average neighbourhood expression from a different assay, you should run calcNhoodExpression(x) with the desired assay.	
scale_to_1	A logical scalar to re-scale gene expression values between 0 and 1 for visuali- sation.	
show_rownames	A logical scalar whether to plot rownames or not. Generally useful to set this to show_rownames=FALSE when plotting many genes.	
highlight_featu	res	
	A character vector of feature names that should be highlighted on the right side of the heatmap. Generally useful in conjunction to show_rownames=FALSE, if you are interested in only a few features	
grid.space	a character setting the space parameter for facet.grid ('fixed' for equally sized facets, 'free' to adapt the size of facent to number of neighbourhoods in group)	

# Value

```
a ggplot object
```

a ggplot object

# Author(s)

Emma Dann

# Examples

NULL

NULL

plotNhoodGraph Plot graph of neighbourhood

# Description

Visualize graph of neighbourhoods

# Usage

```
plotNhoodGraph(
    x,
    layout = "UMAP",
    colour_by = NA,
    subset.nhoods = NULL,
    size_range = c(0.5, 3),
    node_stroke = 0.3,
    is.da = FALSE,
    highlight.da = FALSE,
    ...
)
```

# Arguments

x	A Milo object
layout	this can be (a) a character indicating the name of the reducedDim slot in the Milo object to use for layout (default: 'UMAP') (b) an igraph layout object
colour_by	this can be a data.frame of milo results or a character corresponding to a column in colData
subset.nhoods	A logical, integer or character vector indicating a subset of nhoods to show in plot (default: NULL, no subsetting). This is necessary if testNhoods was run using subset.nhoods=
size_range	a numeric vector indicating the range of node sizes to use for plotting (to avoid overplotting in the graph)
node_stroke	a numeric indicating the desired thickness of the border around each node
is.da	logical scalar that tells plotNhoodGraph to order nhoods by  LFC  which can help to visually emphasise which nhoods are DA.

40

highlight.da logical or numeric scalar that emphasises the DA nhoods in the layout by adjusting the transparency of the non-DA nhoods. Can only be used if is.da=TRUE, otherwise will give a warning. If highlight.da is a numeric then it explicitly sets the transparency level (must be between 0 and 1). If highlight.da is logical then the transparency is set to 0.1

```
... arguments to pass to ggraph
```

# Value

a ggplot-class object

#### Author(s)

Emma Dann

# Examples

NULL

plotNhoodGraphDA Plot Milo results on graph of neighbourhood

# Description

Visualize log-FC estimated with differential nhood abundance testing on embedding of original single-cell dataset.

### Usage

```
plotNhoodGraphDA(x, milo_res, alpha = 0.05, res_column = "logFC", ...)
```

#### Arguments

Х	A Milo object
milo_res	a data.frame of milo results
alpha	significance level for Spatial FDR (default: 0.05)
res_column	which column of milo_res object to use for color (default: logFC)
	arguments to pass to plotNhoodGraph

# Value

a ggplot object

# Author(s)

Emma Dann

# Examples

NULL

plotNhoodGroups *Plot graph of neighbourhoods coloring by nhoodGroups* 

# Description

Visualize grouping of neighbourhoods obtained with groupNhoods

# Usage

```
plotNhoodGroups(x, milo_res, show_groups = NULL, ...)
```

# Arguments

х	A Milo object
milo_res	a data.frame of milo results containing the nhoodGroup column
show_groups	a character vector indicating which groups to plot all other neighbourhoods will be gray
	arguments to pass to plotNhoodGraph

# Value

a ggplot object

# Author(s)

Emma Dann

# Examples

NULL

plotNhoodMA

# Description

Make an MAplot to visualise the relationship between DA log fold changes and neighbourhood abundance. This is a useful way to diagnose issues with the DA testing, such as large compositional biases and/or issues relating to large imbalances in numbers of cells between condition labels/levels.

#### Usage

plotNhoodMA(da.res, alpha = 0.05, null.mean = 0)

# Arguments

da.res	A data.frame of DA testing results
alpha	A numeric scalar that represents the Spatial FDR threshold for statistical significance.
null.mean	A numeric scalar determining the expected value of the log fold change under the null hypothesis. default=0.

# Details

MA plots provide a useful means to evaluate the distribution of log fold changes after differential abundance testing. In particular, they can be used to diagnose global shifts that occur in the presence of confounding between the number of cells acquired and the experimental variable of interest. The expected null value for the log FC distribution (grey dashed line), along with the mean observed log fold change for non-DA neighbourhoods (purple dashed line) are plotted for reference. The deviation between these two lines can give an indication of biases in the results, such as in the presence of a single strong region of DA leading to an increase in false positive DA neighbourhoods in the opposite direction.

### Value

a ggplot object

#### Author(s)

Mike Morgan

#### Examples

NULL

plotNhoodSizeHist Plot histogram of neighbourhood sizes

# Description

This function plots the histogram of the number of cells belonging to each neighbourhood

# Usage

```
plotNhoodSizeHist(milo, bins = 50)
```

### Arguments

milo	A Milo object with a non-empty nhoods slot.
bins	number of bins for geom_histogram

# Value

A ggplot-class object

# Author(s)

Emma Dann

Satterthwaite\_df Compute degrees of freedom using Satterthwaite method

# Description

This function is not intended to be called by the user, and is included for reference

# Usage

```
Satterthwaite_df(
   coeff.mat,
   mint,
   cint,
   SE,
   curr_sigma,
   curr_beta,
   V_partial,
   V_a,
   G_inv,
   random.levels
)
```

# Arguments

coeff.mat	A matrix class object containing the coefficient matrix from the mixed model equations $eq:approx_a$
mint	A numeric scalar of the number of fixed effect variables in the model
cint	A numeric scalar of the number of random effect variables in the model
SE	A 1 x mint matrix, i.e. column vector, containing the standard errors of the fixed effect parameter estimates
curr_sigma	A 1 x cint matrix, i.e. column vector, of the variance component parameter estimates $% \left( {{{\left( {{{{\bf{n}}_{\rm{c}}}} \right)}_{\rm{col}}}} \right)$
curr_beta	A 1 x mint matrix, i.e. column vector, of the fixed effect parameter estimates
V_partial	A list of the partial derivatives for each fixed and random effect variable in the model
V_a	A c+m x c+m variance-covariance matrix of the fixed and random effect variable parameter estimates
G_inv	A nxc X nxc inverse matrix containing the variance component estimates
random.levels	A list containing the mapping between the random effect variables and each respective set of levels for said variable.

# Details

The Satterthwaite degrees of freedom are computed, which estimates the numbers of degrees of freedom in the NB-GLMM based on ratio of the squared standard errors and the product of the Jacobians of the variance-covariance matrix from the fixed effect variable parameter estimation with full variance-covariance matrix. For more details see Satterthwaite FE, Biometrics Bulletin (1946) Vol 2 No 6, pp110-114.

# Value

matrix containing the inferred number of degrees of freedom for the specific model.

### Author(s)

Mike Morgan & Alice Kluzer

# Examples

NULL

sim\_discrete sim\_discrete

# Description

Simulated discrete groups data

# Usage

data(sim\_discrete)

### Format

A list containing a Milo object in the "mylo" slot, and a data.frame containing experimental metadata in the "meta" slot.

### Details

Data are simulated single-cells in 4 distinct groups of cells. Cells in each group are assigned to 1 of 2 conditions: *A* or *B*. Specifically, the cells in block 1 are highly abundant in the *A* condition, whilst cells in block 4 are most abundant in condition *B*.

# Examples

NULL

### 46

sim\_family

sim\_family

# Description

Simulated counts data from a series of simulated family trees

#### Usage

data(sim\_family)

### Format

A list containing a data.frame in the "DF" slot containing the mean counts and meta-data, and a matrix containing the kinship matrix across all families in the "IBD" slot.

# Details

Data are simulated counts from 30 families and includes X and Z design matrices, as well as a single large kinship matrix. Kinships between family members are dictated by the simulated family, i.e. sibs=0.5, parent-sib=0.5, sib-grandparent=0.25, etc. These kinships, along with 2 other random effects, are used to induce a defined covariance between simulated obserations as such:

Z:= random effect design matrix, n X q G:= matrix of variance components, including kinship matrix

 $LL^T = Chol(ZGZ^T) :=$  the Cholesky decomposition of the random effect contribution to the sample covariance Ysim:= simulated means based on exp(offset + Xbeta + Zb) Y = LYsim := simulated means with defined covariance

# Examples

NULL

sim\_nbglmm sim\_nbglmm

# Description

Simulated counts data from a NB-GLMM for a single trait

# Usage

data(sim\_nbglmm)

A data.frame *sim\_nbglmm* containing the following columns:

- Mean: numeric containing the base mean computed as the linear combination of the simulated fixed and random effect weights multiplied by their respective weight matrices.
- Mean.Count: numeric containing the integer count values randomly sampled from a negative binomail distribution with mean = Mean and dispersion = r
- r: numeric containing the dispersion value used to simulate the integer counts in Mean. Count.

Intercept: numeric of all 1s which can be used to set the intercept term in the X design matrix.

- FE1: numeric a binary fixed effect variable taking on values [0, 1]
- FE2: numeric a continuous fixed effect variables
- RE1: numeric a random effect variable with 10 levels
- RE2: numeric a random effect variable with 7 levels

# Details

Data are simulated counts from 50 samples in a single data frame, from which the X and Z design matrices, can be constructed (see examples). There are 2 random effects and 2 fixed effect variables used to simulate the count trait.

# Examples

data(sim\_nbglmm)
head(sim\_nbglmm)

sim\_trajectory Simulated linear trajectory data

### Description

Data are simulated single-cells along a single linear trajectory. Cells are simulated from 5 groups, and assigned to 1 of 2 conditions; *A* or *B*. Data were generated using in the simulate\_linear\_trajectory function in the dyntoy package.

#### Usage

```
data(sim_trajectory)
```

#### Format

A list containing a Milo object in the "mylo" slot, and a data.frame containing experimental metadata in the "meta" slot.

# testDiffExp

# References

https://github.com/dynverse/dyntoy

### Examples

NULL

testDiffExp

Perform post-hoc differential gene expression analysis

# Description

This function will perform differential gene expression analysis within differentially abundant neighbourhoods, by first aggregating adjacent and concordantly DA neighbourhoods, then comparing cells *within* these aggregated groups for differential gene expression using the input design. For comparing *between* DA neighbourhoods see findNhoodMarkers.

# Usage

```
testDiffExp(
    x,
    da.res,
    design,
    meta.data,
    model.contrasts = NULL,
    assay = "logcounts",
    subset.nhoods = NULL,
    subset.row = NULL,
    gene.offset = TRUE,
    n.coef = NULL,
    na.function = "na.pass"
)
```

### Arguments

x	A Milo object containing single-cell gene expression and neighbourhoods.
da.res	A data.frame containing DA results, as expected from running testNhoods.
design	A formula or model.matrix object describing the experimental design for dif- ferential gene expression testing. The last component of the formula or last column of the model matrix are by default the test variable. This behaviour can be overridden by setting the model.contrasts argument. This should be the same as was used for DA testing.
meta.data	A cell X variable data.frame containing single-cell meta-data to which design refers. The order of rows (cells) must be the same as the Milo object columns.

model.contrasts	
	A string vector that defines the contrasts used to perform DA testing. This should be the same as was used for DA testing.
assay	A character scalar determining which assays slot to extract from the Milo object to use for DGE testing.
subset.nhoods	A logical, integer or character vector indicating which neighbourhoods to subset before aggregation and DGE testing (default: NULL).
subset.row	A logical, integer or character vector indicating the rows of x to use for sumamrizing over cells in neighbourhoods.
gene.offset	A logical scalar the determines whether a per-cell offset is provided in the DGE GLM to adjust for the number of detected genes with expression $> 0$ .
n.coef	A numeric scalar refering to the coefficient to select from the DGE model. This is especially pertinent when passing an ordered variable and only one specific type of effects are to be tested.
na.function	A valid NA action function to apply, should be one of na.fail, na.omit, na.exclude, na.pass.

### Details

Adjacent neighbourhoods are first merged based on two criteria: 1) they share at least overlap number of cells, and 2) the DA log fold change sign is concordant. This behaviour can be modulated by setting overlap to be more or less stringent. Additionally, a threshold on the log fold-changes can be set, such that lfc.threshold is required to merge adjacent neighbourhoods. Note: adjacent neighbourhoods will never be merged with opposite signs unless merge.discord=TRUE.

Within each aggregated group of cells differential gene expression testing is performed using the single-cell log normalized gene expression with a GLM (for details see limma-package), or the single-cell counts using a negative binomial GLM (for details see edgeR-package). When using single-cell data for DGE it is recommended to set gene.offset=TRUE as this behaviour adjusts the model by the number of detected genes in each cell as a proxy for differences in capture efficiency and cellular RNA content.

### Value

A list containing a data.frame of DGE results for each aggregated group of neighbourhoods.

#### Author(s)

Mike Morgan & Emma Dann

```
data(sim_discrete)
```

```
milo <- Milo(sim_discrete$SCE)
milo <- buildGraph(milo, k=20, d=10, transposed=TRUE)
milo <- makeNhoods(milo, k=20, d=10, prop=0.3)
meta.df <- sim_discrete$meta</pre>
```

# testNhoods

```
meta.df$SampID <- paste(meta.df$Condition, meta.df$Replicate, sep="_")
milo <- countCells(milo, meta.data=meta.df, samples="SampID")
test.meta <- data.frame("Condition"=c(rep("A", 3), rep("B", 3)), "Replicate"=rep(c("R1", "R2", "R3"), 2))
test.meta$Sample <- paste(test.meta$Condition, test.meta$Replicate, sep="_")
rownames(test.meta) <- test.meta$Sample
da.res <- testNhoods(milo, design=~Condition, design.df=test.meta[colnames(nhoodCounts(milo)), ])
da.res <- groupNhoods(milo, da.res, da.fdr=0.1)
nhood.dge <- testDiffExp(milo, da.res, design=~Condition, meta.data=meta.df)
nhood.dge</pre>
```

```
testNhoods
```

Perform differential neighbourhood abundance testing

# Description

This will perform differential neighbourhood abundance testing after cell counting.

# Arguments

х	A Milo object with a non-empty nhoodCounts slot.
design	A formula or model.matrix object describing the experimental design for dif- ferential abundance testing. The last component of the formula or last column of the model matrix are by default the test variable. This behaviour can be over- ridden by setting the model.contrasts argument
design.df	A data.frame containing meta-data to which design refers to
kinship	(optional) An n X n matrix containing pair-wise relationships between observations, such as expected relationships or computed from SNPs/SNVs/other genetic variants. Row names and column names should correspond to the column names of nhoods(x) and rownames of design.df.
min.mean	A scalar used to threshold neighbourhoods on the minimum average cell counts across samples.
model.contrasts	5
	A string vector that defines the contrasts used to perform DA testing. For a specific comparison we recommend a single contrast be passed to testNhoods. More details can be found in the vignette milo_contrasts.
fdr.weighting	The spatial FDR weighting scheme to use. Choice from max, neighbour-distance, graph-overlap or k-distance (default). If none is passed no spatial FDR correction is performed and returns a vector of NAs.
robust	If robust=TRUE then this is passed to edgeR and limma which use a robust estimation for the global quasilikelihood dispersion distribution. See edgeR and Phipson et al, 2013 for details.

norm.method	A character scalar, either "logMS", "TMM" or "RLE". The "logMS" method nor- malises the counts across samples using the log columns sums of the count ma- trix as a model offset. "TMM" uses the trimmed mean of M-values normalisation as described in Robinson & Oshlack, 2010, whilst "RLE" uses the relative log expression method by Anders & Huber, 2010, to compute normalisation factors relative to a reference computed from the geometric mean across samples. The latter methods provides a degree of robustness against false positives when there are very large compositional differences between samples.
cell.sizes	A named numeric vector of cell numbers per experimental samples. Names should correspond to the columns of nhoodCounts. This can be used to define the model normalisation factors based on a set of numbers instead of the colSums(nhoodCounts(x)). The example use-case is when performing an analysis of a subset of nhoods while retaining the need to normalisation based on the numbers of cells collected for each experimental sample to avoid compositional biases. Infinite or NA values will give an error.
reduced.dim	A character scalar referring to the reduced dimensional slot used to compute dis- tances for the spatial FDR. This should be the same as used for graph building.
REML	A logical scalar that controls the variance component behaviour to use either restricted maximum likelihood (REML) or maximum likelihood (ML). The former is recommened to account for the bias in the ML variance estimates.
glmm.solver	A character scalar that determines which GLMM solver is applied. Must be one of: Fisher, HE or HE-NNLS. HE or HE-NNLS are recommended when supplying a user-defined covariance matrix.
max.iters	A scalar that determines the maximum number of iterations to run the GLMM solver if it does not reach the convergence tolerance threshold.
max.tol	A scalar that deterimines the GLMM solver convergence tolerance. It is recom- mended to keep this number small to provide some confidence that the parameter estimates are at least in a feasible region and close to a <i>local</i> optimum
subset.nhoods	A character, numeric or logical vector that will subset the analysis to the spe- cific nhoods. If a character vector these should correspond to row names of nhoodCounts. If a logical vector then these should have the same length as nrow of nhoodCounts. If numeric, then these are assumed to correspond to in- dices of nhoodCounts - if the maximal index is greater than nrow(nhoodCounts(x)) an error will be produced.
intercept.type	A character scalar, either <i>fixed</i> or <i>random</i> that sets the type of the global intercept variable in the model. This only applies to the GLMM case where additional random effects variables are already included. Setting intercept.type="fixed" or intercept.type="random" will require the user to test their model for failures with each. In the case of using a kinship matrix, intercept.type="fixed" is set automatically.
fail.on.error	A logical scalar the determines the behaviour of the error reporting. Used for debugging only.
BPPARAM	A BiocParallelParam object specifying the arguments for parallelisation. By default this will evaluate using SerialParam(). See detailson how to use parallelisation in testNhoods.

#### testNhoods

force A logical scalar that overrides the default behaviour to nicely error when N < 50 and using a mixed effect model. This is because model parameter estimation may be unstable with these sample sizes, and hence the fixed effect GLM is recommended instead. If used with the LMM, a warning will be produced.

# Details

This function wraps up several steps of differential abundance testing using the edgeR functions. These could be performed separately for users who want to exercise more contol over their DA testing. By default this function sets the lib.sizes to the colSums(x), and uses the Quasi-Likelihood F-test in glmQLFTest for DA testing. FDR correction is performed separately as the default multiple-testing correction is inappropriate for neighbourhoods with overlapping cells. The GLMM testing cannot be performed using edgeR, however, a separate function fitGLMM can be used to fit a mixed effect model to each nhood (see fitGLMM docs for details).

Parallelisation is currently only enabled for the NB-GLMM and uses the BiocParallel paradigm at the level of R, and OpenMP to allow multi-threading of RCpp code. In general the GLM implementation in glmQLFit is sufficiently fast that it does not require parallelisation. Parallelisation requires the user to pass a BiocParallelParam object with the parallelisation arguments contained therein. This relies on the user specifying how to parallelise - for details see the BiocParallel package.

model.contrasts are used to define specific comparisons for DA testing. Currently, testNhoods will take the last formula variable for comparisons, however, contrasts need this to be the first variable. A future update will harmonise these behaviours for consistency. While it is strictly feasible to compute multiple contrasts at once, the recommendation, for ease of interpretability, is to compute one at a time.

If using the GLMM option, i.e. including a random effect variable in the design formula, then testNhoods will check for the sample size of the analysis. If this is less than 60 it will stop and produce an error. It is *strongly* recommended that the GLMM is not used with relatively small sample sizes, i.e. N<60, and even up to N~100 may have unstable parameter estimates across nhoods. This behaviour can be overriden by setting force=TRUE, but also be aware that parameter estimates may not be accurate. A warning will be produced to alert you to this fact.

### Value

A data.frame of model results, which contain:

- logFC: Numeric, the log fold change between conditions, or for an ordered/continous variable the per-unit change in (normalized) cell counts per unit-change in experimental variable.
- logCPM: Numeric, the log counts per million (CPM), which equates to the average log normalized cell counts across all samples.
- F: Numeric, the F-test statistic from the quali-likelihood F-test implemented in edgeR.
- PValue: Numeric, the unadjusted p-value from the quasi-likelihood F-test.

FDR: Numeric, the Benjamini & Hochberg false discovery weight computed from p.adjust.

- Nhood: Numeric, a unique identifier corresponding to the specific graph neighbourhood.
- SpatialFDR: Numeric, the weighted FDR, computed to adjust for spatial graph overlaps between neighbourhoods. For details see graphSpatialFDR.

#### Author(s)

Mike Morgan

```
library(SingleCellExperiment)
ux.1 <- matrix(rpois(12000, 5), ncol=400)
ux.2 <- matrix(rpois(12000, 4), ncol=400)
ux <- rbind(ux.1, ux.2)</pre>
vx <- log2(ux + 1)</pre>
pca <- prcomp(t(vx))</pre>
sce <- SingleCellExperiment(assays=list(counts=ux, logcounts=vx),</pre>
                               reducedDims=SimpleList(PCA=pca$x))
milo <- Milo(sce)</pre>
milo <- buildGraph(milo, k=20, d=10, transposed=TRUE)</pre>
milo <- makeNhoods(milo, k=20, d=10, prop=0.3)</pre>
milo <- calcNhoodDistance(milo, d=10)</pre>
cond <- rep("A", ncol(milo))</pre>
cond.a <- sample(1:ncol(milo), size=floor(ncol(milo)*0.25))</pre>
cond.b <- setdiff(1:ncol(milo), cond.a)</pre>
cond[cond.b] <- "B"</pre>
meta.df <- data.frame(Condition=cond, Replicate=c(rep("R1", 132), rep("R2", 132), rep("R3", 136)))</pre>
meta.df$SampID <- paste(meta.df$Condition, meta.df$Replicate, sep="_")</pre>
milo <- countCells(milo, meta.data=meta.df, samples="SampID")</pre>
test.meta <- data.frame("Condition"=c(rep("A", 3), rep("B", 3)), "Replicate"=rep(c("R1", "R2", "R3"), 2))</pre>
test.meta$Sample <- paste(test.meta$Condition, test.meta$Replicate, sep="_")</pre>
rownames(test.meta) <- test.meta$Sample</pre>
da.res <- testNhoods(milo, design=~Condition, design.df=test.meta[colnames(nhoodCounts(milo)), ], norm.method="T
da.res
```

# Index

\* datasets sim\_discrete, 46 sim\_family, 47 sim\_nbglmm, 47 sim\_trajectory, 48

annotateNhoods, 3

BiocParallelParam, *52*, *53* buildFromAdjacency, 4 buildGraph, 5 buildKNNGraph, *6* buildNhoodGraph, 7

calcNhoodDistance, 8
calcNhoodExpression, 9
checkSeparation, 10
computePvalue, 11
countCells, 12

data.frame, 15

findNhoodGroupMarkers, 13
findNhoodMarkers, 15, 49
fitGeneticPLGlmm, 17
fitGLMM, 19, 25
fitPLGlmm, 22

glmmControl.defaults, 25 graph(Milo-methods), 34 graph,Milo-method(Milo-methods), 34 graph<-(Milo-methods), 34 graph<-,Milo-method(Milo-methods), 34 graphSpatialFDR, 26, 53 groupNhoods, 27

initialiseG, 28
initializeFullZ, 29

makeNhoods, 30
matrix.trace, 31

Milo, 4–10, 12–15, 26, 27, 30, 31, 34, 35, 37, 39–42, 44, 46, 48–51 Milo (Milo-class), 32 Milo-class, 32 Milo-methods, 34 miloR, 35 miloR-package, 3

nhoodAdjacency (Milo-methods), 34 nhoodAdjacency,Milo-method (Milo-methods), 34 nhoodAdjacency<- (Milo-methods), 34 nhoodAdjacency<-,Milo-method</pre> (Milo-methods), 34 nhoodCounts (Milo-methods), 34 nhoodCounts,Milo-method (Milo-methods), 34 nhoodCounts<- (Milo-methods), 34</pre> nhoodCounts<-,Milo-method</pre> (Milo-methods), 34 nhoodDistances (Milo-methods), 34 nhoodDistances,Milo-method (Milo-methods), 34 nhoodDistances<- (Milo-methods), 34</pre> nhoodDistances<-,Milo-method</pre> (Milo-methods), 34 nhoodExpression (Milo-methods), 34 nhoodExpression,Milo-method (Milo-methods), 34 nhoodExpression<- (Milo-methods), 34</pre> nhoodExpression<-,Milo-method</pre> (Milo-methods), 34 nhoodGraph (Milo-methods), 34 nhoodGraph,Milo-method (Milo-methods), 34 nhoodGraph<- (Milo-methods), 34</pre> nhoodGraph<-,Milo-method</pre> (Milo-methods), 34 nhoodIndex (Milo-methods), 34

```
Satterthwaite_df, 21, 45
show (Milo-methods), 34
show, Milo-method (Milo-methods), 34
sim_discrete, 46
sim_family, 47
sim_nbglmm, 47
sim_trajectory, 48
SingleCellExperiment, 6, 32
```

testDiffExp, *13*, *15*, 49 testNhoods, *25*, 51