Package 'scTGIF'

November 13, 2026

Type Package

Title Cell type annotation for unannotated single-cell RNA-Seq data

Version 1.27.0

Depends R (>= 3.6.0)

Imports GSEABase, Biobase, SingleCellExperiment, BiocStyle, plotly, tagcloud, rmarkdown, Rcpp, grDevices, graphics, utils, knitr, S4Vectors, SummarizedExperiment, RColorBrewer, nnTensor, methods, scales, msigdbr, schex, tibble, ggplot2, igraph

Suggests testthat

Description scTGIF connects the cells and the related gene functions without cell type label.

License Artistic-2.0

biocViews DimensionReduction, QualityControl, SingleCell, Software, GeneExpression

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/scTGIF

git_branch devel

git_last_commit 1b32e29

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-11-12

Author Koki Tsuyuzaki [aut, cre]

Maintainer Koki Tsuyuzaki <k.t.the-answer@hotmail.co.jp>

Contents

scTGIF-package 2
calcTGIF 2
cellMarkerToGmt 3
convertRowID 4
DistalLungEpithelium 5
label.DistalLungEpithelium 6
pca.DistalLungEpithelium 6
reportTGIF 7
settingTGIF 8

Index **10**

`scTGIF-package` *Cell type annotation for unannotated single-cell RNA-Seq data*

Description

scTGIF connects the cells and the related gene functions without cell type label.

Details

The DESCRIPTION file: This package was not yet installed at build time.

Index: This package was not yet installed at build time.
`calcTGIF` function calculates what kind of cellular patterns and functional patterns are contained in single-cell RNA-seq data and `reportTGIF` function generates report of analytic result. The algorithm is based on joint NMF, which is implemented in nnTensor package.

Author(s)

Koki Tsuyuzaki [aut, cre]

Maintainer: Koki Tsuyuzaki <k.t.the-answer@hotmail.co.jp>

References

Dominic Grun, Anna Lyubimova, Lennart Kester, Kay Wiebrands, Onur Basak, Nobuo Sasaki, Hans Clevers, Alexander van Oudenaarden (2015) Single-cell messenger RNA sequencing reveals rare intestinal cell types. *Nature*, **525**: 251-255

`calcTGIF` *Function for connecting cellular patterns and functional patterns using jNMF*

Description

`calcTGIF` function calculates what kind of cellular patterns and functional patterns are contained in single-cell RNA-seq data and `reportTGIF` function generates report of analytic result.

Usage

```
calcTGIF(sce, ndim, verbose=FALSE, droplet=TRUE)
```

Arguments

`sce`	A object generated by instantization of SingleCellExperiment-class.
`ndim`	The number of low-dimension of joint NMF algorithm.
`verbose`	The verbose parameter for nnTensor::jNMF (Default: FALSE).
`droplet`	Whether Droplet-based single-cell RNA-Seq or not (Default: TRUE).

Value

The result is saved to metadata slot of SingleCellExperiment object.

Author(s)

Koki Tsuyuzaki [aut, cre]

Examples

```
showMethods("calcTGIF")
```

`cellMarkerToGmt` *A function to convert the CellMarker data to GMT files.*

Description

The GMT (Gene Matrix Transposed file format : *.gmt) file is formatted by the Broad Institute (https://software.broadinstitute.org/cancer/software/gsea/wiki/index.php/Data_formats#GMT:_Gene_Matrix_Transpose
The data can be downloaded from the website of CellMarker (http://biocc.hrbmu.edu.cn/CellMarker).

Usage

```
cellMarkerToGmt(infile, outfile,
  uniq.column=c("tissueType", "cellName"),
  geneid.type=c("geneID", "geneSymbol"))
```

Arguments

`infile`	The input file downloaded from CellMarker website
`outfile`	The output GMT file converted from the CellMarker data
`uniq.column`	The duplicated terms in the specified column are aggrgated as a row of GMT file (Default: geneID)
`geneid.type`	Output gene identifier. (Default: geneID)

Value

`output`	A GMT file is generated.

Author(s)

Koki Tsuyuzaki [aut, cre]

Examples

```
library("GSEABase")

tmp <- tempdir()
infile1 = paste0(tmp, "/Human_cell_markers.txt")
outfile1_1 = paste0(tmp, "/Human_cell_markers_1.gmt")
outfile1_2 = paste0(tmp, "/Human_cell_markers_2.gmt")
outfile1_3 = paste0(tmp, "/Human_cell_markers_3.gmt")
outfile1_4 = paste0(tmp, "/Human_cell_markers_4.gmt")
```

```
sink(infile1)
cat("speciesType\ttissueType\tUberonOntologyID\tcancerType\tcellType\tcellName\tCellOntologyID\tcellMarke
cat("Human\tKidney\tUBERON_0002113\tNormal\tNormal cell\tProximal tubular cell\tNA\tIntestinal Alkaline Pho
cat("Human\tLiver\tUBERON_0002107\tNormal\tNormal cell\tIto cell (hepatic stellate cell)\tCL_0000632\tSynap
cat("Human\tEndometrium\tUBERON_0001295\tNormal\tNormal cell\tTrophoblast cell\tCL_0000351\tCEACAM1\tCEACA
cat("Human\tGerm\tUBERON_0000923\tNormal\tNormal cell\tPrimordial germ cell\tCL_0000670\tVASA\tDDX4\t54514
cat("Human\tCorneal epithelium\tUBERON_0001772\tNormal\tNormal cell\tEpithelial cell\tCL_0000066\tKLF6\tKL
cat("Human\tPlacenta\tUBERON_0001987\tNormal\tNormal cell\tCytotrophoblast\tCL_0000351\tFGF10\tFGF10\t2255
cat("Human\tPeriosteum\tUBERON_0002515\tNormal\tNormal cell\tPeriosteum-derived progenitor cell\tNA\tCD166
cat("Human\tAmniotic membrane\tUBERON_0009742\tNormal\tNormal cell\tAmnion epithelial cell\tCL_0002536\tNAN
cat("Human\tPrimitive streak\tUBERON_0004341\tNormal\tNormal cell\tPrimitive streak cell\tNA\tLHX1, MIXL1\t
sink()

cellMarkerToGmt(infile1, outfile1_1, uniq.column=c("tissueType"),
  geneid.type=c("geneID"))
cellMarkerToGmt(infile1, outfile1_2, uniq.column=c("tissueType"),
  geneid.type=c("geneSymbol"))
cellMarkerToGmt(infile1, outfile1_3, uniq.column=c("cellName"),
  geneid.type=c("geneID"))
cellMarkerToGmt(infile1, outfile1_4, uniq.column=c("cellName"),
  geneid.type=c("geneSymbol"))

gmt1_1 <- getGmt(outfile1_1)
gmt1_2 <- getGmt(outfile1_2)
gmt1_3 <- getGmt(outfile1_3)
gmt1_4 <- getGmt(outfile1_4)
```

`convertRowID` *A function to change the row names of a matrix.*

Description

To avoid to specify the duplicated row names against matrix, multiple aggregation rules are implemented.

Usage

```
convertRowID(input, rowID, LtoR,
    aggr.rule=c("sum", "mean", "large.mean", "large.var", "large.cv2"))
```

Arguments

`input`	A matrix filled with number (n * m).
`rowID`	A vector to specify the row names of input (length: n).
`LtoR`	A corresponding table to covert the row names of input as different type of IDs. (Left: current row names -> Right: new row names)
`aggr.rule`	The aggregation rule to change the row names of input and collapse/select the values, if the row names changed by LtoR are duplicated. sum: Collapses multiple row vectors by summation. mean: Collapses multiple row vectors by mean. large.mean: Select a vector having the largest mean in the duplicated vectors. large.var: Select a vector having the largest variance in the duplicated vectors. large.cv2: Select a vector having the largest CV2 in the duplicated vectors.

Value

output	A matrix, in which the row names are changed, according to the aggregation rule user specified.
ctable	The corresponding table explaining the relationship between previous row names and changed row names of input.

Author(s)

Koki Tsuyuzaki [aut, cre]

Examples

```
input <- matrix(1:20, nrow=4, ncol=5)
rowID <- c("A", "B", "C", "D")
LtoR <- rbind(
  c("A", "3"),
  c("B", "2"),
  c("C", "4"),
  c("D", "7"))
(input2 <- convertRowID(input, rowID, LtoR, "sum"))
(input3 <- convertRowID(input, rowID, LtoR, "mean"))
(input4 <- convertRowID(input, rowID, LtoR, "large.mean"))
(input5 <- convertRowID(input, rowID, LtoR, "large.var"))
(input6 <- convertRowID(input, rowID, LtoR, "large.cv2"))
```

DistalLungEpithelium *Gene expression matrix of DistalLungEpithelium dataset containing five cluster.*

Description

A data frame with 3397 rows (genes) with following 80 columns (cells).

The data is downloaded as supplementary information of the distal lung epithelium paper (https://www.nature.com/article

Low-expressed genes are filted.

All Gene ID is converted to Human Entrez Gene ID for applying the data to scTGIF.

Usage

```
data("DistalLungEpithelium")
```

Source

http://www.nature.com/nbt/journal/v33/n2/full/nbt.3102.html

References

Treutlein, B. et al. (2014) Reconstructing lineage hierarchies of the distal lung epithelium using single-cell RNA-seq. *Nature* **509**, 371-375

Examples

```
data("DistalLungEpithelium")
```

`label.DistalLungEpithelium`
Cellular label of DistalLungEpithelium dataset containing five cluster.

Description

A vector containing 80 elements (cells).

Usage

```
data("label.DistalLungEpithelium")
```

References

Treutlein, B. et al. (2014) Reconstructing lineage hierarchies of the distal lung epithelium using single-cell RNA-seq. *Nature* **509**, 371-375

Examples

```
data("label.DistalLungEpithelium")
```

`pca.DistalLungEpithelium`
The result of PCA of the DistalLungEpithelium dataset.

Description

A matrix having 80 (cells) * 2 (PCs) elements.

Usage

```
data("pca.DistalLungEpithelium")
```

References

Treutlein, B. et al. (2014) Reconstructing lineage hierarchies of the distal lung epithelium using single-cell RNA-seq. *Nature* **509**, 371-375

Examples

```
data("pca.DistalLungEpithelium")
```

reportTGIF *Function for reporting the result of* calcTGIF *function*

Description

calcTGIF function calculates what kind of cellular patterns and functional patterns are contained in single-cell RNA-seq data and reportTGIF function generates report of analytic result.

Usage

```
reportTGIF(sce, out.dir=tempdir(), html.open=FALSE,
    title="The result of scTGIF",
    author="The person who runs this script",
    assayNames="counts")
```

Arguments

sce	A object generated by instantization of SingleCellExperiment-class.
out.dir	Output directory user want to save the report (Default: tempdir()).
html.open	Whether html is opened when reportTGIF is finished (Default: FALSE)
title	Title of report (Default: "The result of scTGIF")
author	The name of user name (Default: "The person who runs this script")
assayNames	The unit of gene expression for using scTGIF (e.g. normcounts, cpm...etc) (Default: "counts").

Value

Some file is generated to output directory user specified.

Author(s)

Koki Tsuyuzaki [aut, cre]

Examples

```
if(interactive()){
    # Package loading
    library("SingleCellExperiment")
    library("GSEABase")
    library("msigdbr")

    # Test data
    data("DistalLungEpithelium")
    data("pca.DistalLungEpithelium")
    data("label.DistalLungEpithelium")

    # Test data
    par(ask=FALSE)
    plot(pca.DistalLungEpithelium, col=label.DistalLungEpithelium, pch=16,
        main="Distal lung epithelium dataset", xlab="PCA1",
        ylab="PCA2", bty="n")
```

```
    text(0.1, 0.05, "AT1", col="#FF7F00", cex=2)
    text(0.07, -0.15, "AT2", col="#E41A1C", cex=2)
    text(0.13, -0.04, "BP", col="#A65628", cex=2)
    text(0.125, -0.15, "Clara", col="#377EB8", cex=2)
    text(0.09, -0.2, "Cilliated", col="#4DAF4A", cex=2)

    # Load the gmt file from MSigDB
    # Only "Entrez Gene ID" can be used in scTGIF
    # e.g. gmt <- GSEABase::getGmt(
    #     "/PATH/YOU/SAVED/THE/GMTFILES/h.all.v6.0.entrez.gmt")
    # Here we use msigdbr to retrieve mouse gene sets

    # Mouse gene set (NCBI Gene ID)
    m_df <- msigdbr(species = "Mus musculus", category = "H")[,
        c("gs_name", "entrez_gene")]

    # Convert to GeneSetCollection
    hallmark = unique(m_df$gs_name)
    gsc <- lapply(hallmark, function(h){
        target = which(m_df$gs_name == h)
        geneIds = unique(as.character(m_df$entrez_gene[target]))
        GeneSet(setName=h, geneIds)
    })
    gmt <- GeneSetCollection(gsc)

    # SingleCellExperiment-class
    sce <- SingleCellExperiment(
        assays = list(counts = DistalLungEpithelium))
    reducedDims(sce) <- SimpleList(PCA=pca.DistalLungEpithelium)

    # User's Original Normalization Function
    CPMED <- function(input){
        libsize <- colSums(input)
        median(libsize) * t(t(input) / libsize)
    }
    # Normalization
    normcounts(sce) <- log10(CPMED(counts(sce)) + 1)

    # Registration of required information into metadata(sce)
    settingTGIF(sce, gmt, reducedDimNames="PCA",
        assayNames="normcounts")

    # Functional Annotation based on jNMF
    calcTGIF(sce, ndim=7)

    # HTML Reprt
    reportTGIF(sce,
        html.open=TRUE,
        title="scTGIF Report for DistalLungEpithelium dataset",
        author="Koki Tsuyuzaki")
}
```

`settingTGIF` *Paramter setting for scTGIF*

Description

All parameters is saved to metadata slot of SingleCellExperiment object.

Usage

```
settingTGIF(sce, gmt, reducedDimNames, assayNames="counts", nbins=40)
```

Arguments

sce	A object generated by instantization of SingleCellExperiment-class.
gmt	Object generated from GSEABase::getGmt function. GMT file can be downloaded from MSigDB web (site http://software.broadinstitute.org/gsea/login.jsp#msigdb). Please confirm that the gmt file contains Human Entrez Gene ID, not gene symbol. Also confirm that the DataMatrix has Human Entrez Gene ID.
reducedDimNames	The names of reducedDim(sce) that user want use in scTGIF.
assayNames	The unit of gene expression for using scTGIF (e.g. normcounts, cpm...etc) (Default: "counts").
nbins	The number of bins of schex (Default: 40).

Value

The result is saved to metadata slot of SingleCellExperiment object.

Author(s)

Koki Tsuyuzaki [aut, cre]

Examples

```
showMethods("settingTGIF")
```

Index

∗ **datasets**
DistalLungEpithelium, 5
label.DistalLungEpithelium, 6
pca.DistalLungEpithelium, 6
∗ **methods**
calcTGIF, 2
cellMarkerToGmt, 3
convertRowID, 4
reportTGIF, 7
settingTGIF, 8
∗ **package**
scTGIF-package, 2

calcTGIF, *2*, 2, *7*
calcTGIF,SingleCellExperiment-method *(*calcTGIF*)*, 2
cellMarkerToGmt, 3
convertRowID, 4

DistalLungEpithelium, 5

label.DistalLungEpithelium, 6

pca.DistalLungEpithelium, 6

reportTGIF, *2*, *7*, 7
reportTGIF,SingleCellExperiment-method *(*reportTGIF*)*, 7

scTGIF *(*scTGIF-package*)*, 2
scTGIF-package, 2
settingTGIF, 8
settingTGIF,SingleCellExperiment-method *(*settingTGIF*)*, 8