Package 'wiggleplotr'

October 30, 2026

Title Make read coverage plots from BigWig files

Version 1.37.0

Description Tools to visualise read coverage from sequencing experiments together with genomic annotations (genes, transcripts, peaks). Introns of long transcripts can be rescaled to a fixed length for better visualisation of exonic read coverage.

Depends R (>= 3.6)

Imports dplyr, ggplot2 (>= 2.2.0), GenomicRanges, rtracklayer, cowplot, assertthat, purrr, S4Vectors, IRanges, GenomeInfoDb

License Apache License 2.0

LazyData true

RoxygenNote 7.2.0

Encoding UTF-8

Suggests knitr, rmarkdown, biomaRt, GenomicFeatures, testthat, ensembldb, EnsDb.Hsapiens.v86, org.Hs.eg.db, TxDb.Hsapiens.UCSC.hg38.knownGene, AnnotationDbi, AnnotationFilter, arrow

VignetteBuilder knitr

biocViews ImmunoOncology, Coverage, RNASeq, ChIPSeq, Sequencing, Visualization, GeneExpression, Transcription, AlternativeSplicing

git_url https://git.bioconductor.org/packages/wiggleplotr

git_branch devel

git_last_commit fc07c23

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-10-29

Author Kaur Alasoo [aut, cre]

Maintainer Kaur Alasoo <kaur.alasoo@gmail.com>

Contents

extractCoverageData . . . 2
getGenotypePalette . . . 4
makeManhattanPlot . . . 4
ncoa7_cdss . . . 5
ncoa7_exons . . . 5
ncoa7_metadata . . . 6
pasteFactors . . . 6
plotCoverage . . . 7
plotCoverageData . . . 9
plotCoverageFromEnsembldb . . . 10
plotCoverageFromUCSC . . . 11
plotTranscripts . . . 12
plotTranscriptsFromEnsembldb . . . 13
plotTranscriptsFromUCSC . . . 14
wiggleplotr . . . 15

Index **16**

`extractCoverageData` *Extract read coverage data from the bigWig files*

Description

Does not work on Windows, because rtracklayer cannot read BigWig files on Windows.

Usage

```
extractCoverageData(
  exons,
  cdss = NULL,
  transcript_annotations = NULL,
  track_data,
  rescale_introns = TRUE,
  new_intron_length = 50,
  flanking_length = c(50, 50),
  plot_fraction = 0.1,
  mean_only = TRUE,
  region_coords = NULL
)
```

Arguments

`exons`	list of GRanges objects, each object containing exons for one transcript. The list must have names that correspond to transcript_id column in transcript_annotations data.frame.
`cdss`	list of GRanges objects, each object containing the coding regions (CDS) of a single transcript. The list must have names that correspond to transcript_id column in trancsript_annotations data.frame. If cdss is not specified then exons list will be used for both arguments. (default: NULL).

`transcript_annotations`
: Data frame with at least three columns: transcript_id, gene_name, strand. Used to construct transcript labels. (default: NULL)

`track_data`
: data.frame with the metadata for the bigWig read coverage files. Must contain the following columns:
  - sample_id - unique id for each sample.
  - track_id - if multiple samples (bigWig files) have the same track_id they will be overlayed on the same plot, track_id is also used as the facet label on the right.
  - bigWig - path to the bigWig file.
  - scaling_factor - normalisation factor for each sample, useful if different samples sequenced to different depth and bigWig files not normalised for that.
  - colour_group - additional column to group samples into, is used as the colour of the coverage track.

`rescale_introns`
: Specifies if the introns should be scaled to fixed length or not. (default: TRUE)

`new_intron_length`
: length (bp) of introns after scaling. (default: 50)

`flanking_length`
: Lengths of the flanking regions upstream and downstream of the gene. (default: c(50,50))

`plot_fraction`
: Size of the random sub-sample of points used to plot coverage (between 0 and 1). Smaller values make plotting significantly faster. (default: 0.1)

`mean_only`
: Plot only mean coverage within each combination of track_id and colour_group values. Useful for example for plotting mean coverage stratified by genotype (which is specified in the colour_group column) (default: TRUE).

`region_coords`
: Start and end coordinates of the region to plot, overrides flanking_length parameter. The 'both' option tends to give better results for wide regions. (default: area).

Value

List containing all of the necessary data for the plotCoverageData function ()

Examples

```
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
    condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
    scaling_factor = 1) %>%
   dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wiggleplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)

selected_transcripts = c("ENST00000438495", "ENST00000392477") #Plot only two transcripts of the gens
## Not run:
extractCoverageData(ncoa7_exons[selected_transcripts], ncoa7_cdss[selected_transcripts], ncoa7_metadata, tra

## End(Not run)
```

getGenotypePalette *Returns a three-colour palette suitable for visualising read coverage stratified by genotype*

Description

Returns a three-colour palette suitable for visualising read coverage stratified by genotype

Usage

```
getGenotypePalette(old = FALSE)
```

Arguments

old	Return old colour palette (now deprecated).

Value

Vector of three colours.

Examples

```
getGenotypePalette()
```

makeManhattanPlot *Make a Manahattan plot of p-values*

Description

The Manhattan plots is compatible with wiggpleplotr read coverage and transcript strucutre plots. Can be appended to those using the cowplot::plot_grid() function.

Usage

```
makeManhattanPlot(
  pvalues_df,
  region_coords,
  color_R2 = FALSE,
  data_track = TRUE
)
```

Arguments

pvalues_df	Data frame of association p-values (required columns: track_id, p_nominal, pos)
region_coords	Start and end coordinates of the region to plot.
color_R2	Color the points according to R2 from the lead variant. Require R2 column in the pvalues_df data frame.
data_track	If TRUE, then remove all information from x-axis. Makes it easy to append to read coverage or transcript strcture plots using cowplot::plot_grid().

Value

gglot2 object

Examples

```
data = dplyr::data_frame(track_id = "GWAS", pos = sample(c(1:1000), 200), p_nominal = runif(200, min = 0.000000
makeManhattanPlot(data, c(1,1000), data_track = FALSE)
```

---

ncoa7_cdss *Coding sequences from 9 protein coding transcripts of NCOA7*

Description

A dataset containing start and end coordinates of coding sequences (CDS) from nine protein coding transcripts of NCOA7.

Usage

```
ncoa7_cdss
```

Format

A GRangesList object with 9 elements:

element CDS start and end coordinates for a single transcript (GRanges object) ...

Source

http://www.ensembl.org/

---

ncoa7_exons *Exons from 9 protein coding transcripts of NCOA7*

Description

A dataset containing start and end coordinates of exons from nine protein coding transcripts of NCOA7.

Usage

```
ncoa7_exons
```

Format

A GRangesList object with 9 elements:

element Exon start and end coordinates for a single transcript (GRanges object) ...

Source

http://www.ensembl.org/

ncoa7_metadata *Gene metadata for NCOA7*

Description

A a list of transcripts for NCOA7.

Usage

```
ncoa7_metadata
```

Format

A data.frame object with 4 columns:

transcript_id Ensembl transcript id.

gene_id Ensembl gene id.

gene_name Human readable gene name.

strand Strand of the transcript (either +1 or -1). ...

Source

http://www.ensembl.org/

pasteFactors *Paste two factors together and preserved their joint order.*

Description

Paste two factors together and preserved their joint order.

Usage

```
pasteFactors(factor1, factor2)
```

Arguments

factor1	First factor
factor2	Second factor

Value

Factors factor1 and factor2 pasted together.

plotCoverage *Plot read coverage across a genomic region*

Description

Also supports rescaling introns to constant length. Extracts read coverage from bigWig files with extractCoverageData and plots it with plotCoverageData. Custom visualisations can be created by modifying the plotCoverageData function. Does not work on Windows, because rtracklayer cannot read BigWig files on Windows.

Usage

```
plotCoverage(
  exons,
  cdss = NULL,
  transcript_annotations = NULL,
  track_data,
  rescale_introns = TRUE,
  new_intron_length = 50,
  flanking_length = c(50, 50),
  plot_fraction = 0.1,
  heights = c(0.75, 0.25),
  alpha = 1,
  fill_palette = c("#a1dab4", "#41b6c4", "#225ea8"),
  mean_only = TRUE,
  connect_exons = TRUE,
  transcript_label = TRUE,
  return_subplots_list = FALSE,
  region_coords = NULL,
  coverage_type = "area",
  show_legend = FALSE
)
```

Arguments

exons	list of GRanges objects, each object containing exons for one transcript. The list must have names that correspond to transcript_id column in transript_annotations data.frame.
cdss	list of GRanges objects, each object containing the coding regions (CDS) of a single transcript. The list must have names that correspond to transcript_id column in transript_annotations data.frame. If cdss is not specified then exons list will be used for both arguments. (default: NULL).
transcript_annotations	Data frame with at least three columns: transcript_id, gene_name, strand. Used to construct transcript labels. (default: NULL)
track_data	data.frame with the metadata for the bigWig read coverage files. Must contain the following columns: • sample_id - unique id for each sample.

- track_id - if multiple samples (bigWig files) have the same track_id they will be overlayed on the same plot, track_id is also used as the facet label on the right.
- bigWig - path to the bigWig file.
- scaling_factor - normalisation factor for each sample, useful if different samples sequenced to different depth and bigWig files not normalised for that.
- colour_group - additional column to group samples into, is used as the colour of the coverage track.

`rescale_introns`
: Specifies if the introns should be scaled to fixed length or not. (default: TRUE)

`new_intron_length`
: length (bp) of introns after scaling. (default: 50)

`flanking_length`
: Lengths of the flanking regions upstream and downstream of the gene. (default: c(50,50))

`plot_fraction` Size of the random sub-sample of points used to plot coverage (between 0 and 1). Smaller values make plotting significantly faster. (default: 0.1)

`heights` Specifies the proportion of the height that is dedicated to coverage plots (first value) relative to transcript annotations (second value). (default: c(0.75,0.25))

`alpha` Transparency (alpha) value for the read coverage tracks. Useful to set to something < 1 when overlaying multiple tracks (see track_id). (default: 1)

`fill_palette` Vector of fill colours used for the coverage tracks. Length must be equal to the number of unique values in track_data$colour_group column.

`mean_only` Plot only mean coverage within each combination of track_id and colour_group values. Useful for example for plotting mean coverage stratified by genotype (which is specified in the colour_group column) (default: TRUE).

`connect_exons` Print lines that connect exons together. Set to FALSE when plotting peaks (default: TRUE).

`transcript_label`
: If TRUE then transcript labels are printed above each transcript. (default: TRUE).

`return_subplots_list`
: Instead of a joint plot return a list of subplots that can be joined together manually.

`region_coords` Start and end coordinates of the region to plot, overrides flanking_length parameter.

`coverage_type` Specifies if the read coverage is represented by either 'line', 'area' or 'both'. The 'both' option tends to give better results for wide regions. (default: area).

`show_legend` display legend for the colour_group next to the read coverage plot (default: FALSE).

Value

Either object from cow_plot::plot_grid() function or a list of subplots (if return_subplots_list == TRUE)

Examples

```
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
    condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
    scaling_factor = 1) %>%
   dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wiggleplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)

selected_transcripts = c("ENST00000438495", "ENST00000392477") #Plot only two transcripts of the gens
## Not run:
plotCoverage(ncoa7_exons[selected_transcripts], ncoa7_cdss[selected_transcripts],
   ncoa7_metadata, track_data,
   heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

plotCoverageData *Plot read coverage across a genomic region*

Description

Does not work on Windows, because rtracklayer cannot read BigWig files on Windows.

Usage

```
plotCoverageData(
  coverage_data_list,
  heights = c(0.75, 0.25),
  alpha = 1,
  fill_palette = c("#a1dab4", "#41b6c4", "#225ea8"),
  connect_exons = TRUE,
  transcript_label = TRUE,
  return_subplots_list = FALSE,
  coverage_type = "area",
  show_legend = FALSE
)
```

Arguments

coverage_data_list

List of required from the extractCoverageData function:

- exons - list of GRanges objects, each object containing exons for one transcript.
- cdss - list of GRanges objects, each object containing the coding regions (CDS) of a single transcript.
- plotting_annotations - Transcript labels for plotting.
- tx_annotations - Transcript coordinates for plotting.
- xlabel - Label of the x-axis.

- coverage_df - Read coverage data frame.
- limits - x-axis limits.

`heights` Specifies the proportion of the height that is dedicated to coverage plots (first value) relative to transcript annotations (second value). (default: c(0.75,0.25))

`alpha` Transparency (alpha) value for the read coverage tracks. Useful to set to something < 1 when overlaying multiple tracks (see track_id). (default: 1)

`fill_palette` Vector of fill colours used for the coverage tracks. Length must be equal to the number of unique values in track_data$colour_group column.

`connect_exons` Print lines that connect exons together. Set to FALSE when plotting peaks (default: TRUE).

`transcript_label`
If TRUE then transcript labels are printed above each transcript. (default: TRUE).

`return_subplots_list`
Instead of a joint plot return a list of subplots that can be joined together manually.

`coverage_type` Specifies if the read coverage is represented by either 'line', 'area' or 'both'. The 'both' option tends to give better results for wide regions. (default: area).

`show_legend` display legend for the colour_group next to the read coverage plot (default: FALSE).

Value

Either object from cow_plot::plot_grid() function or a list of subplots (if return_subplots_list == TRUE)

Examples

```
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
    condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
    scaling_factor = 1) %>%
   dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wiggleplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)

selected_transcripts = c("ENST00000438495", "ENST00000392477") #Plot only two transcripts of the gens
## Not run:
cov_data = extractCoverageData(ncoa7_exons[selected_transcripts], ncoa7_cdss[selected_transcripts], ncoa7_me
plotCoverageData(cov_data, heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

`plotCoverageFromEnsembldb`

Plot read coverage directly from ensembldb object.

Description

A wrapper around the plotCoverage function. See the documentation for (plotCoverage) for more information.

Usage

```
plotCoverageFromEnsembldb(ensembldb, gene_names, transcript_ids = NULL, ...)
```

Arguments

ensembldb	ensembldb object.
gene_names	List of gene names to be plotted.
transcript_ids	Optional list of transcript ids to be plotted.
...	Additional parameters to be passed to plotCoverage.

Value

ggplot2 object

Examples

```
require("EnsDb.Hsapiens.v86")
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
 condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
 scaling_factor = 1) %>%
 dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wiggleplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)
## Not run:
plotCoverageFromEnsembldb(EnsDb.Hsapiens.v86, "NCOA7", transcript_ids = c("ENST00000438495", "ENST0000039247
track_data, heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

plotCoverageFromUCSC *Plot read coverage directly from UCSC OrgDb and TxDb objects.*

Description

A wrapper around the plotCoverage function. See the documentation for (plotCoverage) for more information.

Usage

```
plotCoverageFromUCSC(orgdb, txdb, gene_names, transcript_ids = NULL, ...)
```

Arguments

orgdb	UCSC OrgDb object.
txdb	UCSC TxDb obejct.
gene_names	List of gene names to be plotted.
transcript_ids	Optional list of transcript ids to be plotted.
...	Additional parameters to be passed to plotCoverage.

Value

ggplot2 object

Examples

```
require("dplyr")
require("GenomicRanges")
require("org.Hs.eg.db")
require("TxDb.Hsapiens.UCSC.hg38.knownGene")

orgdb = org.Hs.eg.db
txdb = TxDb.Hsapiens.UCSC.hg38.knownGene

sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
 condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
 scaling_factor = 1) %>%
 dplyr::mutate(bigWig = system.file("extdata",  paste0(sample_id, ".str2.bw"), package = "wiggleplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)
## Not run:
#Note: This example does not work, becasue UCSC and Ensembl use different chromosome names
plotCoverageFromUCSC(orgdb, txdb, "NCOA7", transcript_ids = c("ENST00000438495.6", "ENST00000368357.7"),
track_data, heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

plotTranscripts *Quickly plot transcript structure without read coverage tracks*

Description

Quickly plot transcript structure without read coverage tracks

Usage

```
plotTranscripts(
  exons,
  cdss = NULL,
  transcript_annotations = NULL,
  rescale_introns = TRUE,
  new_intron_length = 50,
  flanking_length = c(50, 50),
  connect_exons = TRUE,
```

```
  transcript_label = TRUE,
  region_coords = NULL
)
```

Arguments

exons	list of GRanges objects, each object containing exons for one transcript. The list must have names that correspond to transcript_id column in transript_annotations data.frame.
cdss	list of GRanges objects, each object containing the coding regions (CDS) of a single transcript. The list must have names that correspond to transcript_id column in transript_annotations data.frame. If cdss is not specified then exons list will be used for both arguments. (default: NULL)
transcript_annotations	Data frame with at least three columns: transcript_id, gene_name, strand. Used to construct transcript labels. (default: NULL)
rescale_introns	Specifies if the introns should be scaled to fixed length or not. (default: TRUE)
new_intron_length	length (bp) of introns after scaling. (default: 50)
flanking_length	Lengths of the flanking regions upstream and downstream of the gene. (default: c(50,50))
connect_exons	Print lines that connect exons together. Set to FALSE when plotting peaks (default: TRUE).
transcript_label	If TRUE then transcript labels are printed above each transcript. (default: TRUE).
region_coords	Start and end coordinates of the region to plot, overrides flanking_length parameter.

Value

ggplot2 object

Examples

```
plotTranscripts(ncoa7_exons, ncoa7_cdss, ncoa7_metadata, rescale_introns = FALSE)
```

---

plotTranscriptsFromEnsembldb

Plot transcripts directly from ensembldb object.

Description

A wrapper around the plotTranscripts function. See the documentation for (plotTranscripts) for more information.

Usage

```
plotTranscriptsFromEnsembldb(ensembldb, gene_names, transcript_ids = NULL, ...)
```

Arguments

ensembldb	ensembldb object.
gene_names	List of gene names to be plotted.
transcript_ids	Optional list of transcript ids to be plotted.
...	Additional parameters to be passed to plotTranscripts

Value

ggplot2 object

Examples

```
require("EnsDb.Hsapiens.v86")
plotTranscriptsFromEnsembldb(EnsDb.Hsapiens.v86, "NCOA7", transcript_ids = c("ENST00000438495", "ENST0000039
```

---

plotTranscriptsFromUCSC

Plot transcripts directly from UCSC OrgDb and TxDb objects.

Description

A wrapper around the plotTranscripts function. See the documentation for (plotTranscripts) for more information. Note that this function is much slower than (plotTranscripts) or (plotTranscriptsFromEnsembldb functions, because indivudally extracting exon coordinates from txdb objects is quite inefficient.

Usage

```
plotTranscriptsFromUCSC(orgdb, txdb, gene_names, transcript_ids = NULL, ...)
```

Arguments

orgdb	UCSC OrgDb object.
txdb	UCSC TxDb obejct.
gene_names	List of gene genaes to be plot.
transcript_ids	Optional list of transcript ids to be plot. (default = NULL)
...	Additional parameters to be passed to plotTranscripts

Value

Transcript plot.

Examples

```
#Load OrgDb and TxDb objects with UCSC gene annotations
require("org.Hs.eg.db")
require("TxDb.Hsapiens.UCSC.hg38.knownGene")
orgdb = org.Hs.eg.db
txdb = TxDb.Hsapiens.UCSC.hg38.knownGene

plotTranscriptsFromUCSC(orgdb, txdb, "NCOA7", transcript_ids = c("ENST00000438495.6", "ENST00000368357.7"))
```

wiggleplotr *wiggleplotr*

Description

wiggleplotr package provides tools to visualise transcript annotations (plotTranscripts) and plot sequencing read coverage over annotated transcripts (plotCoverage).

Details

You can also use covenient wrapper functions (plotTranscriptsFromEnsembldb), (plotCoverageFromEnsembldb), (plotTranscriptsFromUCSC) and (plotCoverageFromUCSC).

To learn more about wiggleplotr, start with the vignette: `browseVignettes(package = "wiggleplotr")`

Index

∗ **datasets**
ncoa7_cdss, 5
ncoa7_exons, 5
ncoa7_metadata, 6

extractCoverageData, 2

getGenotypePalette, 4

makeManhattanPlot, 4

ncoa7_cdss, 5
ncoa7_exons, 5
ncoa7_metadata, 6

pasteFactors, 6
plotCoverage, 7, *11*, *15*
plotCoverageData, 9
plotCoverageFromEnsembldb, 10, *15*
plotCoverageFromUCSC, 11, *15*
plotTranscripts, 12, *13–15*
plotTranscriptsFromEnsembldb, 13, *14, 15*
plotTranscriptsFromUCSC, 14, *15*

wiggleplotr, 15