

# Processed human microRNA-overexpression data from GEO, and sequence information from TargetScan, and targetScore from TargetScore

Yue Li

yueli@cs.toronto.edu

October 30, 2025

## 1 MicroRNA perturbation datasets

We collected 84 Gene Expression Omnibus (GEO) series corresponding to 6 platforms, 77 human cells or tissues, and 112 distinct miRNAs. To our knowledge, this is by far the largest miRNA-overexpression data compendium. To automate the data download and processing, we developed a pipeline written in R, making use of the function `getGEO` from *GEOquery* R/Bioconductor package (Davis and Meltzer [2007]). For each dataset, the pipeline downloads the raw or processed data (if available) and calculates (when necessary) the log fold-change (logFC) in treatment (miRNA transfected) vs (mock) control, taking into account the unique properties of each data. Next, we combined all of the logFC data columns into a single  $N \times M$  matrix for all of the  $N = 19177$  RefSeq mRNAs (NM\_\* obtained from UCSC) and  $M = 286$  datasets. Missing data (logFC) for some genes across studies were imputed using `impute.knn` from *impute* R package (Troyanskaya et al. [2001]). For miRNA transfection data having multiple measurements (in different studies), we picked the one whose logFC correlate the most with the validated targets from mirTarBase Hsu et al. [2011] or average them if no validated target available.

```
> library(TargetScoreData)
> transfection_data <- get_miRNA_transfection_data()$transfection_data
> datasummary <-
+ list( `MicroRNA` = table(names(transfection_data)),
+       `GEO Series` = table(sapply(transfection_data, function(df)
+       `Platform` = table(sapply(transfection_data, function(df)
+       `Cell/Tissue` = table(sapply(transfection_data, function(df)
> print(lapply(datasummary, length))

$MicroRNA
[1] 113

$`GEO Series`
```

```
[1] 84
```

```
$Platform
```

```
[1] 6
```

```
$`Cell/Tissue`
```

```
[1] 77
```

## 2 TargetScan context score and PCT

TargetScan context score and PCT for all of the predicted sites (including conserved and nonconserved sites) downloaded from TargetScan website ([http://www.targetscan.org/cgi-bin/targetscan/data\\_download.cgi?db=vert\\_61](http://www.targetscan.org/cgi-bin/targetscan/data_download.cgi?db=vert_61))

```
> targetScanCS <- get_TargetScanHuman_contextScore()
> targetScanPCT <- get_TargetScanHuman_PCT()
> head(targetScanCS)
```

	Gene Symbol	Transcript ID	miRNA	3prime pairing	local AU	position
1	A1CF	NM_138932	hsa-miR-4711-3p	-0.018	-0.095	-0.100
2	A1CF	NM_138933	hsa-miR-4711-3p	-0.018	-0.095	-0.100
3	A1CF	NM_014576	hsa-miR-4711-3p	-0.018	-0.095	-0.100
4	A1CF	NM_001198820	hsa-miR-4711-3p	-0.018	-0.095	-0.100
5	A1CF	NM_001198819	hsa-miR-4711-3p	-0.018	-0.095	-0.100
6	A1CF	NM_001198818	hsa-miR-4711-3p	-0.018	-0.095	-0.100

  

	TA	SPS	context+	score	context+	score	percentile
1	0.003	0.017		-0.448			99
2	0.003	0.017		-0.448			99
3	0.003	0.017		-0.448			99
4	0.003	0.017		-0.448			99
5	0.003	0.017		-0.448			99
6	0.003	0.017		-0.448			99

```
> dim(targetScanCS)
```

```
[1] 9569357      10
```

```
> head(targetScanPCT)
```

	miR Family	Gene Symbol	Transcript ID	PCT
1	miR-22/22-3p	A1BG	NM_130786	0.00
2	miR-23abc/23b-3p	A1BG	NM_130786	0.00
7	miR-26ab/1297/4465	A1BG	NM_130786	0.00
8	miR-101/101ab	A1BG	NM_130786	0.00
9	miR-103a/107/107ab	A1BG	NM_130786	0.00
10	miR-103a/107/107ab	A1BG	NM_130786	0.09

```
> dim(targetScanPCT)
[1] 2938804      4
```

### 3 TargetScore

Encouraged by the superior performance of TargetScore (manuscript in peer-review), we applied TargetScore to all of the transfection data above. For further exploring miRNA targetome and their associations, we enclose the targetScores results in this package.

```
> targetScoreMatrix <- get_precomputed_targetScores()
> head(names(targetScoreMatrix))

[1] "hsa-miR-34b" "hsa-miR-34c" "hsa-miR-205" "hsa-miR-124" "hsa-miR-1"
[6] "hsa-miR-181a"

> head(targetScoreMatrix[[1]])

      logFC targetScanCS targetScanPCT targetScore
SGIP1  0.077526011      0.00           0  0.03489650
AGBL4  0.020639084      0.00           0  0.03388637
NECAP2 0.078650400      0.00           0  0.03492518
CLIC4   0.016043400     -0.03           0  0.24335149
ADC    -0.002303429      0.00           0  0.03417828
SLC45A1 -0.018655797      0.00           0  0.03457975
```

We can reproduce targetScores using the above data as demonstrated in the following example (require *TargetScore* package). As a convenience function, we applied a wrapper function called `getTargetScores` that does the following: (1) given a miRNA ID, obtain fold-change(s) from `logFC.imputed` matrix or use the user-supplied fold-changes; (2) retrieves TargetScan context score (CS) and PCT (if found); (3) obtain validated targets from the local `mirTarBase` file; (4) compute `targetScore`. We apply `getTargetScores` function using miRNA `hsa-miR-1`, which we know has all three types of data, namely `logFC`, `targetScan` context score, and `PCT`.

```
> library(TargetScore)
> library(gplots)
> myTargetScores <- getTargetScores("hsa-miR-1", tol=1e-3, maxiter=200)
> table((myTargetScores$targetScore > 0.1), myTargetScores$validated) # a v
> # obtain all of targetScore for all of the 112 miRNA
>
> logFC.imputed <- get_precomputed_logFC()
> mirIDs <- unique(colnames(logFC.imputed))
>
> # takes time
>
> # targetScoreMatrix <- mclapply(mirIDs, getTargetScores)
>
> # names(targetScoreMatrix) <- mirIDs
```

## 4 Session Info

```
> sessionInfo()

R Under development (unstable) (2025-10-20 r88955)
Platform: x86_64-pc-linux-gnu
Running under: Ubuntu 24.04.3 LTS

Matrix products: default
BLAS: /home/biocbuild/bbs-3.23-bioc/R/lib/libRblas.so
LAPACK: /usr/lib/x86_64-linux-gnu/lapack/liblapack.so.3.12.0 LAPACK version 3.12.0

locale:
 [1] LC_CTYPE=en_US.UTF-8      LC_NUMERIC=C
 [3] LC_TIME=en_GB            LC_COLLATE=C
 [5] LC_MONETARY=en_US.UTF-8  LC_MESSAGES=en_US.UTF-8
 [7] LC_PAPER=en_US.UTF-8     LC_NAME=C
 [9] LC_ADDRESS=C             LC_TELEPHONE=C
[11] LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C

time zone: America/New_York
tzcode source: system (glibc)

attached base packages:
[1] stats      graphics  grDevices  utils      datasets  methods    base

other attached packages:
[1] TargetScoreData_1.47.0

loaded via a namespace (and not attached):
[1] compiler_4.6.0 tools_4.6.0
```

## References

- Sean Davis and Paul S Meltzer. GEOquery: a bridge between the Gene Expression Omnibus (GEO) and BioConductor. *Bioinformatics (Oxford, England)*, 23(14):1846–1847, July 2007.
- Sheng-Da Hsu, Feng-Mao Lin, Wei-Yun Wu, Chao Liang, Wei-Chih Huang, Wen-Ling Chan, Wen-Ting Tsai, Goun-Zhou Chen, Chia-Jung Lee, Chih-Min Chiu, Chia-Hung Chien, Ming-Chia Wu, Chi-Ying Huang, Ann-Ping Tsou, and Hsien-Da Huang. miRTarBase: a database curates experimentally validated microRNA-target interactions. *Nucleic acids research*, 39 (Database issue):D163–9, January 2011.
- O Troyanskaya, M Cantor, G Sherlock, P Brown, T Hastie, R Tibshirani, D Botstein, and R B Altman. Missing value estimation methods for DNA microarrays. *Bioinformatics (Oxford, England)*, 17(6):520–525, June 2001.