

Package ‘SMTrackR’

August 21, 2026

Type Package

Title SMTrackR: an R/Bioconductor package for mapping protein binding at individual DNA molecules

Version 1.0.0

Date 2024-12-31

Description The package uses exogenous enzyme imprinted information to map protein-DNA binding on individual sequenced DNA molecules. For example, GpC methyltransferase, CpG methyltransferase, and Adenine methyltransferases. Public datasets from such assays are compiled into tracks, and hosted at public servers like Galaxy for their seamless access by this package.

biocViews NucleosomePositioning, Visualization, GeneTarget, GenomeAssembly

Imports jsonlite, GenomicRanges, rtracklayer, stringr, BiocFileCache, S4Vectors

License MIT + file LICENSE

Suggests knitr, rmarkdown, BiocStyle

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.2

Depends R (>= 4.5)

URL <https://www.raolab.in>

BugReports <https://github.com/satyanarayan-rao/SMTrackR>

Contact <mailto:satyanarayan.rao@bt.iitr.ac.in>

git_url <https://git.bioconductor.org/packages/SMTrackR>

git_branch RELEASE_3_23

git_last_commit 9d73803

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-08-20

Author Aashna Bansal [aut, ctb],
 Himani Barmola [aut, ctb],
 Shivam Yadav [aut, ctb],
 Satyanarayan Rao [aut, cre] (ORCID:
<https://orcid.org/0000-0001-7678-3505>)

Maintainer Satyanarayan Rao <satyanarayan.rao@bt.iitr.ac.in>

Contents

generateGvizCodeforSMF	2
listTracks	4
plotFootprints	5
plotFootprintsUsingLocalBigBed	6
plotMethylationCallsNanopore	8
plotMethylationCallsNanoporeUsingLocalBigBed	9

Index	11
--------------	-----------

generateGvizCodeforSMF

Visualize Single Molecule Footprint Patterns with Ideogram and Gene Tracks

Description

Generates Gviz-compatible R code that puts SMF footprints below ideogram and genetracks. This call assumes that you have already ran ‘plotFootprints’ function. Designed for Drosophila melanogaster analysis with expandable parameters for other organisms.

Usage

```
generateGvizCodeforSMF(
  organism = "demlanogaster",
  model = "S2",
  condition = "WT",
  genome_assembly = "dm6",
  type = "dSMF",
  chromosome = "chr2L",
  start = 480290,
  end = 480320,
  tr = "fp_and_mvec",
  label = "peak229",
  span_left = 150,
  span_right = 150,
  remove_dup = FALSE,
  fp_cap = 50,
  gviz_left = 1000,
```

`listTracks`*Discover Available Single Molecule Data Tracks*

Description

Retrieves track metadata from a centralized Google Sheet containing organism-specific single-molecule datasets and experimental conditions.

Usage

```
listTracks()
```

Value

A tibble containing track metadata with columns:

- `organism`: Species identifier (e.g. "dmelanogaster")
- `genome_assembly`: Reference genome version
- `condition`: Experimental condition
- `model`: Biological model/system
- `track_name`: Identifier for 'tr' parameter in 'plotFootprints'
- `data_type`: NOME-seq protocol variant
- `bigbed_url`: Cloud-hosted data location

See Also

'plotFootprints()': Use track names from this list to visualize specific datasets

Examples

```
# List all available tracks from default repository  
listTracks()
```

plotFootprints

*Visualize Single Molecule Footprint Patterns***Description**

Generates footprint plots from NOME-seq data within specified genomic regions. Designed for *Drosophila melanogaster* analysis with expandable parameters for other organisms.

Usage

```
plotFootprints(
  organism = "dmelanogaster",
  model = "S2",
  condition = "WT",
  genome_assembly = "dm6",
  type = "dSMF",
  chromosome = "chr2L",
  start = 480290,
  end = 480320,
  tr = "fp_and_mvec",
  label = "peak229",
  span_left = 150,
  span_right = 150,
  remove_dup = FALSE,
  fp_cap = 50,
  target_dir = ""
)
```

Arguments

organism	Organism code (default: "dmelanogaster")
model	Biological model/system (default: "S2" cells)
condition	Experimental condition (default: "WT")
genome_assembly	Genome version (default: "dm6")
type	Data type ("dSMF" = dual enzyme Single Molecule Footprinting)
chromosome	Chromosome ID (e.g., "chr2L")
start	Genomic start position (numeric/character)
end	Genomic end position (numeric/character)
tr	Track name for BigBed file resource (default: "fp_and_mvec")
label	Plot title annotation
span_left	Upstream window size from region (default: 150)
span_right	Downstream window size from region (default: 150)

<code>remove_dup</code>	Remove duplicate reads? (default: FALSE)
<code>fp_cap</code>	Maximum footprint value for y-axis scaling (default: 50)
<code>target_dir</code>	destination directory where outputs will be stored

Details

This function retrieves and visualizes DNA accessibility patterns from single-molecule data: - Integrates with UCSC-style track hubs via ‘tr’ parameter - Automatically handles coordinate conversion for dm6 genome - Implements dynamic y-axis scaling using ‘fp_cap’

Value

Saves a heatmap in pdf, png, and eps file formats. Also, occupancies are saved in a tsv file

Examples

```
# Basic usage with default parameters
plotFootprints()

# Custom genomic region analysis
plotFootprints(
  chromosome = "chr2L", start = 480290, end = 480320, label = "peak229")
```

`plotFootprintsUsingLocalBigBed`

Visualize Single Molecule Footprint Patterns using Local BigBed file

Description

Generates footprint plots from SMF/dSMF data within specified genomic regions. Designed for *Drosophila melanogaster* analysis with expandable parameters for other organisms.

Usage

```
plotFootprintsUsingLocalBigBed(
  bigBed = "",
  organism = "dmelanogaster",
  model = "S2",
  condition = "WT",
  genome_assembly = "dm3",
  chromosome = "chr2L",
  start = 480290,
  end = 480320,
  label = "peak229",
  span_left = 150,
  span_right = 150,
```

```

    remove_dup = FALSE,
    fp_cap = 50,
    target_dir = ""
)

```

Arguments

bigBed	BigBed file path (e.g., "demo.bb")
organism	Organism code (default: "dmelanogaster")
model	Biological model/system (default: "S2" cells)
condition	Experimental condition (default: "WT")
genome_assembly	Genome version (default: "dm6")
chromosome	Chromosome ID (e.g., "chr2L")
start	Genomic start position (numeric/character)
end	Genomic end position (numeric/character)
label	Plot title annotation
span_left	Upstream window size from region (default: 150)
span_right	Downstream window size from region (default: 150)
remove_dup	Remove duplicate reads? (default: FALSE)
fp_cap	Maximum footprint value for y-axis scaling (default: 50)
target_dir	destination directory where outputs will be stored

Details

This function uses local SMF/dSMF bigBed file and plot heatmap

Value

Saves a heatmap in pdf, png, and eps file formats. Also, occupancies are saved in a tsv file

Examples

```

# Basic usage with default parameters
plotFootprintsUsingLocalBigBed()

# Custom genomic region analysis
plotFootprintsUsingLocalBigBed(
  bigBed = "inst/extdata/demo.bb", organism = "dmelanogaster",
  model = "S2", condition = "WT", genome_assembly = "dm3",
  chromosome = "chr2L", start = 480290, end = 480320, label = "peak229")

```

plotMethylationCallsNanopore

Visualize Single Molecule Footprint Patterns

Description

Generates footprint plots from NOME-seq data within specified genomic regions. Designed for *Drosophila melanogaster* analysis with expandable parameters for other organisms.

Usage

```
plotMethylationCallsNanopore(
  organism = "scerevisiae",
  model = "BY4741 strain",
  condition = "WT",
  genome_assembly = "sacCer3",
  type = "SMF",
  chromosome = "chrIII",
  start = 114300,
  end = 114600,
  tr = "nanopore_meth_calls",
  label = "smac_seq",
  span_left = 1000,
  span_right = 1000,
  stride = 5,
  target_dir = ""
)
```

Arguments

organism	Organism code (default: "scerevisiae")
model	Biological model/system (default: "BY4741 strain")
condition	Experimental condition (default: "WT")
genome_assembly	Genome version (default: "sacCer3")
type	Data type ("Nanopore" = dual enzyme Single Molecule Footprinting)
chromosome	Chromosome ID (e.g., "chrIII")
start	Genomic start position (numeric/character)
end	Genomic end position (numeric/character)
tr	Track name for BigBed file resource (default: "nanopore_meth_calls")
label	Plot title annotation (default: "smac_seq")
span_left	Upstream window size from region (default: 1000)
span_right	Downstream window size from region (default: 1000)
stride	sliding window used for singal aggregation
target_dir	destination directory where outputs will be stored

Details

This function retrieves and visualizes DNA accessibility patterns from single-molecule data: - Integrates with UCSC-style track hubs via 'tr' parameter - Automatically handles coordinate conversion for dm6 genome - Implements dynamic y-axis scaling using 'fp_cap'

Value

Saves a heatmap in pdf, png, and eps file formats. Also, occupancies are saved in a tsv file

Examples

```
# Basic usage with default parameters
plotMethylationCallsNanopore()

# Custom genomic region analysis

plotMethylationCallsNanopore (
  organism = "scerevisiae", model = "BY4741 strain",
  condition = "WT", genome_assembly = "sacCer3",
  type = "SMF", chromosome = "chrIII",
  start = 114300, end = 114600,
  tr = "nanopore_meth_calls", label = "smac_seq",
  span_left = 1000, span_right = 1000, stride = 5, target_dir = "")
```

```
plotMethylationCallsNanoporeUsingLocalBigBed
```

Visualize aggregate methylation calls from ONT sequencing data

Description

Generates heatmap of methylation calls from likes of SMAC-seq datasets. currently has data from Yeast (sacCer3)

Usage

```
plotMethylationCallsNanoporeUsingLocalBigBed(
  bigBed = "",
  chromosome = "chrIII",
  start = 114300,
  end = 114600,
  label = "smac_seq",
  span_left = 1000,
  span_right = 1000,
  remove_dup = FALSE,
  stride = 5,
  target_dir = ""
)
```

Arguments

<code>bigBed</code>	BigBed file path (e.g., "demo.bb")
<code>chromosome</code>	Chromosome ID (e.g., "chr2L")
<code>start</code>	Genomic start position (numeric/character)
<code>end</code>	Genomic end position (numeric/character)
<code>label</code>	Plot title annotation
<code>span_left</code>	Upstream window size from region (default: 150)
<code>span_right</code>	Downstream window size from region (default: 150)
<code>remove_dup</code>	Remove duplicate reads? (default: FALSE)
<code>stride</code>	a window size used for averaging the methylation call values
<code>target_dir</code>	destination directory where outputs will be stored

Details

This function uses local SMF/dSMF bigBed file and plot heatmap

Value

Saves a methylation calls (binary) heatmap in pdf, png, and eps file formats.

Index

`generateGvizCodeforSMF`, [2](#)

`listTracks`, [4](#)

`plotFootprints`, [5](#)

`plotFootprintsUsingLocalBigBed`, [6](#)

`plotMethylationCallsNanopore`, [8](#)

`plotMethylationCallsNanoporeUsingLocalBigBed`,
[9](#)