

# Package ‘VaSP’

February 14, 2025

**Type** Package

**Version** 1.18.0

**Title** Quantification and Visualization of Variations of Splicing in Population

**Description** Discovery of genome-wide variable alternative splicing events from short-read RNA-seq data and visualizations of gene splicing information for publication-quality multi-panel figures in a population. (Warning: The visualizing function is removed due to the dependent package Sushi deprecated. If you want to use it, please change back to an older version.)

**URL** <https://github.com/yuhuihui2011/VaSP>

**BugReports** <https://github.com/yuhuihui2011/VaSP/issues>

**License** GPL (>= 2.0)

**Depends** R (>= 4.0), ballgown

**Imports** IRanges, GenomicRanges, S4Vectors, parallel, matrixStats, GenomicAlignments, GenomeInfoDb, Rsamtools, cluster, stats, graphics, methods

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**biocViews** RNASeq, AlternativeSplicing, DifferentialSplicing, StatisticalMethod, Visualization, Preprocessing, Clustering, DifferentialExpression, KEGG, ImmunoOncology

**Encoding** UTF-8

**LazyData** false

**RoxygenNote** 7.1.1

**git\_url** <https://git.bioconductor.org/packages/VaSP>

**git\_branch** RELEASE\_3\_20

**git\_last\_commit** a50d9a5

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.20

**Date/Publication** 2025-02-13

**Author** Huihui Yu [aut, cre] (<<https://orcid.org/0000-0003-2725-1937>>),  
Qian Du [aut] (<<https://orcid.org/0000-0003-3864-8745>>),  
Chi Zhang [aut] (<<https://orcid.org/0000-0002-1827-8137>>)

**Maintainer** Huihui Yu <yuhuihui2011@foxmail.com>

## Contents

BMfinder . . . . .	2
getDepth . . . . .	3
getGeneinfo . . . . .	3
rice.bg . . . . .	4
spliceGene . . . . .	5
spliceGenome . . . . .	6

<b>Index</b>	<b>8</b>
--------------	----------

---

BMfinder	<i>Discover bimodal distribution features</i>
----------	---

---

### Description

Find bimodal distribution features and divide the samples into 2 groups by k-means clustering.

### Usage

```
BMfinder(x, p.value = 0.01, maf = 0.05, miss = 0.05, fold = 2, log = FALSE,
         cores = detectCores() - 1)
```

### Arguments

x	a numeric matrix with feature rows and sample columns, e.g., splicing score matrix from <a href="#">spliceGenome</a> or <a href="#">spliceGene</a> function.
p.value	p.value threshold for bimodal distribution test
maf	minor allele frequency threshold in k-means clustering
miss	missing grouping rate threshold in k-means clustering
fold	fold change threshold between the two groups
log	whether the scores are to be logarithmic. If TRUE, all the scores are log2 transformed before k-means clustering: $x = \log_2(x+1)$ .
cores	threads to be used. This value is passed to <b>?mclapply</b> in <b>parallel</b> package

### Details

The matrix contains 1, 2 and NA, and values of 'x' in group 2 are larger than group 1.

### Value

a matrix with feature rows and sample columns.

### Examples

```
data(rice.bg)
score<-spliceGene(rice.bg, 'MSTRG.183', junc.type='score')
score<-round(score,2)
as<-BMfinder(score,cores=1) # 4 bimodal distribution features found

##compare
as
score[rownames(score)%in%rownames(as),]
```

---

`getDepth`*Get Read Depth*

---

**Description**

Get read depth from a BAM file (in bedgraph format)

**Usage**

```
getDepth(x, chrom, start, end)
```

**Arguments**

<code>x</code>	path to a BAM file
<code>chrom</code>	chromosome of a region to be searched
<code>start</code>	start position
<code>end</code>	end position

**Value**

a data.frame in bedgraph file format.

**Examples**

```
path <- system.file('extdata', package='VaSP')
bam_files<-list.files(path, 'bam$')
bam_files

depth<-getDepth(file.path(path, bam_files[1]), 'Chr1',
                 start=1171800, end=1179400)
head(depth)

# library(Sushi)
# plotBedgraph(depth, 'Chr1', chromstart=1171800, chromend=1179400, yaxt='s')
# mtext('Depth', side=2, line=2.5, cex=1.2, font=2)
# labelgenome('Chr1', 1171800, 1179400, side=1, scipen=20, n=5, scale='Kb')
```

---

`getGeneinfo`*Get Gene Informaton from a ballgown object*

---

**Description**

Get gene informaton from a ballgown object by genes or by genomic regions

**Usage**

```
getGeneinfo(genes = NA, bg, chrom, start, end, samples = sampleNames(bg),
            trans.select = NA)
```

**Arguments**

genes	a character vector specifying gene IDs in 'bg'. Any values other than NA override genomic region (chrom, start, stop)
bg	ballgown object
chrom	chromosome of a region
start	start position
end	stop position
samples	names of samples. The transcripts in these samples are subjected to 'trans.select'
trans.select	logical expression-like string, indicating transcript rows to select from a matrix of transcript coverages: NA value keeps all transcripts.

**Value**

a data.frame in bed-like file format

**Examples**

```
data(rice.bg)
unique(geneIDs(rice.bg))

gene_id <- c('MSTRG.181', 'MSTRG.182', 'MSTRG.183')
geneinfo <- getGeneinfo(genes=gene_id, rice.bg)
trans <- table(geneinfo$name) # show how many exons each transcript has
trans

# library(Sushi)
# chrom = geneinfo$chrom[1]
# chromstart = min(geneinfo$start) - 1e3
# chromend = max(geneinfo$stop) + 1e3
# color = rep(SushiColors(2)(length(trans)), trans)

# par(mar=c(3,1,1,1))
# plotGenes(geneinfo, chrom, chromstart, chromend, col = color, bheight = 0.2,
#           bentline = FALSE, plotgenetype = 'arrow', labeloffset = 0.5)
# labelgenome(chrom, chromstart, chromend, side = 1, n = 5, scale = 'Kb')
```

---

rice.bg

*Rice ballgown object*

---

**Description**

Small ballgown object created with a subset of rice RNAseq data, for demonstration purposes

**Format**

a ballgown object with 33 transcripts and 6 samples

**Details**

The raw RNA-seq data were screened and trimmed using Trimmomatic (Bolger et al., 2014) and RNA-seq mapping, transcript assembly, and quantification were conducted with HISAT, StringTie, and Ballgown by following the method described by Pertea et al. (Pertea et al., 2016). The rice.bg is a subset ballgown object with 33 transcripts and 6 samples (Yu et al., 2021).

## Source

The raw RNA-seq data were from the project of variation in transcriptional responses to salt stress in rice (SRA Accession: [SRP106054](https://www.ncbi.nlm.nih.gov/sra/SRP106054))

## References

Yu, H., Du, Q., Campbell, M., Yu, B., Walia, H. and Zhang, C. (2021), Genome-wide discovery of natural variation in pre-mRNA splicing and prioritising causal alternative splicing to salt stress response in rice. *New Phytol.* <https://doi.org/10.1111/nph.17189>

Bolger, A.M., Lohse, M., and Usadel, B. (2014). Trimmomatic: a flexible trimmer for Illumina sequence data. *Bioinformatics* 30, 2114-2120.

Pertea, M., Kim, D., Pertea, G.M., Leek, J.T., and Salzberg, S.L. (2016). Transcript-level expression analysis of RNA-seq experiments with HISAT, StringTie and Ballgown. *Nat Protoc* 11, 1650-1667.

## Examples

```
data(rice.bg)
rice.bg
# ballgown instance with 33 transcripts and 6 samples
```

---

spliceGene

*Calculate Splicing Scores for One Gene*

---

## Description

Calculate splicing Scores from ballgown object for a given gene. This function can only calculate one gene. Please use function [spliceGenome](#) to obtain genome-wide splicing scores.

## Usage

```
spliceGene(bg, gene, samples = sampleNames(bg), junc.type = c("score", "count"),
           trans.select = "rowMaxs(x)>=1", junc.select = "rowMaxs(x)>=5")
```

## Arguments

bg	ballgown object
gene	a character string specifying gene id
samples	names of samples
junc.type	type of junction estimate ('score' for junction score; 'count' for junction read count)
trans.select	logical expression-like string, indicating transcript rows to select from a matrix of transcript coverages: NA value keeps all transcripts. e.g. use trans.select='rowMaxs(x)>=1' to filter the transcripts with the maximum coverage among all the samples less than 1.
junc.select	logical expression-like string, indicating junction rows to select from a matrix of junction counts: NA value keeps all junctions. e.g. use junc.select='rowMaxs(x)>=5' to filter the junctions with the maximum read count among all the samples less than 5.

## Details

score = junction count/gene-level per base read coverage. Row functions for matrices are useful to select transcripts and junctions. See [matrixStats](#) package.

## Value

a matrix of junction scores with intron rows and sample columns.

## References

Yu, H., Du, Q., Campbell, M., Yu, B., Walia, H. and Zhang, C. (2021), Genome-wide discovery of natural variation in pre-mRNA splicing and prioritising causal alternative splicing to salt stress response in rice. *New Phytol.* <https://doi.org/10.1111/nph.17189>

## See Also

[spliceGenome](#), which calculates splicing scores in whole genome.

## Examples

```
data(rice.bg)
rice.bg
head(geneIDs(rice.bg))

score<-spliceGene(rice.bg, 'MSTRG.183',junc.type='score')
count<-spliceGene(rice.bg, 'MSTRG.183',junc.type='count')

## compare
tail(score)
tail(count)

## get intron structure
intron<-structure(rice.bg)$intron
intron[intron$id%in%rownames(score)]
```

---

spliceGenome

*Calculate Genome-wide Splicing Scores*

---

## Description

Calculate splicing scores from ballgown objects for all genes.

## Usage

```
spliceGenome(bg, gene.select = "rowQuantiles(x,probs = 0.05)>=1",
             intron.select = "rowQuantiles(x,probs = 0.95)>=5")
```

## Arguments

<code>bg</code>	ballgown object
<code>gene.select</code>	logical expression-like string, indicating genes to select from a matrix of gene-level coverages: NA value keeps all genes. e.g. <code>gene.select = 'rowQuantiles(x,probs = 0.05)&gt;=1'</code> keeps the genes with the read coverage greater than or equal to 1 in at least 95 (0.05 quantile). Used to filter low expressed genes.
<code>intron.select</code>	logical expression-like string, indicating introns to select from a matrix of junction counts: NA value keeps all introns. e.g. <code>intron.select = 'rowQuantiles(x,probs = 0.95)&gt;=5'</code> keeps the introns with the read count greater than or equal to 5 in at least 5 (0.95 quantile). Used to filter introns with very few junction reads supporting.

## Details

`score` = junction count/gene-level per base read coverage. Row functions for matrices in [matrixStats](#) package are useful to select genes and introns.

## Value

a list of two elements: 'score' is matrix of intron splicing scores with intron rows and sample columns and 'intron' is a [GRanges](#) object of intron structure. See [structure](#) in **ballgown** package

## References

Yu, H., Du, Q., Campbell, M., Yu, B., Walia, H. and Zhang, C. (2021), Genome-wide discovery of natural variation in pre-mRNA splicing and prioritising causal alternative splicing to salt stress response in rice. *New Phytol.* <https://doi.org/10.1111/nph.17189>

## See Also

[spliceGene](#), which calculates splicing scores in one gene.

## Examples

```
data(rice.bg)
rice.bg

splice<-spliceGenome(rice.bg,gene.select=NA,intron.select=NA)
names(splice)

head(splice$score)
splice$intron
```

# Index

## \* datasets

rice.bg, 4

BMfinder, 2

getDepth, 3

getGeneinfo, 3

GRanges, 7

matrixStats, 6, 7

rice.bg, 4

spliceGene, 2, 5, 7

spliceGenome, 2, 5, 6, 6

structure, 7