

Package ‘iModMix’

November 3, 2025

Title Integrative Modules for Multi-Omics Data

Version 1.0.0

Description The iModMix network-based method offers an integrated framework for analyzing multi-omics data, including metabolomics, proteomics, and transcriptomics data, enabling the exploration of intricate molecular associations within heterogeneous biological systems.

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.3

biocViews Software, Network, Clustering, Visualization,
Transcriptomics, Proteomics, Metabolomics, GeneExpression,
PrincipalComponent

URL <https://github.com/biodatalab/iModMix>

BugReports <https://github.com/biodatalab/iModMix/issues>

Depends R (>= 4.5.0)

Imports config (>= 0.3.2), golem (>= 0.4.1), shiny (>= 1.7.5),
ComplexHeatmap, DT, RColorBrewer, WGCNA, corrplot, cowplot,
dynamicTreeCut, ggplot2, glassoFast, impute, purrr, stringr,
tidyr, visNetwork, shinyBS, httr, dplyr, stats, iModMixData,
SummarizedExperiment, ExperimentHub (>= 2.99.0)

Suggests testthat (>= 3.0.0), ggfortify, shinyWidgets, pROC, tuneR,
knitr, curl, readxl, reshape2, vroom, here, enrichR, rmarkdown

Config/testthat/edition 3

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/iModMix>

git_branch RELEASE_3_22

git_last_commit f1207f8

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2025-11-02

Author Isis Narvaez-Bandera [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-7320-618X>>)

Maintainer Isis Narvaez-Bandera <isis.narvaez@upr.edu>

Contents

fctAssignmentGenesEnrichr	2
fctClusterAssignments	3
fctEigengenes	4
fctFeaturesAnnotCorrelation	5
fctHierarchicalCluster	6
fctiModMix2SE	7
fctLoadData	8
fctModulesCorrelation	8
fctPartialCors	9
fctPerformClassification	10
run_app	11
Index	13

fctAssignmentGenesEnrichr
fctAssignmentGenesEnrichr

Description

Enrichr terms for genes (Proteins and transcriptomics)

Usage

```
fctAssignmentGenesEnrichr(
  clusterAssignmentsProtGenes,
  database = "GO_Biological_Process_2023"
)
```

Arguments

clusterAssignmentsProtGenes
 (data frame containing cluster_assignments and HMDB/Symbol)

database
 A list with all the available databases from enrichr

Value

result_list data frame containing cluster_assignments and Enrichr terms

Examples

```
if (interactive()) {
  # Simulated cluster assignments with gene symbols
  cluster_assignments <- data.frame(
    feature = c("F1", "F2", "F3", "F4"),
    cluster = c("cluster_1", "cluster_1", "cluster_2", "cluster_2"),
    col = c("#FF0000", "#FF0000", "#00FF00", "#00FF00"),
    feature_name = c("TP53", "BRCA1", "EGFR", "MYC"),
    stringsAsFactors = FALSE
  )
}
```

```

# Run enrichment analysis using Enrichr (requires internet connection)
enriched_results <- fctAssignmentGenesEnrichr(
  clusterAssignmentsProtGenes = cluster_assignments,
  database = "GO_Biological_Process_2023"
)

# View results
head(enriched_results)
}

```

fctClusterAssignments *fctClusterAssignments*

Description

Cluster assignments with annotation.

Usage

```
fctClusterAssignments(cluster, phenoData = NULL, selectedColumns = NULL)
```

Arguments

cluster	A data frame containing cluster assignments.
phenoData	A data frame with the annotation names of the Dataset. Should have a column called Feature_ID.
selectedColumns	Columns selected for the user to merge in the cluster assignments table

Value

A data frame containing cluster assignments and selected columns by user.

Examples

```

# Simulated cluster assignment data
cluster_df <- data.frame(
  feature = paste0("F", 1:5),
  cluster = paste0("cluster_", 1:5),
  col = RColorBrewer::brewer.pal(5, "Set1"),
  stringsAsFactors = FALSE
)

# Simulated annotation data
pheno_df <- data.frame(
  Feature_ID = paste0("F", 1:5),
  Symbol = c("GeneA", "GeneB", "GeneC", "GeneD", "GeneE"),
  Description = paste("Description", 1:5),
  stringsAsFactors = FALSE
)

# Run without selected columns

```

```
fctClusterAssignments(cluster_df, phenoData = pheno_df)

# Run with selected columns
fctClusterAssignments(cluster_df, phenoData = pheno_df, selectedColumns = "Description")
```

fctEigengenes	<i>fctEigengenes</i>
---------------	----------------------

Description

Calculates module eigengenes using the WGCNA package.

Usage

```
fctEigengenes(loadData = loadData, clusterAssignments = clusterAssignments)
```

Arguments

loadData A preprocessed data matrix resulting from "load data" function

clusterAssignments A vector of cluster assignments for each feature.

Value

A list containing:

module_eigenmetab_List_Me The full result from WGCNA::moduleEigengenes.

module_eigenmetab_Me The matrix of module eigengenes.

feature_mat_t The filtered and scaled feature matrix.

Examples

```
# Simulate a small expression matrix
set.seed(123)
mat <- matrix(rnorm(100), nrow = 10, ncol = 10)
colnames(mat) <- paste0("Gene", 1:10)
rownames(mat) <- paste0("Sample", 1:10)

# Simulate cluster assignments
clusters <- rep(1:2, each = 5)

# Run Eigengenes function
result <- fctEigengenes(loadData = mat, clusterAssignments = clusters)

# View eigengene matrix
head(result$module_eigenmetab_Me)
```

```
fctFeaturesAnnotCorrelation  
  fctFeaturesAnnotCorrelation
```

Description

Calculate correlation between the features of top correlated modules.

Usage

```
fctFeaturesAnnotCorrelation(  
  corDataiDataj,  
  clusterAssignmentsD1,  
  clusterAssignmentsD2,  
  loadData1 = loadData1,  
  loadData2 = loadData2,  
  topn = 5  
)
```

Arguments

corDataiDataj	A data frame with the first principal component of each protein cluster and their correlations.
clusterAssignmentsD1	A data frame containing cluster assignments for metabolites.
clusterAssignmentsD2	A data frame containing cluster assignments and Enrichr terms for proteins.
loadData1	A preprocessed data matrix resulting from "load data" function from Data1.
loadData2	A preprocessed data matrix resulting from "load data" function from Data2.
topn	The number of top correlations to select.

Value

A list containing important features and correlation matrices.

Examples

```
# Simulated correlation data  
corDataiDataj <- data.frame(  
  from = c("blue", "green"),  
  to = c("red", "yellow"),  
  value = c(0.9, 0.85),  
  stringsAsFactors = FALSE  
)  
  
# Simulated cluster assignments  
clusterAssignmentsD1 <- data.frame(  
  feature = c("M1", "M2"),  
  col = c("blue", "green"),  
  stringsAsFactors = FALSE  
)
```

```

clusterAssignmentsD2 <- data.frame(
  feature = c("P1", "P2"),
  col = c("red", "yellow"),
  stringsAsFactors = FALSE
)

# Simulated expression matrices
loadData1 <- matrix(rnorm(20), nrow = 5, ncol = 4)
colnames(loadData1) <- c("M1", "M2", "X1", "X2")
rownames(loadData1) <- paste0("Sample", 1:5)

loadData2 <- matrix(rnorm(20), nrow = 5, ncol = 4)
colnames(loadData2) <- c("P1", "P2", "Y1", "Y2")
rownames(loadData2) <- paste0("Sample", 1:5)

# Run the function
result <- fctFeaturesAnnotCorrelation(
  corDataiDataj = corDataiDataj,
  clusterAssignmentsD1 = clusterAssignmentsD1,
  clusterAssignmentsD2 = clusterAssignmentsD2,
  loadData1 = loadData1,
  loadData2 = loadData2,
  topn = 2
)

# View top correlations
result$Top_correlations

```

fctHierarchicalCluster

fctHierarchicalCluster

Description

Perform hierarchical clustering of a partial correlation matrix. By default uses the topological overlap measure (TOM)

Usage

```
fctHierarchicalCluster(parcorMat, tom = TRUE, minModuleSize = 10)
```

Arguments

parcorMat	A partial correlation matrix from <code>glassoFast\$wi</code> : Estimated inverse covariance matrix
tom	TRUE: topological overlap measure; FALSE: partial correlation matrix; default is TRUE.
minModuleSize	Smallest modules to be generated; default is 10

Value

result_list List containing TOM_diss (TOM dissimilarity; NA if argument TOM = FALSE), hclust-Tree (hierarchical clustering object), dynamicMods (index of module membership for features), and mod_count (number of modules).

Examples

```
# Simulate a small partial correlation matrix
set.seed(123)
mat <- matrix(rnorm(100), nrow = 10)
colnames(mat) <- paste0("Gene", 1:10)
rownames(mat) <- paste0("Sample", 1:10)

# Compute covariance and partial correlation matrix
cov_mat <- cov(mat)
parcorMat <- glassoFast::glassoFast(cov_mat, rho = 0.25)$wi
diag(parcorMat) <- NA
colnames(parcorMat) <- rownames(parcorMat) <- paste0("Gene", 1:10)

# Run hierarchical clustering
result <- fctHierarchicalCluster(parcorMat, tom = TRUE, minModuleSize = 3)

# View module assignments
head(result$cluster_assignments)
```

fctiModMix2SE

fctiModMix2SE

Description

Converts expression data and corresponding sample metadata into a Bioconductor-compliant SummarizedExperiment object.

Usage

```
fctiModMix2SE(dataExp, metadata)
```

Arguments

dataExp	A data frame with metabolites (features) in rows and samples in columns. The first column should contain feature IDs (e.g., metabolite names).
metadata	A data frame containing sample metadata. Must include a column named "Sample" that matches the column names of dataExp (excluding the first column).

Value

A SummarizedExperiment object.

Examples

```
dataExp <- data.frame(Feature_ID = paste0("M", 1:5),
                      S1 = rnorm(5), S2 = rnorm(5))
metadata <- data.frame(Sample = c("S1", "S2"),
                      Group = c("A", "B"))
se <- fctiModMix2SE(dataExp, metadata)
se
```

fctLoadData	<i>fctLoadData</i>
-------------	--------------------

Description

A function to load and preprocess the expression data.

Usage

```
fctLoadData(expressionMat = expressionMat)
```

Arguments

expressionMat A feature matrix (e.g., gene expression) with samples in rows and features (e.g., genes) in columns. Row names must be unique.

Value

A preprocessed data matrix.

Examples

```
# Simulated expression matrix with missing values
set.seed(123)
mat <- matrix(rnorm(1000), nrow = 10, ncol = 100)
colnames(mat) <- paste0("Gene", 1:100)
rownames(mat) <- paste0("Sample", 1:10)
mat[sample(length(mat), 50)] <- NA # introduce some NAs

# Add a Feature_ID column to mimic expected input
expressionMat <- cbind(Feature_ID = paste0("F", 1:10), mat)
expressionMat <- as.data.frame(expressionMat)

# Convert Feature_ID to character (if needed)
expressionMat$Feature_ID <- as.character(expressionMat$Feature_ID)

# Run the function
processed_data <- fctLoadData(expressionMat)
```

fctModulesCorrelation	<i>fctModulesCorrelation</i>
-----------------------	------------------------------

Description

Calculates correlations between omic modules.

Usage

```
fctModulesCorrelation(eigengenesList, clusterList, threshold = 0.5)
```

Arguments

`eigengenesList` List with the first principal component of each cluster.
`clusterList` list containing cluster_assignments matrix.
`threshold` A numeric value to filter correlations. Default is 0.5.

Value

Return the Top_correlations between Prot and metab eigengenes, graph of red, correlation plot.

Examples

```
# Simulate eigengene matrices for two omics datasets
set.seed(123)
eig1 <- matrix(rnorm(50), nrow = 10, ncol = 5)
colnames(eig1) <- paste0("ME", 1:5)
eig2 <- matrix(rnorm(50), nrow = 10, ncol = 5)
colnames(eig2) <- paste0("ME", 1:5)

# Simulate cluster assignments for each omic
cluster1 <- data.frame(
  feature = paste0("F", 1:5),
  cluster = paste0("cluster_", 1:5),
  col = RColorBrewer::brewer.pal(5, "Set1"),
  stringsAsFactors = FALSE
)
cluster2 <- data.frame(
  feature = paste0("F", 6:10),
  cluster = paste0("cluster_", 6:10),
  col = RColorBrewer::brewer.pal(5, "Set2"),
  stringsAsFactors = FALSE
)

# Run the correlation function
result <- fctModulesCorrelation(
  eigengenesList = list(eig1, eig2),
  clusterList = list(cluster1, cluster2),
  threshold = 0.5
)

# View top correlations
head(result$Top_cor_Prot_metab)
```

fctPartialCors

fctPartialCors

Description

Calculates partial correlations based on graphical lasso (<https://www.rdocumentation.org/packages/glassoFast/versions/1>)

Usage

```
fctPartialCors(loadData, rho = 0.25)
```

Arguments

loadData	A preprocessed data matrix resulting from "load data" function.
rho	The regularization parameter for lasso. (a non-negative value or a p by p matrix of regularization parameters).

Value

partial_cor_mat A partial correlation matrix with NA's in the diagonal.

Examples

```
# Simulate a small expression matrix
set.seed(123)
mat <- matrix(rnorm(100), nrow = 10, ncol = 10)
colnames(mat) <- paste0("Gene", 1:10)
rownames(mat) <- paste0("Sample", 1:10)

# Run partial correlation
partial_cor_matrix <- fctPartialCors(mat, rho = 0.25)

# View a portion of the result
partial_cor_matrix[1:5, 1:5]
```

fctPerformClassification
fctPerformClassification

Description

Performs classification using different methods such as Welch's T-test, Random Forest, and K-Nearest Neighbors.

Usage

```
fctPerformClassification(
  eigengeneData,
  metadata,
  phenotypeVariable,
  significanceThreshold = 0.05
)
```

Arguments

eigengeneData	A data frame of eigengenes organized with patient IDs in rows and variables in columns.
metadata	A data frame containing metadata, with a column call "Sample" that matches patient IDs in eigengeneData.
phenotypeVariable	The variable selected by the user in the Shiny app (response variable).
significanceThreshold	A numeric value to filter p-value. Default is 00.5.

Value

A data frame with metrics such as AUC, Accuracy, and Error Rate for each binary classification.

Examples

```
# Simulate eigengene data
set.seed(123)
eigengeneData <- as.data.frame(matrix(rnorm(100), nrow = 10, ncol = 10))
colnames(eigengeneData) <- paste0("ME", 1:10)
rownames(eigengeneData) <- paste0("Sample", 1:10)
# Simulate metadata with a binary phenotype
metadata <- data.frame(
  Sample = paste0("Sample", 1:10),
  Phenotype = rep(c("A", "B"), each = 5),
  stringsAsFactors = FALSE
)
# Run classification
result <- fctPerformClassification(
  eigengeneData = eigengeneData,
  metadata = metadata,
  phenotypeVariable = "Phenotype",
  significanceThreshold = 0.05
)

# View results
head(result$result)
```

run_app

*Run the Shiny Application***Description**

Run the Shiny Application

Usage

```
run_app(
  onStart = NULL,
  options = list(),
  enableBookmarking = NULL,
  uiPattern = "/",
  ...
)
```

Arguments

onStart	A function that will be called before the app is actually run. This is only needed for shinyAppObj, since in the shinyAppDir case, a global.R file can be used for this purpose.
---------	--

options	Named options that should be passed to the runApp call (these can be any of the following: "port", "launch.browser", "host", "quiet", "display.mode" and "test.mode"). You can also specify width and height parameters which provide a hint to the embedding environment about the ideal height/width for the app.
enableBookmarking	Can be one of "url", "server", or "disable". The default value, NULL, will respect the setting from any previous calls to enableBookmarking() . See enableBookmarking() for more information on bookmarking your app.
uiPattern	A regular expression that will be applied to each GET request to determine whether the ui should be used to handle the request. Note that the entire request path must match the regular expression in order for the match to be considered successful.
...	arguments to pass to golem_opts. See <code>'?golem::get_golem_options'</code> for more details.

Value

A Shiny application object that launches the iModMix interface.

Index

`enableBookmarking()`, [12](#)

`fctAssignmentGenesEnrichr`, [2](#)

`fctClusterAssignments`, [3](#)

`fctEigengenes`, [4](#)

`fctFeaturesAnnotCorrelation`, [5](#)

`fctHierarchicalCluster`, [6](#)

`fctiModMix2SE`, [7](#)

`fctLoadData`, [8](#)

`fctModulesCorrelation`, [8](#)

`fctPartialCors`, [9](#)

`fctPerformClassification`, [10](#)

`run_app`, [11](#)