Package 'MetaScope'

May 16, 2024

Type Package

Title Tools and functions for preprocessing 16S and metagenomic sequencing microbiome data

Version 1.4.0

Description This package contains tools and methods for preprocessing microbiome data. Functionality includes library generation, demultiplexing, alignment, and microbe identification. It is in part an R translation of the PathoScope 2.0 pipeline.

License GPL (>= 3)

URL https://github.com/wejlab/metascope

https://wejlab.github.io/metascope-docs/

BugReports https://github.com/wejlab/MetaScope/issues

Depends R (>= 4.3.0)

- Imports BiocFileCache, Biostrings, data.table, dplyr, ggplot2, magrittr, Matrix, MultiAssayExperiment, Rbowtie2, readr, rlang, Rsamtools, S4Vectors, stringr, SummarizedExperiment, taxize, tibble, tidyr, tools
- Suggests animalcules, BiocStyle, biomformat, GenomicRanges, IRanges, knitr, lintr, plyr, qlcMatrix, rBLAST, rmarkdown, R.utils, Rsubread, spelling, sys, testthat, usethis

Enhances BiocParallel

VignetteBuilder knitr

Remotes mhahsler/rBLAST

BiocType Software

biocViews MicrobiomeData, ReproducibleResearch, SequencingData

Encoding UTF-8

Language en-US

LazyData FALSE

RoxygenNote 7.2.3

Contents

2

git_url https://git.bioconductor.org/packages/MetaScope

git_branch RELEASE_3_19

git_last_commit 1370e8e

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-16

Author Aubrey Odom [aut, cre] (<https://orcid.org/0000-0001-7113-7598>),
 Rahul Varki [aut],
 W. Evan Johnson [aut] (<https://orcid.org/0000-0002-6247-6595>),
 Howard Fan [ctb]

Maintainer Aubrey Odom <aodom@bu.edu>

Contents

MetaScope-package
align_details
align_target
align_target_bowtie
bam_reheader_R
blast_result_metrics
bt2_16S_params 10
bt2_missing_params 10
bt2_regular_params
check_samtools_exists 12
combined_header
convert_animalcules
convert_animalcules_patho
convert_animalcules_silva 16
count_matches
demultiplex
download_refseq
extract_reads
filter_host
filter_host_bowtie
filter_unmapped_reads
get_children
get_seqs
locations
merge_bam_files
metascope_blast
metascope_id
mk_bowtie_index
mk_subread_index
rBlast_results
rBLAST_single_result
remove_matches

MetaScope-package

taxid_to_name

Index

MetaScope-package MetaScope: Tools and functions for preprocessing 16S and metagenomic sequencing microbiome data

Description

This package contains tools and methods for preprocessing microbiome data. Functionality includes library generation, demultiplexing, alignment, and microbe identification. It is in part an R translation of the PathoScope 2.0 pipeline.

Author(s)

Maintainer: Aubrey Odom <aodom@bu.edu> (ORCID)

Authors:

- Rahul Varki <rvarki@bu.edu>
- W. Evan Johnson <wej@bu.edu>(ORCID)

Other contributors:

• Howard Fan <hjfan@bu.edu> [contributor]

See Also

Useful links:

- https://github.com/wejlab/metascopehttps://wejlab.github.io/metascope-docs/
- Report bugs at https://github.com/wejlab/MetaScope/issues

align_details A universal parameter settings object for Rsubread alignment

Description

This object is a named vector of multiple options that can be chosen for functions that involve alignment with Rsubread, namely align_target() and filter_host(). Both functions take an object for the parameter settings, which are provided by align_details by default, or may be given by a user-created object containing the same information.

Usage

data(align_details)

42

Format

list

Details

The default options included in align_details are type = "dna", maxMismatches = 3, nsubreads = 10, phredOffset = 33, unique = FALSE, and nBestLocations = 16. Full descriptions of these parameters can be read by accessing ?Rsubread::align.

Examples

data("align_details")

align_target

Align microbiome reads to a set of reference libraries

Description

This is the main MetaScope target library mapping function, using Rsubread and multiple libraries. Aligns to each library separately, filters unmapped reads from each file, and then merges and sorts the .bam files from each library into one output file. If desired, output can be passed to 'filter_host()' to remove reads that also map to filter library genomes.

Usage

```
align_target(
  read1,
  read2 = NULL,
  lib_dir = NULL,
  libs,
  threads = 1,
  align_file = tools::file_path_sans_ext(read1),
  subread_options = align_details,
  quiet = TRUE
)
```

Arguments

read1	Path to the .fastq file to align.
read2	Optional: Location of the mate pair .fastq file to align.
lib_dir	Path to the index files for all libraries.
libs	A vector of character strings giving the basenames of the Subread index files for alignment. If ALL indices to be used are located in the current working directory, set lib_dir = NULL. Default is lib_dir = NULL.
threads	The number of threads that can be utilized by the function. Default is 1 thread.

align_target

align_file	The basename of the output alignment file (without trailing .bam extension).
subread_option	S
	A named list specifying alignment parameters for the Rsubread::align() function, which is called inside align_target(). Elements should include type, nthreads, maxMismatches, nsubreads, phredOffset, unique, and nBestLocations. Descriptions of these parameters are available under ?Rsubread::align. Defaults to the global align_details object.
quiet	Turns off most messages. Default is TRUE.

Value

This function writes a merged and sorted .bam file after aligning to all reference libraries given, along with a summary report file, to the user's working directory. The function also outputs the new .bam filename.

Examples

Align example reads to an example reference library using Rsubread

```
## Create temporary directory
target_ref_temp <- tempfile()</pre>
dir.create(target_ref_temp)
## Download genome
tax <- "Ovine atadenovirus D"</pre>
all_ref <- MetaScope::download_refseq(tax,</pre>
                                         reference = FALSE,
                                         representative = FALSE,
                                         compress = TRUE,
                                         out_dir = target_ref_temp,
                                         caching = TRUE)
## Create subread index
ind_out <- mk_subread_index(all_ref)</pre>
## Get path to example reads
readPath <- system.file("extdata", "reads.fastq",</pre>
                         package = "MetaScope")
## Copy the example reads to the temp directory
refPath <- file.path(target_ref_temp, "reads.fastq")</pre>
file.copy(from = readPath, to = refPath)
## Modify alignment parameters object
data("align_details")
align_details[["type"]] <- "rna"</pre>
align_details[["phredOffset"]] <- 50</pre>
# Just to get it to align - toy example!
align_details[["maxMismatches"]] <- 100</pre>
## Run alignment
target_map <- align_target(refPath,</pre>
```

```
libs = stringr::str_replace_all(tax, " ", "_"),
lib_dir = target_ref_temp,
subread_options = align_details)
```

Remove temporary folder unlink(target_ref_temp, recursive = TRUE)

align_target_bowtie Align microbiome reads to set of indexed Bowtie2 libraries

Description

This is the main MetaScope target library mapping function, using Rbowtie2 and multiple libraries. Aligns to each library separately, filters unmapped reads from each file, and then merges and sorts the .bam files from each library into one output file. If desired, output can be passed to 'filter_host_bowtie()' to remove reads that also map to filter library genomes.

Usage

```
align_target_bowtie(
  read1,
  read2 = NULL,
  lib_dir,
  libs,
  align_dir,
  align_file,
  bowtie2_options = NULL,
  threads = 1,
  overwrite = FALSE,
  quiet = TRUE
)
```

Arguments

read1	Path to the .fastq file to align.
read2	Optional: Location of the mate pair .fastq file to align.
lib_dir	Path to the directory that contains the Bowtie2 indexes.
libs	The basename of the Bowtie2 indexes to align against (without trailing .bt2 or .bt2l extensions).
align_dir	Path to the directory where the output alignment file should be created.
align_file	The basename of the output alignment file (without trailing .bam extension).

bowtie2_options

	Optional: Additional parameters that can be passed to the align_target_bowtie()
	function. To see all the available parameters use Rbowtie2::bowtie2_usage().
	See Details for default parameters. NOTE: Users should pass all their parame-
	ters as one string and if optional parameters are given then the user is responsible
	for entering all the parameters to be used by Bowtie2. The only parameter that
	should NOT be specified here is the number of threads.
threads	The number of threads that can be utilized by the function. Default is 1 thread.
overwrite	Whether existing files should be overwritten. Default is FALSE.
quiet	Turns off most messages. Default is TRUE.

Details

The default parameters are the same that PathoScope 2.0 uses. "-very-sensitive-local -k 100 -score-min L,20,1.0"

If you experience any issues with reading the input files, make sure that the file(s) are not located in a read-only folder. This can be circumvented by copying files to a new location before running the function.

Value

Returns the path to where the output alignment file is stored.

Examples

Align example reads to an example reference library using Rbowtie2

```
## Create temporary directory to store file
target_ref_temp <- tempfile()
dir.create(target_ref_temp)
```

```
## Create temporary directory to store the indices
index_temp <- tempfile()
dir.create(index_temp)
```

```
## Create bowtie2 index
MetaScope::mk_bowtie_index(
  ref_dir = target_ref_temp,
  lib_dir = index_temp,
  lib_name = "target",
  overwrite = TRUE
```

```
)
## Create temporary directory for final file
output_temp <- tempfile()</pre>
dir.create(output_temp)
## Get path to example reads
readPath <- system.file("extdata", "virus_example.fastq",</pre>
                        package = "MetaScope")
## Align to target genomes
target_map <-</pre>
 MetaScope::align_target_bowtie(
    read1 = readPath,
   lib_dir = index_temp,
   libs = "target",
    align_dir = output_temp,
   align_file = "bowtie_target",
   overwrite = TRUE,
   bowtie2_options = "--very-sensitive-local"
 )
## Remove extra folders
unlink(target_ref_temp, recursive = TRUE)
unlink(index_temp, recursive = TRUE)
unlink(output_temp, recursive = TRUE)
```

bam_reheader_R Replace the header from a .bam file

Description

This function replaces the header from one .bam file with a header from a different .sam file. This function mimics the function of the 'reheader' function in samtools. It is not intended for use by users.

Usage

```
bam_reheader_R(
    head,
    old_bam,
    new_bam = paste(tools::file_path_sans_ext(old_bam), "h.bam", sep = "")
)
```

Arguments

head	A file name and location for the .sam file with the new header.
old_bam	A file name and location for the .bam file which you would

8

new_bam A file name for the new .bam file with a replaced header. Defaults to the same base filename plus 'h.bam'. For example, 'example.bam' will be written as 'exampleh.bam'.

Value

This function will return a new .bam file with a replaced header. The function also outputs the new .bam filename.

blast_result_metrics Calculates result metrics from a blast results table

Description

This function calculates the best hit (genome with most blast read hits), uniqueness score (total number of genomes hit), species percentage hit (percentage of reads where MetaScope species also matched the blast hit species), genus percentage hit (percentage of reads where blast genus matched MetaScope aligned genus) and species contaminant score (percentage of reads that blasted to other species genomes) and genus contaminant score (percentage of reads that blasted to other genus genomes)

Usage

blast_result_metrics(blast_results_table_path, NCBI_key = NULL)

Arguments

blast_results_table_path	
	path for blast results csv file
NCBI_key	(character) NCBI Entrez API key. optional. See taxize::use_entrez(). Due to the high number of requests made to NCBI, this function will be less prone to errors if you obtain an NCBI key.

Value

a dataframe with best_hit, uniqueness_score, species_percentage_hit genus_percentage_hit, species_contaminant_score, and genus_contaminant_score

```
bt2_16S_params
```

Description

This character string provides several Bowtie 2 options to provide an optimized alignment specifically optimized for 16S amplicon sequencing data. This object can be used with functions that use the Bowtie 2 aligner through the Rbowtie2 package, namely align_target_bowtie() and filter_host_bowtie. These settings can be substituted for default settings by passing to the bowtie2_options argument.

Usage

data(bt2_16S_params)

Format

list

Details

The default parameters listed in this object are "-local -R 2 -N 0 -L 25 -i S,1,0.75 -k 5 -score-min L,0,1.88"

Note that k is actually 10 and is doubled internally from 5. The score-min function was chosen such that the minimum alignment score allowed requires 98

Further delineation of Bowtie 2 parameters is provided in the Bowtie 2 manual.

Examples

data("bt2_16S_params")

<pre>bt2_missing_params</pre>	A universal parameter object for Bowtie 2 metagenomic alignment
	where the host genome is thought to be absent from the reference database

Description

This character string provides several Bowtie 2 options to conduct an alignment useful for metagenomes, especially in the case where a genome may not be present in the reference database. This object can be used with functions that use the Bowtie 2 aligner through the Rbowtie2 package, namely align_target_bowtie() and filter_host_bowtie. These settings can be substituted for default settings by passing to the bowtie2_options argument.

```
bt2_regular_params
```

Usage

data(bt2_missing_params)

Format

list

Details

The default parameters listed in this object are "-local -R 2 -N 0 -L 25 -i S,1,0.75 -k 5 -score-min L,0,1.4".

Further delineation of Bowtie 2 parameters is provided in the Bowtie 2 manual.

Examples

data("bt2_missing_params")

bt2_regular_params	A universal parameter object for Bowtie 2 metagenomic or non-16S
	alignment

Description

This character string provides several Bowtie 2 options to provide a 95 alignment useful for metagenomes. This object can be used with functions that use the Bowtie 2 aligner through the Rbowtie2 package, namely align_target_bowtie() and filter_host_bowtie. These settings can be substituted for default settings by passing to the bowtie2_options argument.

Usage

```
data(bt2_regular_params)
```

Format

list

Details

The default parameters listed in this object are "-local -R 2 -N 0 -L 25 -i S,1,0.75 -k 5 -score-min L,0,1.7".

Further delineation of Bowtie 2 parameters is provided in the Bowtie 2 manual.

Examples

```
data("bt2_regular_params")
```

check_samtools_exists Check if samtools exists on the system

Description

This is an internal function that is not meant to be used outside of the package. It checks whether samtools exists on the system.

Usage

```
check_samtools_exists()
```

Value

Returns TRUE if samtools exists on the system, else FALSE.

combined_header

Create a combined .bam header

Description

This function generates a combined header from multiple .bam files from different reference libraries (e.g. a split bacterial library). It is not intended for use by users.

Usage

```
combined_header(bam_files, header_file = "header_tmp.sam")
```

Arguments

bam_files	A character vector of the locations/file names of .bam files from which to com- bine the headers.
header_file	A file name and location for the output file for the combined header. This will be a .sam format file without any reads. Defaults to 'header_tmp.sam'.

Value

This function will return a combined header from all the supplied .bam files.

convert_animalcules

Create a multi-assay experiment from MetaScope output for usage with animalcules

Description

Upon completion of the MetaScope pipeline, users can analyze and visualize abundances in their samples using the animalcules package. This function allows interoperability of metascope_id output with both animalcules and QIIME. After running this function, the user should save the returned MAE to an RDS file using a function like saveRDS to upload the output into the animalcules package.

Usage

```
convert_animalcules(
  meta_counts,
  annot_path,
  which_annot_col,
  end_string = ".metascope_id.csv",
  qiime_biom_out = FALSE,
  path_to_write = ".",
  NCBI_key = NULL,
  num_tries = 3
)
```

Arguments

meta_counts	A vector of filepaths to the counts ID CSVs output by metascope_id().
annot_path	The filepath to the CSV annotation file for the samples.
which_annot_co	1
	The name of the column of the annotation file containing the sample IDs. These should be the same as the meta_counts root filenames.
end_string	The end string used at the end of the metascope_id files. Default is ".metas-cope_id.csv".
qiime_biom_out	Would you also like a qiime-compatible biom file output? If yes, two files will be saved: one is a biom file of the counts table, and the other is a specifically formatted mapping file of metadata information. Default is FALSE.
path_to_write	If qiime_biom_out = TRUE, where should output QIIME files be written? Should be a character string of the folder path. Default is '.', i.e. the current working directory.
NCBI_key	(character) NCBI Entrez API key. optional. See taxize::use_entrez(). Due to the high number of requests made to NCBI, this function will be less prone to errors if you obtain an NCBI key.
num_tries	(numeric) Number of attempts to get UID.

Value

Returns a MultiAssay Experiment file of combined sample counts data and/or biom file and mapping file for analysis with QIIME. The MultiAssay Experiment will have a counts assay ("MGX").

Examples

```
tempfolder <- tempfile()</pre>
dir.create(tempfolder)
# Create three different samples
samp_names <- c("X123", "X456", "X789")</pre>
all_files <- file.path(tempfolder,</pre>
                        paste0(samp_names, ".csv"))
create_IDcsv <- function (out_file) {</pre>
 final_taxids <- c("273036", "418127", "11234")
 final_genomes <- c(</pre>
    "Staphylococcus aureus RF122, complete sequence",
    "{\ensuremath{\mathsf{Staphylococcus}}} aureus subsp. aureus Mu3, complete sequence",
    "Measles virus, complete genome")
 best_hit <- sample(seq(100, 1050), 3)</pre>
 proportion <- best_hit/sum(best_hit) |> round(2)
 EMreads <- best_hit + round(runif(3), 1)</pre>
 EMprop <- proportion + 0.003
 dplyr::tibble(TaxonomyID = final_taxids,
                 Genome = final_genomes,
                 read_count = best_hit, Proportion = proportion,
                 EMreads = EMreads, EMProportion = EMprop) |>
   dplyr::arrange(dplyr::desc(.data$read_count)) |>
    utils::write.csv(file = out_file, row.names = FALSE)
 message("Done!")
 return(out_file)
}
out_files <- vapply(all_files, create_IDcsv, FUN.VALUE = character(1))</pre>
# Create annotation data for samples
annot_dat <- file.path(tempfolder, "annot.csv")</pre>
dplyr::tibble(Sample = samp_names, RSV = c("pos", "neg", "pos"),
              month = c("March", "July", "Aug"),
              yrsold = c(0.5, 0.6, 0.2)) |>
 utils::write.csv(file = annot_dat,
                    row.names = FALSE)
# Convert samples to MAE
outMAE <- convert_animalcules(meta_counts = out_files,</pre>
                                annot_path = annot_dat,
                                which_annot_col = "Sample",
                                end_string = ".metascope_id.csv",
                                qiime_biom_out = FALSE,
                               NCBI_key = NULL)
unlink(tempfolder, recursive = TRUE)
```

convert_animalcules_patho

Create a multi-assay experiment from PathoScope 2.0 output for usage with animalcules

Description

This function serves as a legacy integration method for usage with PathoScope 2.0 outputs. Upon completion of the PathoScope 2.0 pipeline, users can analyze and visualize abundances in their samples using the animalcules package. After running this function, the user should save the returned MAE to an RDS file using a function like saveRDS to upload the output into the animalcules package.

Usage

```
convert_animalcules_patho(
   patho_counts,
   annot_path,
   which_annot_col,
   end_string = "-sam-report.tsv"
)
```

Arguments

patho_counts	$Character \ string, \ a \ directory \ filepath \ to \ the \ counts \ ID \ CSVs \ output \ by \ metascope_id().$	
annot_path	The filepath to the CSV annotation file for the samples.	
which_annot_col		
	The name of the column of the annotation file containing the sample IDs. These should be the same as the meta_counts root filenames.	
end_string	The end string used at the end of the metascope_id files. Default is ".metas-cope_id.csv".	

Value

Returns a MultiAssay Experiment file of combined sample counts data. The MultiAssay Experiment will have a counts assay ("MGX").

```
convert_animalcules_silva
```

Create a multi-assay experiment from MetaScope output for usage with animalcules with the SILVA 13_8 database

Description

Upon completion of the MetaScope pipeline, users can analyze and visualize abundances in their samples using the animalcules package. This function allows interoperability of metascope_id output with both animalcules and QIIME. After running this function, the user should save the returned MAE to an RDS file using a function like saveRDS to upload the output into the animalcules package. NOTE: This function is for outputs that were generated with the SILVA 13_8 database.

Usage

```
convert_animalcules_silva(
  meta_counts,
  annot_path,
  which_annot_col,
  end_string = ".metascope_id.csv",
  qiime_biom_out = FALSE,
  path_to_write = ".",
  caching = TRUE
)
```

Arguments

meta_counts	A vector of filepaths to the counts ID CSVs output by $metascope_id()$ created with the SILVA database.
annot_path	The filepath to the CSV annotation file for the samples.
which_annot_col	
	The name of the column of the annotation file containing the sample IDs. These should be the same as the meta_counts root filenames.
end_string	The end string used at the end of the metascope_id files. Default is ".metascope_id.csv".
qiime_biom_out	Would you also like a qiime-compatible biom file output? If yes, two files will be saved: one is a biom file of the counts table, and the other is a specifically formatted mapping file of metadata information. Default is FALSE.
path_to_write	If qiime_biom_out = TRUE, where should output QIIME files be written? Should be a character string of the folder path. Default is '.', i.e. the current working directory.
caching	Whether to use BiocFileCache when downloading genomes. Default is FALSE.

Value

Returns a MultiAssay Experiment file of combined sample counts data and/or saved biom file and mapping file for analysis with QIIME. The MultiAssayExperiment will have a counts assay ("MGX").

Examples

```
tempfolder <- tempfile()</pre>
dir.create(tempfolder)
# Create three different samples
samp_names <- c("X123", "X456", "X789")</pre>
all_files <- file.path(tempfolder,</pre>
                        paste0(samp_names, ".csv"))
create_IDcsv <- function (out_file) {</pre>
  final_taxids <- c("AY846380.1.2583", "AY909584.1.2313", "HG531388.1.1375")</pre>
  final_genomes <- rep("Genome name", 3)</pre>
  best_hit <- sample(seq(100, 1050), 3)</pre>
  proportion <- best_hit/sum(best_hit) |> round(2)
  EMreads <- best_hit + round(runif(3), 1)</pre>
  EMprop <- proportion + 0.003
  dplyr::tibble("TaxonomyID" = final_taxids,
                 "Genome" = final_genomes,
                 "read_count" = best_hit, "Proportion" = proportion,
                 "EMreads" = EMreads, "EMProportion" = EMprop) |>
    dplyr::arrange(dplyr::desc(.data$read_count)) |>
    utils::write.csv(file = out_file, row.names = FALSE)
  message("Done!")
  return(out_file)
}
out_files <- vapply(all_files, create_IDcsv, FUN.VALUE = character(1))</pre>
# Create annotation data for samples
annot_dat <- file.path(tempfolder, "annot.csv")</pre>
dplyr::tibble(Sample = samp_names, RSV = c("pos", "neg", "pos"),
              month = c("March", "July", "Aug"),
              yrsold = c(0.5, 0.6, 0.2)) |>
  utils::write.csv(file = annot_dat,
                    row.names = FALSE)
# Convert samples to MAE
outMAE <- convert_animalcules_silva(meta_counts = out_files,</pre>
                                annot_path = annot_dat,
                                which_annot_col = "Sample",
                                end_string = ".metascope_id.csv",
                                qiime_biom_out = FALSE,
                                caching = TRUE)
unlink(tempfolder, recursive = TRUE)
```

count_matches

Description

The 'CIGAR' (Compact Idiosyncratic Gapped Alignment Report) string is how the SAM/BAM format represents spliced alignments. This function will accept a CIGAR string for a single read and a single character indicating the operation to be parsed in the string. An operation is a type of column that appears in the alignment, e.g. a match or gap. The integer following the operator specifies a number of consecutive operations. The count_matches() function will identify all occurrences of the operator in the string input, add them, and return an integer number representing the total number of operations for the read that was summarized by the input CIGAR string.

Usage

 $count_matches(x, char = "M")$

Arguments

х	Character. A CIGAR string for a read to be parsed. Examples of possible oper-
	ators include "M", "D", "I", "S", "H", "=", "P", and "X".
char	A single letter representing the operation to total for the given string.

Details

This function is best used on a vector of CIGAR strings using an apply function (see examples).

Value

an integer number representing the total number of alignment operations for the read that was summarized by the input CIGAR string.

Examples

```
# A single cigar string: 3M + 3M + 5M
cigar1 <- "3M1I3M1D5M"
count_matches(cigar1, char = "M")
# Parse with operator "P": 2P
cigar2 <- "4M1I2P9M"
count_matches(cigar2, char = "P")
# Apply to multiple strings: 1I + 1I + 5I
cigar3 <- c("3M1I3M1D5M", "4M1I1P9M", "76M13M5I")
vapply(cigar3, count_matches, char = "I",
FUN.VALUE = numeric(1))
```

demultiplex

Description

Function for demultiplexing sequencing reads arranged in a common format provided by sequencers (such as Illumina) generally for 16S data. This function takes a matrix of sample names/barcodes, a .fastq file of barcodes by sequence header, and a .fastq file of reads corresponding to the barcodes. Based on the barcodes given, the function extracts all reads for the indexed barcode and writes all the reads from that barcode to separate .fastq files.

Usage

```
demultiplex(
   barcodeFile,
   indexFile,
   readFile,
   rcBarcodes = TRUE,
   location = NULL,
   threads = 1,
   hammingDist = 0,
   quiet = TRUE
)
```

Arguments

barcodeFile	File name for a file containing a .tsv matrix with a header row, and then sample names (column 1) and barcodes (column 2).
indexFile	Location to a .fastq file that contains the barcodes for each read. The headers should be the same (and in the same order) as readFile, and the sequence in the indexFile should be the corresponding barcode for each read. Quality scores are not considered.
readFile	Location to the sequencing read .fastq file that corresponds to the indexFile.
rcBarcodes	Should the barcode indexes in the barcodeFile be reverse complemented to match the sequences in the indexFile? Defaults to TRUE.
location	A directory location to store the demultiplexed read files. Defaults to generate a new temporary directory.
threads	The number of threads to use for parallelization (BiocParallel). This function will parallelize over the barcodes and extract reads for each barcode separately and write them to separate demultiplexed files.
hammingDist	Uses a Hamming Distance or number of base differences to allow for inexact matches for the barcodes/indexes. Defaults to 0. Warning: if the Hamming Distance is >=1 and this leads to inexact index matches to more than one barcode, that read will be written to more than one demultiplexed read files.
quiet	Turns off most messages. Default is TRUE.

Value

Returns multiple .fastq files that contain all reads whose index matches the barcodes given. These files will be written to the location directory, and will be named based on the given sampleNames and barcodes, e.g. './demultiplex_fastq/SampleName1_GGAATTATCGGT.fastq.gz'

Examples

download_refseq Download RefSeq genome libraries

Description

This function will automatically download RefSeq genome libraries in a fasta format from the specified taxon. The function will first download the summary report at: ftp://ftp.ncbi.nlm.nih.gov/genomes/refseq/**ki and then use this file to download the genome(s) and combine them in a single compressed or uncompressed .fasta file.

Usage

```
download_refseq(
  taxon,
  reference = TRUE,
  representative = FALSE,
  compress = TRUE,
  patho_out = FALSE,
  out_dir = NULL,
  caching = FALSE,
  quiet = TRUE
)
```

Arguments

taxon

Name of single taxon to download. The taxon name should be a recognized NCBI scientific or common name, with no grammatical or capitalization inconsistencies. All available taxonomies are visible by accessing the MetaScope:::taxonomy_table object included in the package.

extract_reads

reference	Download only RefSeq reference genomes? Defaults to TRUE. Automatically set to TRUE if representative = TRUE.
representative	Download RefSeq representative and reference genomes? Defaults to FALSE. If TRUE, reference is automatically set at TRUE.
compress	Compress the output .fasta file? Defaults to TRUE.
patho_out	Create duplicate outpute files compatible with PathoScope? Defaults to FALSE.
out_dir	Character string giving the name of the directory to which libraries should be output. Defaults to creation of a new temporary directory.
caching	Whether to use BiocFileCache when downloading genomes. Default is FALSE.
quiet	Turns off most messages. Default is TRUE.

Details

When selecting the taxon to be downloaded, if you receive an error saying Your input is not a valid taxon, please take a look at the taxonomy_table object, which can be accessed with the command MetaScope:::taxonomy_table). Only taxa with exact spelling as they appear at any level of the table will be acknowledged.

Value

Returns a .fasta or .fasta.gz file of the desired RefSeq genomes. This file is named after the kingdom selected and saved to the current directory (e.g. 'bacteria.fasta.gz'). This function also has the option to return a .fasta file formatted for PathoScope as well (e.g. bacteria.pathoscope.fasta.gz') if path_out = TRUE.

Examples

Download RefSeq genomes

extract_reads Helper function for demultiplexing

Description

Helper function for demultiplexing sequencing reads, designed in a way to allow for parallelization across barcodes (parallel extraction of reads by barcode). This function takes a specific barcode (numeric index) from lists of sample names/barcodes, a Biostrings::DNAStringSet of barcodes by sequence header, and a Biostrings::QualityScaledXStringSet of reads corresponding to the barcodes. Based on the barcode index given, it extracts all reads for the indexed barcode and writes all the reads from that barcode to a separate .fastq file.

Usage

```
extract_reads(
   barcodeIndex,
   barcodes,
   sampleNames,
   index,
   reads,
   location = "./demultiplex_fastq",
   rcBarcodes = TRUE,
   hDist = 0,
   quiet = TRUE
)
```

Arguments

barcodeIndex	Which barcode (integer number or index) in the barcodes or sample name to use for read extraction.
barcodes	A list of all barcodes in the sequencing dataset. Correlates and in same order as sampleNames.
sampleNames	A list of sample names or identifiers associated with each barcode in the barcodes list.
index	A Biostrings::DNAStringSet that contains the read headers and barcode se- quence for each header in the sequence slot.
reads	A Biostrings::QualityScaledXStringSet that has the same headers and or- der as the index file, but contains the read sequences and their quality scores.
location	A directory location to store the demultiplexed read files. Defaults to generate a new subdirectory at './demultiplex_fastq'
rcBarcodes	Should the barcode indices in the barcodes list be reverse complemented to match the sequences in the index DNAStringSet? Defaults to TRUE.
hDist	Uses a Hamming Distance or number of base differences to allow for inexact matches for the barcodes/indexes. Defaults to 0. Warning: if the Hamming Distance is $>=1$ and this leads to inexact index matches to more than one barcode, that read will be written to more than one demultiplexed read files.
quiet	Turns off most messages. Default is TRUE.

Value

Writes a single .fastq file that contains all reads whose index matches the barcode specified. This file will be written to the location directory, and will be named based on the specified sampleName and barcode, e.g. './demultiplex_fastq/SampleName1_GGAATTATCGGT.fastq.gz'

Examples

```
## Create temporary directory
ref_temp <- tempfile()
dir.create(ref_temp)</pre>
```

22

```
## Load example barcode, index, and read data into R session
barcodePath <- system.file("extdata", "barcodes.txt", package = "MetaScope")</pre>
bcFile <- read.table(barcodePath, sep = "\t", header = TRUE)</pre>
indexPath <- system.file("extdata", "virus_example_index.fastq",
package = "MetaScope")
inds <- Biostrings::readDNAStringSet(indexPath, format = "fastq")</pre>
readPath <- system.file("extdata", "virus_example.fastq",</pre>
                         package = "MetaScope")
reads <- Biostrings::readQualityScaledDNAStringSet(readPath)</pre>
## Extract reads from the first barcode
results <- extract_reads(1, bcFile[, 2], bcFile[, 1], inds, reads,</pre>
                         rcBarcodes = FALSE, location = ref_temp)
## Extract reads from multiple barcodes
more_results <- lapply(1:6, extract_reads, bcFile[, 2], bcFile[, 1], inds,</pre>
                        reads, rcBarcodes = FALSE, location = ref_temp)
## Remove temporary directory
unlink(ref_temp, recursive = TRUE)
```

filter_host

Use Rsubread to align reads against one or more filter libraries and subsequently remove mapped reads

Description

After aligning your sample to a target library with align_target(), use filter_host() to remove unwelcome host contamination using filter reference libraries. This function takes as input the name of the .bam file produced via align_target(), and produces a sorted .bam file with any reads that match the filter libraries removed. This resulting .bam file may be used upstream for further analysis. This function uses Rsubread. For the Rbowtie2 equivalent of this function, see filter_host_bowtie.

Usage

```
filter_host(
  reads_bam,
  lib_dir = NULL,
  libs,
  make_bam = FALSE,
  output = paste(tools::file_path_sans_ext(reads_bam), "filtered", sep = "."),
  subread_options = align_details,
  YS = 1e+05,
  threads = 1,
```

```
quiet = TRUE
)
```

Arguments

reads_bam	The name of a merged, sorted .bam file that has previously been aligned to a reference library. Likely, the output from running an instance of align_target().
lib_dir	Path to the directory that contains the filter Subread index files.
libs	The basename of the filter libraries (without index extension).
make_bam	Logical, whether to also output a bam file with host reads filtered out. A .csv.gz file will be created instead if FALSE. Creating a bam file is costly on resources over creating a compressed csv file with only relevant information, so default is FALSE.
output	The desired name of the output .bam or .csv.gz file. Extension is automatically defined by whether make_bam = TRUE. Default is the basename of unfiltered_bam + .filtered + extension.
subread_options	
	A named list specifying alignment parameters for the Rsubread::align() function, which is called inside align_target(). Elements should include type, nthreads, maxMismatches, nsubreads, phredOffset, unique, and nBestLo- cations. Descriptions of these parameters are available under ?Rsubread::align. Defaults to the global align_details object.
YS	yieldSize, an integer. The number of alignments to be read in from the bam file at once for chunked functions. Default is 100000.
threads	The amount of threads available for the function. Default is 1 thread.
quiet	Turns off most messages. Default is TRUE.

Details

A compressed .csv can be created to produce a smaller output file that is created more efficiently and is still compatible with metascope_id().

Value

The name of a filtered, sorted .bam file written to the user's current working directory. Or, if make_bam = FALSE, a .csv.gz file containing a data frame of only requisite information to run metascope_id().

Examples

```
#### Filter reads from bam file that align to any of the filter libraries
## Assuming a bam file has been created previously with align_target()
## Create temporary directory
filter_ref_temp <- tempfile()
dir.create(filter_ref_temp)
## Download filter genome</pre>
```

24

```
all_species <- c("Staphylococcus aureus subsp. aureus str. Newman")
all_ref <- vapply(all_species, MetaScope::download_refseq,</pre>
                  reference = FALSE, representative = FALSE, compress = TRUE,
                  out_dir = filter_ref_temp, caching = FALSE,
                  FUN.VALUE = character(1))
ind_out <- vapply(all_ref, mk_subread_index, FUN.VALUE = character(1))</pre>
## Get path to example reads
readPath <- system.file("extdata", "subread_target.bam",</pre>
                        package = "MetaScope")
## Copy the example reads to the temp directory
refPath <- file.path(filter_ref_temp, "subread_target.bam")</pre>
file.copy(from = readPath, to = refPath)
utils::data("align_details")
align_details[["type"]] <- "rna"
align_details[["phredOffset"]] <- 10
# Just to get it to align - toy example!
align_details[["maxMismatches"]] <- 10
## Align and filter reads
filtered_map <- filter_host(</pre>
 refPath, lib_dir = filter_ref_temp,
 libs = stringr::str_replace_all(all_species, " ", "_"),
 threads = 1, subread_options = align_details)
## Remove temporary directory
unlink(filter_ref_temp, recursive = TRUE)
```

filter_host_bowtie Use Rbowtie2 to align reads against one or more filter libraries and subsequently remove mapped reads

Description

After a sample is aligned to a target library with align_target_bowtie(), we may use filter_host_bowtie() to remove unwelcome host contamination using filter reference libraries. This function takes as input the name of the .bam file produced via align_target_bowtie(), and produces a sorted .bam or .csv.gz file with any reads that match the filter libraries removed. This resulting .bam file may be used downstream for further analysis. This function uses Rbowtie2 For the Rsubread equivalent of this function, see filter_host.

Usage

```
filter_host_bowtie(
  reads_bam,
  lib_dir,
```

```
libs,
make_bam = FALSE,
output = paste(tools::file_path_sans_ext(reads_bam), "filtered", sep = "."),
bowtie2_options = NULL,
YS = 1e+05,
threads = 1,
overwrite = FALSE,
quiet = TRUE
```

Arguments

)

reads_bam	The name of a merged, sorted .bam file that has previously been aligned to a reference library. Likely, the output from running an instance of align_target_bowtie().	
lib_dir	Path to the directory that contains the filter Bowtie2 index files.	
libs	The basename of the filter libraries (without .bt2 or .bt2l extension).	
make_bam	Logical, whether to also output a bam file with host reads filtered out. A .csv.gz file will be created instead if FALSE. Creating a bam file is costly on resources over creating a compressed csv file with only relevant information, so default is FALSE.	
output	The desired name of the output .bam or .csv.gz file. Extension is automatically defined by whether make_bam = TRUE. Default is the basename of unfiltered_bam + .filtered + extension.	
bowtie2_options		
	Optional: Additional parameters that can be passed to the filter_host_bowtie() function. To see all the available parameters use Rbowtie2::bowtie2_usage(). See Details for default parameters. NOTE: Users should pass all their parameters as one string and if optional parameters are given then the user is responsible for entering all the parameters to be used by Bowtie2. The only parameters that should NOT be specified here is the threads.	
YS	yieldSize, an integer. The number of alignments to be read in from the bam file at once for chunked functions. Default is 100000.	
threads	The amount of threads available for the function. Default is 1 thread.	
overwrite	Whether existing files should be overwritten. Default is FALSE.	
quiet	Turns off most messages. Default is TRUE.	

Details

A compressed .csv can be created to produce a smaller output file that is created more efficiently and is still compatible with metascope_id().

The default parameters are the same that PathoScope 2.0 uses. "-very-sensitive-local -k 100 -score-min L,20,1.0"

Value

The name of a filtered, sorted .bam file written to the user's current working directory. Or, if make_bam = FALSE, a .csv.gz file containing a data frame of only requisite information to run metascope_id().

26

Examples

Filter reads from bam file that align to any of the filter libraries

```
## Assuming a bam file has already been created with align_target_bowtie()
# Create temporary filter library
filter_ref_temp <- tempfile()</pre>
dir.create(filter_ref_temp)
## Download reference genome
MetaScope::download_refseq("Orthoebolavirus zairense",
                            reference = FALSE,
                            representative = FALSE,
                            compress = TRUE,
                            out_dir = filter_ref_temp,
                            caching = TRUE)
## Create temp directory to store the indices
index_temp <- tempfile()</pre>
dir.create(index_temp)
## Create filter index
MetaScope::mk_bowtie_index(
  ref_dir = filter_ref_temp,
  lib_dir = index_temp,
  lib_name = "filter",
  overwrite = TRUE
)
## Create temporary folder to hold final output file
output_temp <- tempfile()</pre>
dir.create(output_temp)
## Get path to example bam
bamPath <- system.file("extdata", "bowtie_target.bam",</pre>
                        package = "MetaScope")
target_copied <- file.path(output_temp, "bowtie_target.bam")</pre>
file.copy(bamPath, target_copied)
## Align and filter reads
filter_out <-</pre>
  filter_host_bowtie(
    reads_bam = target_copied,
    lib_dir = index_temp,
    libs = "filter",
    threads = 1
  )
## Remove temporary directories
unlink(filter_ref_temp, recursive = TRUE)
unlink(index_temp, recursive = TRUE)
unlink(output_temp, recursive = TRUE)
```

filter_unmapped_reads Filter unmapped reads

Description

This function will remove all unmapped reads or lines in a .bam file (warning: overwrites the original file!). This function is needed because combining multiple .bam files from different microbial libraries may lead to some reads that mapped to one library and have unmapped entries from another library. This will remove any unmapped entries and leave all reference mapped lines in the .bam file.

Usage

filter_unmapped_reads(bamfile)

Arguments

bamfile Location for the .bam file to filter & remove all unmapped reads

Details

It is not intended for direct use.

Value

This function will overwrite the existing .bam file with a new .bam file in the same location that has only mapped lines. The function itself returns the output .bam file name.

Description

This function will utilize an organism classification table to obtain all children species and/or strains with available NCBI reference sequences given a parent taxon and its rank.

Usage

```
get_children(input_taxon, input_rank, tax_dat = NULL)
```

Arguments

input_taxon	The parent taxon.	
input_rank	The taxonomic rank of the input taxon.	
tax_dat	A dataframe of organism classification information. At minimum, should have a column indicating "strain", and and all others should be taxonomic ranks. Each row should be a taxonomic relationship. This defaults to NULL, which calls the 'taxonomy_table' object.	

get_seqs

Value

Returns a vector of all the child species and/or strains of the input taxon.

Examples

```
## Get all child species and strains in bacteria superkingdom
get_children('Bacteria','superkingdom')
```

Get all child species and strains in fungi kingdom
get_children('Fungi', 'kingdom')

```
## Get all child species in primate order
get_children('Primates', 'order')
```

get_seqs

Gets sequences from bam file

Description

Returns fasta sequences from a bam file with a given taxonomy ID

Usage

get_seqs(id, bam_file, n = 10, quiet, NCBI_key = NULL, bam_seqs)

Arguments

id	Taxonomy ID of genome to get sequences from	
bam_file	A sorted bam file and index file, loaded with Rsamtools::bamFile	
n	Number of sequences to retrieve	
quiet	Logical, whether to print out more informative messages. Default is FALSE.	
NCBI_key	(character) NCBI Entrez API key. optional. See taxize::use_entrez(). Due to the high number of requests made to NCBI, this function will be less prone to errors if you obtain an NCBI key.	
bam_seqs	A list of the sequence IDs from the bam file	

Value

Biostrings format sequences

locations

Description

Used to create plots of genome coverage for any number of accession numbers

Usage

```
locations(
  which_taxid,
  which_genome,
  accessions,
  taxids,
  reads,
  out_base,
  out_dir
)
```

Arguments

which_taxid	Which taxid to plot
which_genome	Which genome to plot
accessions	List of accessions from metascope_id()
taxids	List of accessions from metascope_id()
reads	List of reads from input file
out_base	The basename of the input file
out_dir	The path to the input file

Value

A plot of the read coverage for a given genome

merge_bam_files Merge multiple .bam files

Description

This function merges .bam files. It first used the combined_header function to generate a combined header for all the files, reheaders the files, and then merges and sorts the .bam files. It is similar to the 'samtools merge' function, but it allows the .bam files to have different headers. It is not intended for direct use.

metascope_blast

Usage

```
merge_bam_files(
    bam_files,
    destination,
    head_file = paste(destination, "_header.sam", sep = ""),
    quiet = TRUE
)
```

Arguments

bam_files	A list of file names for the .bam files to be merged.
destination	A file name and location for the merged .bam file.
head_file	A file name and location for the combined header file. Defaults to the destina- tion. For example, 'example.bam' will be written as 'example.bam'.
quiet	Turns off most messages. Default is TRUE.

Value

This function merges .bam files and combines them into a single file. The function also outputs the new .bam filename.

metascope_blast Blast reads from MetaScope aligned files

Description

This function allows the user to check a subset of identified reads against NCBI BLAST and the nucleotide database to confirm or contradict results provided by MetaScope. It aligns the top 'metascope_id()' results to NCBI BLAST database. It REQUIRES that command-line BLAST and a separate nucleotide database have already been installed on the host machine. It returns a csv file updated with BLAST result metrics.

Usage

```
metascope_blast(
    metascope_id_path,
    bam_file_path = list.files(tmp_dir, ".updated.bam$", full.names = TRUE)[1],
    tmp_dir,
    out_dir,
    sample_name,
    num_results = 10,
    num_reads = 100,
    hit_list = 10,
    num_threads = 1,
    db_path,
    quiet = FALSE,
    NCBI_key = NULL
)
```

Arguments

metascope_id_path		
	Character string; path to a csv file output by 'metascope_id()'.	
bam_file_path	Character string; full path to bam file for the same sample processed by 'metas- cope_id'. Note that the 'filter_bam' function must have output a bam file, and not a .csv.gz file. See '?filter_bam_bowtie' for more details. Defaults to list.files(file_temp, ".updated.bam\$")[1].	
tmp_dir	Character string, a temporary directory in which to host files.	
out_dir	Character string, path to output directory.	
sample_name	Character string, sample name for output files.	
num_results	Integer, the maximum number of taxa from the metascope_id output to check reads. Takes the top n taxa, i.e. those with largest abundance. Default is 10.	
num_reads	Integer, the maximum number of reads to blast per microbe. If the true number of reads assigned to a given taxon is smaller, then the smaller number will be chosen. Default is 100. Too many reads will involve more processing time.	
hit_list	Integer, number of blast hit results to keep. Default is 10.	
num_threads	Integer, number of threads if running in parallel (recommended). Default is 1.	
db_path	Character string. The database file to be searched (including basename, but without file extension). For example, if the nt database is in the nt folder, this would be /filepath/nt/nt assuming that the database files have the nt basename. Check this path if you get an error message stating "No alias or index file found".	
quiet	Logical, whether to print out more informative messages. Default is FALSE.	
NCBI_key	(character) NCBI Entrez API key. optional. See taxize::use_entrez(). Due to the high number of requests made to NCBI, this function will be less prone to errors if you obtain an NCBI key.	

Details

This function assumes that you used the NCBI nucleotide database to process samples, with a download date of 2021 or later. This is necessary for compatibility with the bam file headers.

This is highly computationally intensive and should be ran with multiple cores, submitted as a multi-threaded computing job if possible.

Note, if best_hit_strain is FALSE, then no strain was observed more often among the BLAST results.

Value

This function writes an updated csv file with metrics evaluating...

Examples

```
## Not run:
### Create temporary directory
file_temp <- tempfile()
dir.create(file_temp)
```

```
bamPath <- system.file("extdata", "bowtie_target.bam",</pre>
                       package = "MetaScope")
file.copy(bamPath, file_temp)
metascope_id(file.path(file_temp, "bowtie_target.bam"), aligner = "bowtie2",
             input_type = "bam", out_dir = file_temp, num_species_plot = 0,
             update_bam = TRUE)
## Run metascope blast
### Get export name and metascope id results
out_base <- bamPath %>% base::basename() %>% strsplit(split = "\\.") %>%
 magrittr::extract2(1) %>% magrittr::extract(1)
metascope_id_path <- file.path(file_temp, paste0(out_base, ".metascope_id.csv"))</pre>
# NOTE: change db_path to the location where your BLAST database is stored!
db <- "/restricted/projectnb/pathoscope/data/blastdb/nt/nt"</pre>
Sys.setenv(ENTREZ_KEY = "<your id here>")
metascope_blast(metascope_id_path,
                bam_file_path = file.path(file_temp, "bowtie_target.updated.bam"),
                tmp_dir = file_temp,
                out_dir = file_temp,
                sample_name = out_base,
                db_path = db,
                num_results = 10,
                num_reads = 5,
                hit_list = 10,
                num_threads = 3,
                quiet = FALSE,
                NCBI_key = NULL)
## Remove temporary directory
unlink(file_temp, recursive = TRUE)
## End(Not run)
```

metascope_id Identify which genomes are represented in a processed sample

Description

This function will read in a .bam or .csv.gz file, annotate the taxonomy and genome names, reduce the mapping ambiguity using a mixture model, and output a .csv file with the results. Currently, it assumes that the genome library/.bam files use NCBI accession names for reference names (rnames in .bam file).

Usage

```
metascope_id(
  input_file,
  input_type = "csv.gz",
 aligner = "bowtie2",
 db = "ncbi",
 db_feature_table = NULL,
 NCBI_key = NULL,
 out_dir = dirname(input_file),
 convEM = 1/10000,
 maxitsEM = 25,
 blast_fastas = FALSE,
 num_genomes = 100,
 num_reads = 50,
 update_bam = FALSE,
 num_species_plot = NULL,
 quiet = TRUE
)
```

Arguments

input_file	The .bam or .csv.gz file of sample reads to be identified.
input_type	Extension of file input. Should be either "bam" or "csv.gz". Default is "csv.gz".
aligner	The aligner which was used to create the bam file. Default is "bowtie2" but can also be set to "subread" or "other".
db	Currently accepts one of c("ncbi", "silva", "other") Default is "ncbi", appropriate for samples aligned against indices compiled from NCBI whole genome databases. Alternatively, usage of an alternate database (like Green- genes2) should be specified with "other".
db_feature_tabl	e
	If db = "other", a data.frame must be supplied with two columns, "Feature ID" matching the names of the alignment indices, and a second character column supplying the taxon identifying information.
NCBI_key	(character) NCBI Entrez API key. optional. See taxize::use_entrez(). Due to the high number of requests made to NCBI, this function will be less prone to errors if you obtain an NCBI key. You may enter the string as an input or set it as ENTREZ_KEY in .Renviron.
out_dir	The directory to which the .csv output file will be output. Defaults to dirname(input_file).
convEM	The convergence parameter of the EM algorithm. Default set at 1/10000.
maxitsEM	The maximum number of EM iterations, regardless of whether the convEM is below the threshold. Default set at 50. If set at 0, the algorithm skips the EM step and summarizes the .bam file 'as is'
blast_fastas	Logical, whether or not to output fasta files for MetaBlast. Default is FALSE.
num_genomes	Number of genomes to output fasta files for MetaBlast. Default is 100.
num_reads	Number of reads per genome per fasta file for MetaBlast. Default is 50.

34

metascope_id

update_bam	Whether to update BAM file with new read assignments. Default is FALSE.
	If TRUE, requires input_type = TRUE such that a BAM file is the input to the
	function.
<pre>num_species_plo</pre>	t
	The number of genome coverage plots to be saved. Default is NULL, which saves coverage plots for the ten most highly abundant species.
quiet	Turns off most messages. Default is TRUE.

Value

This function returns a .csv file with annotated read counts to genomes with mapped reads. The function itself returns the output .csv file name. Depending on the parameters specified, can also output an updated BAM file, and fasta files for usage downstream with MetaBLAST.

Examples

```
#### Align reads to reference library and then apply metascope_id()
## Assuming filtered bam files already exist
## Create temporary directory
file_temp <- tempfile()</pre>
dir.create(file_temp)
#### Subread aligned bam file
## Create object with path to filtered subread csv.gz file
filt_file <- "subread_target.filtered.csv.gz"</pre>
bamPath <- system.file("extdata", filt_file, package = "MetaScope")</pre>
file.copy(bamPath, file_temp)
## Run metascope id with the aligner option set to subread
metascope_id(input_file = file.path(file_temp, filt_file),
             aligner = "subread", num_species_plot = 0,
             input_type = "csv.gz")
#### Bowtie 2 aligned .csv.gz file
## Create object with path to filtered bowtie2 bam file
bowtie_file <- "bowtie_target.filtered.csv.gz"</pre>
bamPath <- system.file("extdata", bowtie_file, package = "MetaScope")</pre>
file.copy(bamPath, file_temp)
## Run metascope id with the aligner option set to bowtie2
metascope_id(file.path(file_temp, bowtie_file), aligner = "bowtie2",
             num_species_plot = 0, input_type = "csv.gz")
## Remove temporary directory
unlink(file_temp, recursive = TRUE)
```

mk_bowtie_index Mak

Description

This function is a wrapper for the Rbowtie2::bowtie2_build function. It will create either small (.bt2) or large Bowtie2 indexes (.bt2l) depending on the combined size of the reference fasta files.

Usage

```
mk_bowtie_index(
   ref_dir,
   lib_dir,
   lib_name,
   bowtie2_build_options,
   threads = 1,
   overwrite = FALSE
)
```

Arguments

ref_dir	The path to the directory that contains the reference files either uncompressed or compressed (.gz). NOTE: This directory should contain only the reference fasta files to be indexed.
lib_dir	The path to the directory where Bowtie2 index files should be created.
lib_name	The basename of the index file to be created (without the .bt2 or .bt2l extension)
bowtie2_build_c	ptions
	Optional: Options that can be passed to the mk_bowtie_index() function. All options should be passed as one string. To see all the available options that can be passed to the function use Rbowtie2::bowtie2_build_usage(). NOTE: Do not specify threads here.
threads	The number of threads available to the function. Default is 1 thread.
overwrite	Whether existing files should be overwritten. Default is FALSE.

Value

Creates the Bowtie2 indexes of the supplied reference .fasta files. Returns the path to the directory containing these files.

Examples

Create a bowtie index from the example reference library

```
## Create a temporary directory to store the reference library
ref_temp <- tempfile()
dir.create(ref_temp)</pre>
```

mk_subread_index Make a Subread index

Description

This function is a wrapper for the Rsubread::buildindex function. It will generate one or more Subread indexes from a .fasta file. If the library is too large (default >4GB) it will automatically be split into multiple indexes, with _1, _2, etc at the end of the ref_lib basename.

Usage

```
mk_subread_index(ref_lib, split = 4, mem = 8000, quiet = TRUE)
```

Arguments

ref_lib	The name/location of the reference library file, in (uncompressed) .fasta format.
split	The maximum allowed size of the genome file (in GB). If the ref_lib file is larger than this, the function will split the library into multiple parts.
mem	The maximum amount of memory (in MB) that can be used by the index gener- ation process (used by the Rsubread::buildindex function).
quiet	Turns off most messages. Default is TRUE.

Value

Creates one or more Subread indexes for the supplied reference .fasta file. If multiple indexes are created, the libraries will be named the ref_lib basename + "_1", "_2", etc. The function returns the names of the folders holding these files.

Examples

rBlast_results rBlast_results

Description

rBlast_results

Usage

```
rBlast_results(
   results_table,
   bam_file,
   num_results = 10,
   num_reads_per_result = 100,
   hit_list = 10,
   num_threads = 1,
   db_path,
   out_path,
   sample_name = NULL,
   quiet = quiet,
   NCBI_key = NULL
)
```

Arguments

results_table	A data.frame of the Metascope results
bam_file	A sorted bam file and index file, loaded with Rsamtools::bamFile
num_results	A number indicating number of Metascope results to blast
num_reads_per_	result
	A number indicating number of reads to blast per result

38

hit_list	A number of how many blast results to fetch for each read
num_threads	Number of threads if multithreading
db_path	Blast database path
out_path	Output directory to save csv files, including base name of files
<pre>sample_name</pre>	Character string, sample name for output files.
quiet	Logical, whether to print out more informative messages. Default is FALSE.
NCBI_key	(character) NCBI Entrez API key. optional. See taxize::use_entrez(). Due to the high number of requests made to NCBI, this function will be less prone to errors if you obtain an NCBI key.

Value

Creates and exports num_results number of csv files with blast results from local blast

rBLAST_single_result rBLAST_single_result

Description

rBLAST_single_result

Usage

```
rBLAST_single_result(
   results_table,
   bam_file,
   which_result,
   num_reads = 100,
   hit_list = 10,
   num_threads = 1,
   db_path,
   quiet = quiet,
   NCBI_key = NULL,
   bam_seqs
)
```

Arguments

results_table	A dataframe of the Metascope results
bam_file	A sorted bam file and index file, loaded with Rsamtools::bamFile
which_result	Index in results_table for which result to Blast search
num_reads	Number of reads to blast per result
hit_list	Number of how many blast results to fetch per read
num_threads	Number of threads if multithreading

db_path	Blast database path
quiet	Logical, whether to print out more informative messages. Default is FALSE.
NCBI_key	(character) NCBI Entrez API key. optional. See taxize::use_entrez(). Due to the high number of requests made to NCBI, this function will be less prone to errors if you obtain an NCBI key.
bam_seqs	A list of the sequence IDs from the bam file

Value

Returns a dataframe of blast results for a metascope result

remove_matches Helper function to remove reads matched to filter libraries

Description

Using the filter_host() function, we align our sequencing sample to all filter libraries of interest. The remove_matches() function allows for removal of any target reads that are also aligned to filter libraries.

Usage

```
remove_matches(
   reads_bam,
   read_names,
   output,
   YS,
   threads,
   aligner,
   make_bam,
   quiet
)
```

Arguments

erence library. Likely, the output from running an instance of align_target().
read_names A list of target query names from reads_bam that have also aligned to a filter reference library. Each list element should be a vector of read names.
output The name of the .bam or .csv.gz file that to which the filtered alignments will be written.
YS yieldSize, an integer. The number of alignments to be read in from the bam file at once for chunked functions. Default is 100000.
threads The number of threads to be used in filtering the bam file. Default is 1.
aligner The aligner which was used to create the bam file.

taxid_to_name

make_bam	Logical, whether to also output a bam file with host reads filtered out. A .csv.gz
	file will be created instead if FALSE. Creating a bam file is costly on resources
	over creating a compressed csv file with only relevant information, so default is
	FALSE.
quiet	Turns off most messages. Default is TRUE.

Details

This function is not intended for direct use.

Value

Depending on input make_bam, either the name of a filtered, sorted .bam file written to the user's current working directory, or an RDS file containing a data frame of only requisite information to run metascope_id().

taxid_to_name Converts NCBI taxonomy ID to scientific name

Description

Converts NCBI taxonomy ID to scientific name

Usage

```
taxid_to_name(taxids, NCBI_key = NULL)
```

Arguments

taxids	List of NCBI taxids to convert to scientific name
NCBI_key	(character) NCBI Entrez API key. optional. See taxize::use_entrez(). Due to the high number of requests made to NCBI, this function will be less prone to errors if you obtain an NCBI key.

Value

Returns a dataframe of blast results for a metascope result

Index

* datasets align_details, 3 bt2_16S_params, 10 bt2_missing_params, 10 bt2_regular_params, 11 * internal MetaScope-package, 3 align_details, 3 align_target, 4 align_target_bowtie, 6 bam_reheader_R, 8 blast_result_metrics,9 bt2_16S_params, 10 bt2_missing_params, 10 bt2_regular_params, 11 check_samtools_exists, 12 combined_header, 12 convert_animalcules, 13 convert_animalcules_patho, 15 convert_animalcules_silva, 16 $\texttt{count_matches}, 18$ demultiplex, 19 download_refseq, 20 extract_reads, 21 filter_host, 23 filter_host_bowtie, 25 filter_unmapped_reads, 28 get_children, 28 get_seqs, 29 locations, 30merge_bam_files, 30 MetaScope (MetaScope-package), 3 MetaScope-package, 3
metascope_blast, 31
metascope_id, 33
mk_bowtie_index, 36
mk_subread_index, 37

rBlast_results, 38
rBLAST_single_result, 39
remove_matches, 40

taxid_to_name, 41